I'm not robot
reCAPTCHA
Continue

Ducane furnace troubleshooting guide 2020 printable calendar template

FUR-16 American Standard 80 Single Stage (AUE1, ADE1)... (BTUH) H W D (lbs.) Rating MCA* Fuse* E Power Supply LI N 18,000 23,000 29,000 35,000 41,000 47,000 57, Line Size (in) OD OD Gas Liq /4 /4 3 /4 3 / N 1 For coastal applications where units are installed within one (1) mile of salt water, epoxy coated models are available for order. Airflow Directions: Downflow models when placed in horizontal position provide left to right airflow. Comparative Enthalpy Economizer Kit...EAC180A* - EAC300A* w/low Leak Economizer & FDD BAYCURB027B... M124X04CF Consecutive order of production...last Five digits... TAYBASETAMA...Downflow Sub-Base Kit...A-C... Single stage cool ½ Single stage gas... Focus Pro 3 Heat/ 2 Cool PHASED OUT Programmable Comfort Controls for ReliaTel Units ASYSTAT090A Large, Clear Display with Backlighting Current temperature, set temperature and time are easy-toread and all are displayed on the main screen. Fan Failure Switch... Direct/Non-Direct * Information subject to change. EXISTING CURB NEW UNIT 4TC/WC/YC****A USE BAYADAP0**A BAYCURB030,38A BAYCURB030,38A BAYCURB033A BAYCURB033A BAYCURB034A It is the designer/engineer/installer s responsibility to review product specifications and technical literature to insure optimal performance and compliance to codes. Single Setpoint for 3-25 Tons Electric/Electric and Gas/Electric Systems Can be used with Remote Sensor (ASYSTAT669) Light Commercial Comfort Controls/Zone Sensors ASYSTAT107A Manual Changeover ASYSTAT108A Automatic Changeover ASYSTAT109A Automatic Changeover ASYSTAT709A/707A LCD Digital Display Zone Sensor 4-6 wires required. 2 Do not use with programmable thermostats. 0 Return Air Smoke Detector9...A Supply Air Smoke Detector...B Supply and Return Air Smoke Detectors9...C Plenum Smoke Detector...D 25 System Monitoring Controls No Monitoring Control... Registered limited lifetime heat exchanger warranty and 10-year on all other functional parts (Residential Use)1... Reuseable Pallet for Condenser End Unit Lifting...All Foundation Ton Units BAYCOSW300A... 9 The manual outside air damper will ship factory supplied within the unit, but must be field installed. Any such damage must be reported and claims made against the transportation company immediately. R-22 TXV conversion kit BAYATXV6161B... 1 Compatible with all In-Wall GE and Jasco Switches, Dimmers and Fan Controls Required for use with 3- and 4-way wiring Interchangeable paddles; white and light almond included in package (wall plate not included) Easy to install; includes space-saving screw terminals Application: Protocol: Z-Wave Power: 120 VAC, 60Hz Max Load: 1000W, 2-gang 800W and 3-gang 600W Operating Temperature: 0 C-40 C Indoor Use Only Specifications subject to change without notice Warranty 1-Year Limited Warranty Application: Protocol: Z-Wave Power: 120 VAC, 60Hz Max Load: 960W Incandescent, 1/2 HP Motor, 1800W (15A) Resistive Operating Temperature: 0 C-40 C Indoor Use Only Specifications subject to change without notice Warranty 1-Year Limited Warranty Application: Protocol: Z-Wave Power: 120 VAC, 60Hz Operating Temperature: 0 C-40 C Indoor Use Only Specifications subject to change without notice Warranty 1-Year Limited Warranty CHS-6 1 Requires internet service and Nexia smart home system registration.25 GE In-Wall Fan Control Switch Linear In-Wall Switch JASCO In-Wall Smart Motion Switch Nexia Compatible Products Fan Control Switch SKU: Turn fan on/off and control up to three speed levels remotely from Nexia app Interchangeable paddles; white and light almond included in package (wall plate not included) Easy to install; includes space-saving screw terminals and neutral jumper wires Automate with Nexia based on temperature (with Z-Wave temperature sensor) or time of day Trigger actions from other smart products LED indicator glows in dark On/Off Switch SKU: Turn any light on/off remotely from Nexia app 1 Includes decor wall plate Serves as Z-Wave repeater Automate with Nexia based on time of day Trigger actions from other smart products LED indicator glows in dark In-Wall Smart Motion Switch SKU: Indoor in-wall Z-Wave light switch with integrated motion sensor Wirelessly trigger scenes/automations and send alerts to smartphone or tablet when motion detection has turned lights on or off. 3-way vent option on downflow models (top,right or left) (downflow models only) gauge aluminized steel heat exchanger volt secondary fuse... AC/IN-11 Wind Shields... The Nexia Bridge is Dimensions: Product: 5.9"w x 3.47"h x.95"d Display: 3.8"w x 2.3"h 1 Requires internet service and Nexia smart home system registration. Gold plated sensing probes for corrosion resistance Sensor floats and continues to alert for up to 24 hours. LPC-25207 Foundation Packaged Cooling Tons Heaters Table LPC-26-A Foundation - R-410A - Field Installed Accessories Model Power kw Nominal No. Number Supply Rating BTUH Stages Used With BAYHTFA318A /3/ /18 46,100/64,400 1 EAC180A3* BAYHTFA336A /3/60 27/36 92,200/122,900 2 EAC180A3*, EAC210A3* BAYHTFB336A /3/60 27/36 92,200/122,900 2 EAC240A3*, EAC300A3* BAYHTFA354A /3/ /54 138,200/184,300 2 EAC180A3*, EAC210A3* BAYHTFB354A /3/ /54 138,200/184,300 2 EAC240A3*, EAC300A3* BAYHTFA372A /3/60 54/72 184,300/245,700 2 EAC210A3* BAYHTFB372A /3/60 54/72 184,300/245,700 2 EAC240A3*, EAC300A3* Light Commercial Packaged Cooling BAYHTFA418A 460/3/ ,000 1 EAC180A4* BAYHTFA436A 460/3/ ,900 2 EAC180A4*, EAC210A4* BAYHTFB436A 460/3/ ,900 2 EAC240A4*, EAC400A4* BAYHTFA454A 460/3/ ,300 2 EAC180A4*, EAC210A4* BAYHTFB454A 460/3/ ,300 2 EAC240A4*, EAC400A4* BAYHTFA472A 460/3/ ,700 2 EAC210A4* BAYHTFB472A 460/3/ ,700 2 EAC240A4*, EAC400A4* BAYHTFAW18A 575/3/ ,000 1 EAC180AW* BAYHTFAW36A 575/3/ ,900 2 EAC180AW*, EAC210AW* BAYHTFBW36A 575/3/ ,900 2 EAC240AW*, EACW00AW* BAYHTFAW54A 575/3/ ,300 2 EAC180AW*, EAC210AW* BAYHTFBW54A 575/3/ ,300 2 EAC240AW*, EACW00AW* BAYHTFAW72A 575/3/ ,700 2 EAC210AW* BAYHTFBW72A 575/3/ ,700 2 EAC240AW*, EACW00AW* Information subject to change. 4A6H4018G1000A 208/230/1/60 18, / 4 3 / 8 4A6H4024G1000A 208/230/1/60 24, / 4 3 / 8 4A6H4030G1000A 208/230/1/60 29, / 4 3 / 8 4A6H4036G1000A 208/230/1/60 34, / 8 3 / 8 4A6H4042G1000A 208/230/1/60 41, / 8 3 / 8 4A6H4048G1000A 208/230/1/60 48, / 8 3 / 8 4A6H4060G1000A 208/230/1/60 58, / 8 3 / 8 * Information subject to change. 0 Through the Base Electricq... R-410A R-410A Glossy corrosion resistant finish High pressure switch Low pressure switch Liquid line filter drier - factory supplied for Field Install year basic limited warranty on compressor, 1-year on outdoor coil & all other functional parts (Commercial Use) year registered limited warranty on compressor, outdoor coil & 5-year on all other functional parts (Residential Use) Extended warranties available Table SH-10-B Optional Accessories Model Number Description Shipping Weight AY28X084...Evaporator Defrost Control HP BAYCCHT301RES...Crankcase Heater Kit (Scroll) ½-5 BAYCCHT302RES...Crankcase Heater Kit (Scroll) BAYECMT004...Extreme Conditions Mounting Kit (Base 4) BAYISLT101...Rubber Isolators BAYLEGS007...Snow Legs - 7" High (Black) BAYLEGS004...Snow Legs - 4" High (Black) BAYLOAM107A...Low Ambient Kit BAYSDEN003...Small Scroll Compressor Enclosures BAYSDEN004...Large Scroll Compressor Enclosures ,5 3½-5 BAYSEAC001...Seacoast Kit TAYASCT501A23...Anti-short cycle timer PAI Heresite Spraypaint AAYSVPANL0032AA...Service Valve Panel Cover Kit ½ AAYSVPANL0044AA...Service Valve Panel Cover Kit AAYSVPANL0046AA...Service Valve Panel Cover Kit AAYSVPANL3343AA...Service Valve Panel Cover Kit BAYAWGR All Weather Top - Fits unit base size of (W x D) of 37" X 34"... (lbs.) Rating MCA* Fuse* 4A6H7024A1000D 4A6H7024B1000A 4A6H7036B1000D 4A6H7048A1000D 4A6H7060A1000D 208/230/1/60 208/230/1/60 208/230/1/60 208/230/1/60 208/230/1/60 24, PHASING OUT Q ,000 COMING SOON , , , Line Size (in) OD OD Gas Liq. This model ODT gives a temperature range for 44 F. Do not order the return air smoke detectors when using this type of accessory. 1½-2½ BAYATXV4248B... OUT BAYINSKT235A6...Sound Insulation Kit 17.5" through 23.5" Cabinet...A-C... 4 Clogged Filter Switch and Discharge Air SensingTube... Cap Cooling (BTUH) Power Supply46 AccuComfort Variable Speed Heat Pump Single Phase 2-5 Tons Split System Heat Pumps Platinum 20 Platinum 19 Platinum 18 Table SH-4-A Features (4A6V0) (4A6L9) (4A6V8) SEER up to HSPF up to Duration compressor Number of stages... FUR-18 Special Use Furnace Accessories... Choose Precise Relative Humidity % Settings based on your needs and outdoor conditions. Field convertible to 460/3/60. Lite Port /Stored diagnostics... Comparative Enthalpy Kit... 1 Unit Mounted Circuit Breakerq Convenience Outlet No Convenience Outlet... Variable Variable Comfort-R mode approved AccuLink system DuraBase base, fast complete drain, weatherproof Easy-Sess cabinet, service access Spine Fin coil Compressor sound enclosure Compressor sump heat Factory supplied charge... Accessories/Information AC/IN-5153 Refrigerant HFC 410A (R-410A) Tables contain no allowances for vertical lift! Table AC/IN-6-A Liquid Line Selection Table for R-410A Single Speed Systems Maximum Allowable Liquid Line Pressure Drop... (mm): 2.0" (51)w x 3.25" (83)h x.6 (15)d Storage Temperature: -40 to 140 F (-40 to 65 C) Finish: White SENSATIVE Sensative Strips Door/ Window Sensor Sensative Strips Door/Window Sensor SKU: Ultra thin design (less than 3 mm) for invisible mounting between most doors/windows and their frames Simple to set up with the included adhesive backing Indoor or outdoor use Not for use on metal surfaces which may block the signal Long lasting non-replaceable battery (10 year life) Application: Protocol: Z-Wave Manufacturer: Sensative Application: Indoor Range: 130 ft. From Dwg. Magnetic Range: 0.6" Operating Temperature: -4 F-140 F (-20 C-60 C) Dimensions: Sensor: 7.7 l x 0.6"w x 0.12"d Magnet: 1.2"l x 0.43"w x 0.04"d Weight: 2 oz. Service Valve Panel Cover Kit ½-2 1½-2½ AAYSVPANL0032AA... Front return only... Fuse* OD Gas OD Liq. 2AYTXVH3G2436A...R-22 TXV conversion kit 1-1/2 to 3 ton... PK-4135 Packaged Hybrid/Dual Fuel Convertible 2-5 Tons 4DCZ6 4DCY4 Table PK-5-A Features SEER up to HSPF up to Exclusive Duration high efficiency compressor with internal overload protection... Meets requirements for 1% or less air leakage... The indicator has been factory calibrated and should not normally require adjustment. E Clogged Filter Switch, Discharge Air Sensing Tube and Condensate Drain Pan Overflow Switch... 0 Unit Mounted Non-Fused Disconnect Unit Mounted Circuit Breaker Convenience Outlet No Convenience Outlet... Draw through design... BAYLOAM105A Low Ambient Control Kit BAYOSAH001A Manual Fresh Air Damper BAYOSAH002A Manual Fresh Air Damper ½-5 3½-5 3½-5 BAYQSTK300A Start Kit... F.D.B. F.D.B. F.D.B. Grains/lb. Bottom Panel (upflow models only)... Please verify with ordering system for availability.220 Packaged Heat Pump with ReliaTel Controls 12½-20 Tons Zone Sensors Table LPH-13-A Zone Sensors Model Number Description Used With ASYSTAT107A Single Setpoint Manual Changeover WC* ASYSTAT109A Dual Setpoint Manual or Automatic Changeover WC* ASYSTAT111A Remote Room Sensor ASYSTAT777A ASYSTAT777A Programmable Night Setback WC* BAYMTPL110A Retrofit Wall Cover Plate Kit 7.25" x 6.0" ASYSTAT777A BAYSENS924A1 Title 24 Zone Sensor All 1 Must be used with ReliaTel Control and BCI Communications Interface LPH-13 Light Commercial Packaged Heat Pumps221 Packaged Heat Pump with ReliaTel Controls 12½-20 Tons Accessories Table LPH-14-A Field Installed Accessories Model Number Description Used With BAYABRD002B6... C Discharge Air Sensing8 and Condensate Drain Pan Overflow Switch... Works with both well or city water. t Demand Control Ventilation Option includes wiring only. (lbs.) (Cool) (Heat) MCA* Fuse* Table SH-3-B - Platinum 19 R-410A Side Discharge Variable Speed Heat Pump (50-100% capacity) with AccuLink 2 Nom. Five-Year Standard Warranty includes all functional Parts. Accuracy +/ 1.5 F over 32 F to 100 F Display Range -40 F to 140 F ZZSENSAL0400AA Indoor Wired Sensor for use with AZON1050AC, AZONE950AC, ACONT850AC, ACONT824AS, ACONT624AS, ACONT402AN, BAY24VRPAC52D*. A Service Sequence First Sequence (Factory Supplied)..., 14 Fresh Air Selection No Fresh Air % Manual Outside Air Damper0... Silicon Nitride hot surface igniter... PHASING OUT FUR-1893 Platinum 80, Gold 80v, Gold 80, Silver 80h, Silver 80, and American Standard 80 Convertible Gas Furnaces AUD2-ACV/ADD2-ACV AUD2-9V/ 2 Stage ADD2-9V 2-Stg. Light Commercial Split System Heat Pumps LSH-2168 Split System Heat Pumps Accessories Three Phase 6-20 Tons, R-410A Table LSH-3-A TWA Accessories Model LSH-3 Used With Coil (Hail/Vandal) Guard BAYGARD058* TWA072**A, TWA090**A BAYGARD059* TWA072**D, TWA090**D BAYGARD060* TWA120 BAYGARD061* TWA180, TWA240 Rubber Isolators BAYISLT005* (black) TWA072, TWA090, TWA120 BAYISLT009* (red) TWA180 BAYISLT010* (green) TWA240 Steel Spring Isolators BAYISLT023* (red) TWA072, TWA090, TWA120 BAYISLT024* (black) TWA180 BAYISLT025* (yellow) TWA240 Service Valve Kit BAYVALV001A TWA0724*A, TWA1204*A BAYVALV002A TWA0904*A BAYVALV003A TWA0724*D, TWA0904*D, TWA1204*D BAYVALV006A TWA01804*D, TWA2404*D Low Ambient On/Off Fan Control (External mount, small cabinets)1 2 3 BAYLOAMU01* (External Mount, small cabinets)4 (all voltages) TWA072**A, TWA090**A BAYLOAMU02* (Internal mount, large cabinets) (all voltages) TWA120, TWA180, TWA240 Head Pressure Control2 BAYLOAM335* (V, 0.5 HP, Hi-Eff Motor) TWA072*3A/D, TWA090*3A/D BAYLOAM336* (V, 1 HP, Hi-Eff Motor) TWA120*3A/D, TWA180*3D, TWA240*3D BAYLOAM435*(V, 0.5HP Hi-Eff Motor) TWA072*4A/D, TWA090*4A/D BAYLOAM436*(V, 1 HP Hi-Eff Motor) TWA120*4A/D, TWA180*4D, TWA240*4D BAYLOAMW36* (575V, 1 HP, Hi-Eff Motor) TWA120*WA/D, TWA180*WD, TWA240*WD Transducer Kit for Head Pressure Control (BAYLOAM335, 336, 435, 436, W36) BAYLOTR001*5 TWA072**D, TWA090**D, TWA120**D Trane Communication (3/4 Communications Interface)6 BAYICSI003* All Models LonTalk Communications Interface6 BAYLTCI002* All Models 1 Cycles fan on/off (no modulating). Optional Remote Sensor When using the optional remote sensor (BAYSENS077A), it should be located in the space that is to be controlled. 2 Frostat and Crankcase Heater Smoke Detector5w No Smoke Detector... 0 Manual Damper... Direct drive, multi-speed (PSC) blower motor... R 11 Minor Design Sequence Service Sequence 14 Fresh Air Selection No Fresh Air... N o V 2. 3 2-Stage cooling control required when using economizer. 5 Direct drive variable speed motor is an ECM constant airflow blower motor. AC/IN-12 TOC-36 Contents - Light Commercial Model Nomenclature...LTOC-17 Split System Cooling Three Phase, 6-25 Tons, R-410A (TTA)...LSC-1 Three Phase, 6-25 Tons, R-22 (TTA)...LSC-2 Three Phase, 6-25 Tons, R-410A (TTA)...LSC-3 ReliaTel Controls, 6-25 Tons - Protection/Operation Timings and Features...LSC-6 Split System Heat Pumps Three Phase, 6-20 Tons, R-410A (TWA)...LSH-1 Three Phase, Tons, R-22 (TWA)...LSH-2 ReliaTel Controls, 6-20 Tons - Protection/Operation Timings and Features...LSH-5 Air Handlers/Heaters Single Phase 5-10 Tons (TWE)...LAH-1 Three Phase 5-25 Tons (TWE)...LAH-1 Comfort Controls/Zone Sensors Non-Programmable for ReliaTel Units...LCCZS-1 Programmable for ReliaTel Units...LCCZS-1 Zone Sensor Unit Installation...LCCZS-3 Micro Control Zone Sensors...LCCZS-4 Electronic Programmable Zone Sensors for ReliaTel Units...LCCZS-5 Integrated Comfort Systems Sensors for ReliaTel Units...LCCZS-5 Packaged Cooling Convertible, 3-10 Tons Features...LPC-1 Convertible, 3-5 Tons, R-410A (THC, TSC)...LPC-2 Convertible, 6-10 Tons, R-410A (THC, TSC)...LPC-3 Convertible, 3-10 Tons Model Digit Numbers...LPC-4 Convertible, 3-5 Tons, R-410A Electric Heaters...LPC-6 Convertible, 6-10 Tons, R-410A Electric Heaters...LPC-7 Convertible, 3-10 Tons Accessories...LPC-9 Convertible, 3-10 Tons Zone Sensors/Thermostats...LPC-11 ReliaTel Controls (Packaged Unit Protection/Operation Timings & Features)...LPC-12 ReliaTel Controls (Operation with an Electromechanical Thermostat)...LPC-13 Packaged Cooling with ReliaTel Controls, 12½-25 Tons, R-410A (T*D-G/T*H-G)... 2½-5 AAYSVPANL3343AA...Service Valve Panel Cover Kit ½-2 AAYSVPANL0044AA...Service Valve Panel Cover Kit ½-3 AAYSVPANL0046AA...Service Valve Panel Cover Kit ½-5 PAI Heresite Spraypaint BRK Wall Mount Kit BAYAWGR All Weather Top - Fits unit base size of (W x D) of 37" X 34" BAYAWGR All Weather Top - Fits unit base size of (W x D) of 33" X 30" Comfort Controls See Comfort Controls/Zone Sensors Section 1 Registered Limited Warranty terms are available when you register within 60 days of installation. 3 Units having steam of hot water coils applied vertically or horizontally check IOM for proper Isolator kit selection. Cap Cooling (BTUH) Power Supply36 AccuComfort Variable Speed Cooling Single Phase 2-5 Tons Split System Cooling Platinum 20 Platinum 18 Table SC-2-A Features (4A7V0) (4A7V8) SEER up to Duration compressor Number of stages... Direct drive, variable speed ECM blower motor**... 2 Information subject to change. Information subject to change. dry air Excess Latent Capacity Make up of System x % Run Time 23. EXISTING CURB NEW UNIT 4WCY*A USE BAYADAP0**A BAYCURB030,38A BAYCURB030,38A BAYCURB033A BAYCURB033A BAYCURB034A It is the designer/engineer/installer s responsibility to review product specifications and technical literature to insure optimal performance and compliance to codes. 3 Table AC/IN-8-B Line Sizes VSPD Side Discharge Rated Line SIZES MODEL RATED LINE SERVICE SIZE VALVE CON- NECTION SIZE HP 4A6L9 Vapor Line Liquid Line Vapor Line Liquid Line HP 024 5" (a) 3" 5" 3" HP 036 3/4" (a) 3" 3/4" 3" HP 049 7" (a) 3" 7" 3" HP 060 7"(a)(b) 3" 7" 3" (a) The maximum length of refrigerant lines from outdoor to indoor unit must NOT exceed 150 feet. 4A6C7036A3000A 208/230/3/60 36, ¾ 3 4A6C7048A3000A 208/230/3/60 46, A6C7060A3000A 208/230/3/60 58, Gold 17 (Two Stage) 3-Phase 4A6C7036A4000A 460/3/60 36, ¾ 3 4A6C7048A4000A 460/3/60 46, A6C7060A4000A 460/3/60 58, Silver 14 (Single Stage) 3-Phase Table SH-9-B Silver 14 3-Phase R-410A Split System Single Stage Heat Pump - Three Phase Nom. Easy case attachment to furnace... LPC-14196 Packaged Cooling with ReliaTel Controls 12½-25 Tons (Model Digit Numbers) Digit Description Order Number 1 Unit Type Packaged Cooling, Electric Heat... All the Time In No Time. Electric Heaters with polarized plug connections (sold as accessory)... 4 These models comply with California 40ng/J Low NOx regulations. Sets cooling setpoint up a minimum of 7 F, sets heating setpoint back a minimum of 7 F, forces outside air damper (if present) minimum position to zero, and forces fan operation to automatic. N o = CFM o (60 min./hr.) V Accessories/Information Total Heat (H T) Sensible Heat (H S) Latent Heat (H L) Entering Air Temperature (T 1) (Mixed Air) Leaving Air D.B. Temperature (T 2) Required Airflow Enthalpy Leaving Air (h 2) Leaving Air W.B. Temperature Heat Required to Evaporate Water Vapor Added to Ventilation Air Humidification Requirements CFM T CFM o N T N o V H T H S H L * h 1 * h 2 T 1 T 2 T adp t 1 t 2 W 1 W 2 W 3 W o = = =

Exchanger Z = High Heat, Stainless Steel Heat Exchanger Digit 11 Minor Design Sequence A = First Sequencey Digit 12,13 Service Sequence **Factory Assigned Digit 14 Fresh Air Selection 0 = No Fresh Air A = Manual Outside Air Damper 0-50%2 B = Motorized Outside Air Damper 0-50% C = Economizer, Dry Bulb 0-100% without Barometric Relief5 D = Economizer, Dry Bulb 0-100% with Barometric Relief5 E = Economizer, Reference Enthalpy 0-100% without Barometric Relief5 F = Economizer, Reference Enthalpy 0-100% with Barometric Relief5 G = Economizer, Comparative Enthalpy 0-100% without Barometric Relief5 H = Economizer, Comparative Enthalpy 0-100% with Barometric Relief5 K = Low Leak Economizer, Dry Bulb with Barometric Relief M = Low Leak Economizer, Comparative Enthalpy with Barometric Relief P = Low Leak Economizer, Reference Enthalpy with Barometric Relief 1 Standard on all variable stage units. 7 Mounts inside air filter channel on air handler. Currently, the minimum clearance between a wood or suitable grounding material type fence requires minimum 3 feet. Easy Mounting Flexibility to your existing duct work or can be remotely mounted. 1 Registered Limited Warranty terms are available when you register within 60 days of installation. Single Setpoint for W- Heat Pump Systems (3-20 Tons) Can be used with Remote Sensor (ASYSTAT669) 5 wires required. BAYRETFLGCA...Return Duct Flange C...C... TASB175SB24...Plenum Stand with Integrated Sound Baffle A...A... All BAYECON089-92A BAYFRST003A... AC/IN-12160 Split System Cooling Three Phase 6-25 Tons, R-410A ReliaTel controls option (1) Scroll compressor (TTA A) (2) Scroll compressors (TTA D) with independent refrigerant circuits Single point power Compressor motor overload protection Compressor discharge temperature limit switch TTA 6-25 Tons Control transformer High and low pressure cut-out switches Liquid line filter drier, factory installed Electrical phase reversal protection Model Number Description Cooling Condenser Digit 1 3 Unit Function TTA = Split System Cooling Digit 4 6 Tonnage 072 = 6 Tons (60Hz) 090 = 7.5 Tons (60Hz) 120 = 10 Tons (60Hz) 150 = 12.5 Tons (60Hz) 180 = 15 Tons (60Hz) 240 = 20 Tons (60Hz) 300 = 25 Tons (60Hz) Digit 7 Refrigerant 4 = R-410A Digit 8 Voltage 3 = VAC - 3 PH (60Hz) 4 = 460VAC - 3 PH (60Hz) W = 575VAC - 3 PH (60Hz) K = 380VAC - 3 PH (60Hz) Digit 9 Refrigeration Circuit/Stage A = 1 Compressor/1 Line/1 Stage (Single) C = 2 Compressors/1 Line/2 Stage (Manifold) D = 2 Compressors/2 Line/2 Stage (Duals) Digit 10 Major Design Sequence A = Rev A Digit 11 Minor Design Sequence B = Rev B Digit Service Digits 00 = 00 Digit 14 Efficiency Generation A = Generation A Digit 15 Controls E = Electromechanical R = ReliaTel 1 Sound rating shown is tested in accordance with ARI Standard 270 or 370. Not compatible with openers using a proprietary communication protocol to the wall switch such as Genie Series II and the Chamberlain/Liftmaster MyQ system. D 19 Disconnect Switch/Circuit Breaker No Disconnect/circuit break... 4,5 3½-5 3½-5 3½-5 1 Relay required with economizer on all heat pump applications. 3 HACR type circuit breaker per NEC. BAYQACB010A adapts Voyager BAYCURB022A roof curb to accept Precedent 3-5 ton unit. Smooth cleanable interior design... 0 Econ Dry Bulb w/ Barometric Relief... B Fan Failure Switch8 and Condensate Drain Pan Overflow Switch... Reference Enthalpy Kit...All BAYECON089-92A BAYENTH008A... Example a 2AYTXVH3D1830A is an R-22 valve. Non-bleed expansion valves on indoor coil.... time delay programming... H T = CFM T x 4.5 x (h 2 h 1) = Btuh 8. Adding accessories to your Nexia system may require a monthly subscription for remote access via most web-enabled smartphones, tablets and computers.111 AccuLink Communicating Connected Controls Tue, Dec 16 4:19 PM Indoor Temp Indoor Humidity System Idle Following Schedule Home Menu Auto System Mode 16 % Circulate Fan Mode Auto Air Cleaner PLATINUM 850 ACONT850AC52UA $ Away Status ACONT850AC52UA Nexia Z-Wave Bridge Connect over 200 Z-Wave devices12 WiFi or Ethernet connection Control from a smartphone, tablet, or computer " diagonal color touchscreen Compatible with AccuLink communicating systems (variable speed and two stage) Compatible with conventional 24 volt HVAC, heating, heat pump, and dual fuel systems when used with accessory relay panel model BAY24VRPAC52DC 7 Day programmable with up to four schedules per day Five day weather forecast, weather radar, and weather alerts 1 Indoor relative humidity display Test modes and alert diagnostics Nexia Diagnostics 1 Over-the-air software upgrades 1 Local software upgrade option Silver color Wall cover plate BAYCOVR800A Limited Warranty: 5 yr. Note: S8X1A026M2, S8X1A040M3, S8X1B040M2, and S8X2A040M3 require new orifices included in kit. Clogged Filter Switch (MERV 13)... Refer to the appropriate unit installation manual for interconnecting wiring instructions. 9 Field installed accessory requires economizer. 5 = Better, Entry Level High Effy., Multi-Speed 7 = Best, Retail Replacement High Effy., Variable-Speed 8 = Best, Retail Ultimate High Effy., Variable-Speed 9 = Best, Comm/24V Variable-Speed G = Best, Geothermal Major Design Change No Descriptor 0 = Air Handler / Coil Size (Footprint) A = 17.5 x 21.8 B = 21.3 x 21.8 C = 23.5 x 21.8 Cooling Size: Air Handler or Coil 0-9 = AH Coil BTU s (18, 24, 30, 36, 42, 48, 60) Airflow Type & Capability S = Standard Effy PSC, nom. TSC , THC036, THC037 BAYDMPR056B % Manual Outside Air Damper... A Standard Panels & 2" Pleated Filters MERV 8... BAYSUPFLGCA...Supply Duct Flange C... Table FUR-2-C High Altitude Pressure Switch S9V2-VS 90% Furnaces Model Shipping Number Description Used With Weight BAYHALT250 2 Switches S9V2B040U3VSA 2 BAYHALT251 2 Switches S9V2B060U3VSA 2 BAYHALT252 2 Switches S9V2B080U3VSA, S9V2B080D3VSA 2 S9V2C100D4VSA BAYHALT253 2 Switches S9V2C100U4VSA 2 BAYHALT254 2 Switches S9V2D120U5VSA 2 FUR-277 Convertible Gas Furnaces S9V2-VS S9V2 S9X2 Table FUR-3-A Features Variable Speed Variable Speed Multi-Speed Comfort-R enhanced mode (cooling)... Non-Programmable Zone Sensor with a digital display PHASED OUT ASYSTAT709A - Cool/Gas ASYSTAT707A - Heat Pumps Zone Sensors must be used with Micro Control units. registered CHS-3 Application: AccuComfort Variable Speed AccuLink II Two Stage Systems AccuLink II Zoning Systems AccuComfort Variable speed outdoor cooling or heat pump unit combined with S-Series noncommunicating variable speed furnace and "C" model Relay Panel Relay panel (BAY24VRP52DC) is required when applied with conventional systems (Gas Electric, Heat Pump, Dual Fuel, Boilers - forced air only) Relay Panel Supports: - Up to 5 stages heat, 2 stages cool - Connections for Remote indoor and outdoor temperature sensors - 3 Dry Auxiliary Contacts to control whole house humidifier, dehumidifier, or ventilation system Remote wired indoor temperature sensor (optional) ZZSENSAL0400AA Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AW00MA Remote wired outdoor temperature sensor (optional) BAYSEN01ATEMPA Dimensions: Product: 7.2"w x 4.5"h x 1.2"d Display: 6.1"w x 3.3"h Application: AccuLink communicating systems (variable speed and two stage) Variable speed outdoor cooling combined with S-Series noncommunicating variable speed furnace and "C" model Relay Panel Conventional gas/electric, heat pump, dual fuel systems, or boiler systems (forced air only) with use of relay panel model BAY24VRPAC52DB. BAYFRT5LVPNL26A...Louver Panel 26" - Quantity 5... Heat Pump Control Kit...Gas, LP., Oil and Electric Furnaces TAYSTAT250B... 2 Applicable for all furnaces with 35 VA or larger low voltage transformer (separate high voltage power not required). Light Commercial Comfort Controls/Zone Sensors Installation: 18-HD60D41 Source: Clarksville LCCZS-3180 Micro Control Zone Sensors ASYSTAT106A Manual Changeover 4 wires required. dry air F.W.B. Btuh Lbs. Multi-port in shot burners... Ability to Select Multiple Days Allows easy customizing for unique schedules. Swept-blade outdoor fan for quiet operation... dehumidification models). Side return duct starter tabs... B Digit Description Order Number 21 Communications Optionsw No Communications Interface... See Installer's Guide for complete instructions. Crankcase Heater Kit (Scroll) ½-3 1½-3 BAYECMT Extreme Conditions Mounting Kit (Base 2/3) ½-3 1½-4 BAYECMT Extreme Conditions Mounting Kit (Base 4) ½-5 43,49,60 BAYISLT Rubber Isolators BAYKSKT Start Kit ½ BAYLEGS Snow Legs - 7" High (Black) BAYLEGS Snow Legs - 4" High (Black) BAYLOAM Low Ambient Kit BAYSDEN Small Scroll Compressor Enclosures ½-3 1½-3 BAYSDEN Small Scroll Compressor Enclosures ½-5 3½-5 BAYSEAC Seacoast Kit TAYASCT501A23... of moisture removal Exclusive XT coil technology means higher efficiency humidity removal rates than standard units All Units are Energy Star rated All units come with optional ventilation capability to meet ASHRAE 62.2 Ventilation requirements Units can be ducted to and wired to operate with HVAC system or can used independently of HVAC system with internal blower and wired control Units come standard with MERV 11 filter for improved indoor air quality 5 Year Unit Replacement Warranty for Refrigeration Circuit Failures (Registered Warranty) EDHUM1551H1MDAA Table IAQ-11-A Specifications: Envirowise Whole Home Dehumidifiers with Optional Ventilation Dimensions- W" x H" x L" Model Number Description EDHUM70V1H1MDAA Ventilating Dehumidifier, pint category, 1800 sq' ft. Air Handler Downflow Sub-Bases "... w Precedent E cabinet to Precedent D cabinet (BAYCURB044 to BAYCURB043) e Precedent B cabinet to Precedent C cabinet (BAYCURB042 to BAYCURB043) Light Commercial Packaged Heat Pumps LPH-10218 Packaged Heat Pump with ReliaTel Controls 12½-20 Tons 12½ 20 Ton WSD Downflow 12½ 20 Ton WSH Horizontal EER up to 10.6 ReliaTel processor control features are listed on page LPC-13 Built-in anti-short cycle, time-delay relay and minimum on time controls 2" filters for 12½ - 20 ton units Liquid line drier Built-in fork lift holes Operating charge of R-410A Quick-Sess service panels slide in and out Scroll compressors Dedicated horizontal and downflow designs Single-side access Single point power for electric heat Complete line of optional electric heaters Internally enhanced coil tubing Low ambient to 0 F standard Colored and numbered wiring Common cabinet and accessories Cooling only and Gas/Electric Heat models Quick-adjust idler arm pulley 5-year limited compressor warranty (12½ 20 tons) Table LPH-11-A Standard ReliaTel Units (R-410A) Unit Power Supply Performance Cooling Dimensions (in.) Shipping Max Fuse Size or4 Downflow Tons Model No. Volts/Phase/Hz IEER Capacity (Btuh) H x W x L Weight (Ibs.) MCA5 Max Circuit Breaker Roofcurb 12 ½ WS*150E3R0B /3/ , x 84 3 /16 x / BAYCURB027B 15 WS*180E3R0B /3/ , x 84 3 /16 x / BAYCURB027B 20 WS*240E3R0B /3/ ,000 66¼ x 84 3 /16 x / BAYCURB027B 12 ½ WS*150E4R0B /3/ , x 84 3 /16 x / BAYCURB027B 15 WS*180E4R0B /3/ , x 84 3 /16 x / BAYCURB027B 20 WS*240E4R0B /3/ ,000 66¼ x 84 3 /16 x / BAYCURB027B 12 ½ WS*150EWR0B /3/ , x 84 3 /16 x / BAYCURB027B 15 WS*180EWR0B /3/ , x 84 3 /16 x / BAYCURB027B 20 WS*240EWR0B /3/ ,000 66¼ x 84 3 /16 x / BAYCURB027B Supply Return Supply Return Curb Size Roof Opening Tons Downflow W x L12 Downflow W x L12 Horizontal H x W12 Horizontal H x W12 H x W x L23 W x L /16 x 69 1 / /4 x /16 x 26 1 / /16 x 27 9 / /16 x 81 x / /2 x 81 1 Dimensions are in inches. All aluminum Spine Fin outdoor coil... D 25 System Monitoring Controls No Monitoring Controls... 2 Heat/2 Cool Commercial Vision Pro Light Commercial Comfort Controls/Zone Sensors LCCZS-1178 Programmable Comfort Controls for ReliaTel Units PHASED OUT ASYSTAT800A ASYSTAT800A Wall mounted remote space sensor For use with ASYSTAT090A, ASYSTAT092A, and ASYSTAT093A programmable thermostats PHASED OUT Light Commercial Comfort Controls/Zone Sensors LCCZS-2179 Zone Sensor Unit Installation The zone sensor provides the operator control and zone temperature sensing functions for use with electronic unit controls. Cleanable/reusable high velocity filters... Proportional sets corrective action proportional to deviation from setpoint. Compatible with variable speed and 2 speed outdoor models... For dimensional/outline drawings, please refer to Product Data. K 36 kw Electric Heat2... Horizontal Duct Conversion Kit...EAC180A* - EAC300A* BAYCARR001A... 4 Barometric Relief accessory installs in ductwork for horizontal configuration. Vortica blower with polarized plug connections and integrated slide deck for easy removal... Required for supply air tempering. ** Rated in accordance with AHRI Standard 275 COMING Q ALL WEATHER TOP ACCESSORY BAYAWGR Fits base sizes 33"x30" (WxD) BAYAWGR Fits base sizes 37"x34" (WxD) SH-3 Split System Heat Pumps Platinum 18 (Variable Speed) 24,200 35,000 47,000 54,500 Shipping Sound** Rating Weight Max. Economizer, Dry Bulb, Downflow...EAC180A* - EAC300A* BAYECON301A... Removable battery holder for fast, easy replacement. R-410A R-410A R-410A R-410A Composite Vortica indoor blower... R Gas Heat - High1... High Temperature Stat...WS*150E-240E BAYGARD045A6...Tool-less Hail Guard... 2 Economizer with Barometric Relief is for downfllow configured units only. D.B. CFM T Btu/lb. BAYFRT5LVPNL30A...Louver Panel 30" - Quantity 5... of torque Manual gear release Screw terminal blocks Table CCZS-15-A Specifications: Rectangular Dampers with Bottom Mount Actuator Uncrated Model Power Dimensions (in.) Number Supply Description H W ZDAMPBMMA0810A 24 VAC Rectangular-Bottom Mount Actuator 8 10 ZDAMPBMMA0812A 24 VAC Rectangular-Bottom Mount Actuator 8 12 ZDAMPBMMA0814A 24 VAC Rectangular-Bottom Mount Actuator 8 14 ZDAMPBMMA0816A 24 VAC Rectangular-Bottom Mount Actuator 8 16 ZDAMPBMMA0818A 24 VAC Rectangular-Bottom Mount Actuator 8 18 ZDAMPBMMA0820A 24 VAC Rectangular-Bottom Mount Actuator 8 20 ZDAMPBMMA0822A 24 VAC Rectangular-Bottom Mount Actuator 8 22 ZDAMPBMMA0824A 24 VAC Rectangular-Bottom Mount Actuator 8 24 ZDAMPBMMA0826A 24 VAC Rectangular-Bottom Mount Actuator 8 26 ZDAMPBMMA0828A 24 VAC Rectangular-Bottom Mount Actuator 8 28 ZDAMPBMMA0830A 24 VAC Rectangular-Bottom Mount Actuator 8 30 ZDAMPBMMA1012A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1014A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1016A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1018A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1020A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1022A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1024A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1026A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1028A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1030A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1214A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1216A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1218A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1220A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1222A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1224A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1226A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1228A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1230A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1416A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1418A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1420A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1422A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1424A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1426A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1428A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1430A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1618A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1620A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1622A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1624A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1626A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1628A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1630A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1820A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1822A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1824A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA1826A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA2022A 24 VAC Rectangular-Bottom Mount Actuator ZDAMPBMMA2024A 24 VAC Rectangular-Bottom Mount Actuator CCZS-15 97% leak proof rating Sturdy aluminum blades and frame Motor is always located on the second dimension of the model number, i.e ZDAMP*MMA1012A will have the motor mounted on the 12" dimension Comfort Controls/Zone Sensors122 Excellence Without Comprimise GEAR Supply OPEN PC PO COM 24 Volt Modulating Dampers Table CCZS-16-A Rectangular Damper Net Free Area B B1 A1 CLOSED Listed Size Wide A Actual Outside Size A Actual Inside Size A Listed Size High Act. 0 Frostat Smoke Detector Without Smoke Detector... TSH150F BAYECON092A... Any missing parts should be reported to your supplier at once and replaced with authorized parts only. BAYCURB026A/B to BAYCURB027A/B BAYSERV001A...Selective Resistance Service Tester... g Demand Control Ventilation not available with electromechanical controls. TS*150F, TH*150F, TH*180F BAYHSDR010A4... SH-649 Split System Heat Pumps Single Phase 1½-5 Tons Table SH-7-A Silver 15 R-410A Split System Single Stage Heat Pump Nom. Steeply sloped composite drainpan... 4 Multispeed direct drive standard on single-phase products. FUR-2 S9V2, S9X2 Features & Accessories... FUR-17 Platinum 80, Gold 80v, Gold 80, Silver 80h, Silver 80 & American Standard 80 Features & Accessories... Light Commercial Packaged Cooling LPC-9191 Packaged Cooling Convertible 3-10 Tons Accessories Light Commercial Packaged Cooling Table LPC-10-A Accessories Model Number Description Used With BAYGARD037C...Condenser Coil Hail Guard...THC036, THC037 BAYGARD040C...Condenser Coil Hail Guard...TSC , THC BAYGARD041C...Condenser Coil Hail Guard...TSC BAYGARD070A...Condenser Coil Hail Guard...THC120 BAYGARD137A...Condenser Coil Hail Guard...TSC BAYGARD141A...Condenser Coil Hail Guard...THC BAYGARD437A...Condenser Coil Hail Guard... to -10 F. LPC-12194 ReliaTel Controls Operation With An Electromechanical Thermostat When the ReliaTel RTRM Thermostat Interface is used, equipment operation differs significantly. Two tone color... For additional Controls Information: See ReliaTel and Micro Control features on PC-12 and PC-13. Remote access is via most webenabled smartphones, tablets and computers. Quick Adapt Roof Curb...WHC120H, DHC120H BAYQACB113A23... 1 Unit Mounted Circuit Breaker Convenience Outlet Option Without Convenience Outlet... BAYINSKT215A...Sound Insulation Kit 21.5" PHASING Cabinet...B... registered CCZS-2 Application: Up to 4 Stages Heat/2 Stages Cool Conventional gas/electric, heat pump, and dual fuel systems Conventional boiler systems (baseboard & radiators) Remote wired indoor temperature sensor (optional): ZZSENSAL0400AA Remote wired outdoor temperature sensor (optional): BAYSEN01ATEMPA Wall cover plate BAYCOVR800A Nexia Bridge is required for control of Z-Wave devices, such as lighting, door locks, etc., and remote climate access. H 26 System Monitoring Controls No Monitoring Controls... Heat Pump Smart Recovery and Smart Staging is lost, Heat Pump operation becomes more costly unless generic control being applied can accomplish this. Dual Stage Gas LP Kit Hight Altitude Gas Kit...DHC074H(3,4,W)*(H,Z), DHC(092/102)H(3,4,W)*(M,Y,H,Z), DHC120H(3,4,W)*(L,X,M,Y,H,Z) BAYLTCI002B7... AC/IN-5 Refrigerant HFC 410A (R-410A)... necessary information and choices on each screen. BAYEXMK002B Extreme Conditions Mounting Kit... Supply Duct Flange Kit... Operating Ambient Temperature Range: 20 to 120 F (-6.7 to 48.9 C) Display Range: 20 to 120 F (-6.7 to 48.9 C) Sensor Accuracy: +/.5 F at 75 F Operating Relative Humidity: 5% to 90% non-condensing ZZSENSAL0800AA Indoor Wired Temperature Sensor for use with ACONT800, ACONT802, ACONT803 Operating Ambient Temperature Range: 20 to 120 F (-6.7 to 48.9 C) Display Range: 0 to 99 F (-18 to 37 C) Sensor Accuracy: +/ 1.5 F at 70 F (+/.84 at 21 C) Operating Relative Humidity: 5% to 95% non-condensing Dimensions in in. AC/IN-10 Low Ambient Accessories, Cooling & Heating Models... Economizer, Dry Bulb, Downflow 3-5T...All BAYENTH320A... BACNet Enabled Thermostat...EAC180A* - EAC300A* 1 Please check availability. 0 Unit Mounted Non-Fused Disconnect Switch... C 31 Advanced Unit Controls Standard Unit Controls... Architecturally integrated louvers and corner guards... BACnet Communication Interface... TASB235SB24...Plenum Stand with Integrated Sound Baffle C C... of dry air at leaving condition Grains of water/lb. 3 /4 /4 3 / O 1 For coastal applications where units are installed within one (1) mile of salt water, epoxy coated models are available for order. Standard with economizer accessory. BAYTEMDFKT1A... Cap Cooling (BTUH) Uncrated Dimensions(in.) H W D 23,800 35,000 35,000 47,000 47,000 54, Shipping Weight Sound** Rating Max. $ Away Off Status Cool to AccuLink Communicating Connected Controls AZON1050AC52ZA Nexia Z-Wave Bridge Inside Connect over 200 Z-Wave devices12 Nexia Diagnostics 1 WiFi or Ethernet connection Control from a smartphone, tablet, or computer 12 7"diagonal color touchscreen 1-Touch Presets - Home, Away, Sleep 7 Day programmable with up to four schedules per day Customizable Home Screen Runtime History Allergy and Quick Clean Air Cycles Smart Continuous Fan Adjustable Continuous Airflow (35-100%) Screen access restrictions Dealer Contact Widget Service, Filter, Humidifier, UV Light, Air Cleaner Reminders Five day weather forecast, weather radar, and weather alerts 1 Indoor relative humidity display Test modes and alert diagnostics Over-the-air Software Upgrade 1 Local Software Upgrade option Color: Designer Silver Limited Warranty: 5 yr. A Dehumidification (Hot Gas Reheat)... H Low Leak Economizer, Dry Bulb with Barometric Relief... Roof Curb...WHC120H, DHC120H BAYDFPS003B4... S8X1 S8X2 Table FUR-12-B Optional Accessories 1 Stage 2 Stage Model Number Description Shipping Weight BAYLPSS400B...LP Kit with Stainless Steel Burners (except 026) BAYLPSS410A...LP Kit with Stainless Steel Burners S8X1A026 BAYHANG...Horizontal hanging kit BAYVENT200B...Sidewall vent Termination Kit fo Direct vent furnaces BAYSF1165A...1" SlimFit Box with MERV 4 Filter (side return) BAYFLTR203...Horizontal Filter Kit for B Cabinets BAYFLTR204...Horizontal Filter Kit for C Cabinets BAYFLTR205...Horizontal Filter Kit for D Cabinets BAYVENT600A...Internal venting kit BAYVENT800B...Masonry Chimney Vent Kit PIP U fitting for gas piping BAYLIFTB...Dual return kit. registered ACONT850AC52UA Nexia Z-Wave Bridge Inside Connect over 200 Z-Wave devices WiFi (b/g/n) or Ethernet connection Control from a smartphone, tablet, or computer "diagonal color touchscreen Compatible with AccuLink communicating systems (variable speed and two stage) Compatible with conventional 24 volt HVAC, heating, heat pump, and dual fuel systems when used with accessory relay panel model BAY24VRPAC52DB 7 Day programmable with up to six schedules per day Five day weather forecast, weather radar, and weather alerts 1 Indoor relative humidity display Test modes and alert diagnostics Nexia Diagnostics Upgradable software Silver color Wall Cover Plate BAYCOVR800A Limited Warranty: 5 yr. w Not available with electro-mechanical unit controls. Use the following guidelines for your application. Do Not Exceed this value when selecting Liquid Line PSI Accessories/Information Tube Rated Pressure Drop (PSI) For Total Equivalent Length O.D. BTUH 20' 40' 60' 80' 100' 120' 140' 160' 180' 200' 220' 240' 1/4" /16" " /2" Note 1: A blank space indicates a pressure drop of over 50 PSI. Horizontal Economizer Conversion Kit...EAC180A* - EAC300A* BAYBARO300A... Includes white and light almond paddles (wall plate not included) Application: Protocol: Z-Wave Power: 120 VAC, 60Hz Max Load: 1.5A no more than two identical fans per switch not to exceed 1.5A resistive load - Controls Fan Motor Only - for use with split capacitor or shaded pole ceiling fan motors Operating Temperature: 0 C-40 C Indoor Use Only Specifications subject to change without notice Application: Protocol: Z-Wave Power: 120 VAC, 60Hz Max Load: 960W Incandescent, 1/2 HP maximum Operating Temperature: 0 C-40 C Indoor Use Only Specifications subject to change without notice Warranty 1-Year Limited Warranty Application: Protocol: Z-Wave Manufacturer: JASCO Max load: 960W incandescent, ½ HP motor, 1800W, 120VAC Operating Temperature: F Unit Dimensions: 1.5"w x 1.5"d x 3.0"h Warranty 1-Year Limited Warranty Connected Home Solutions CHS-726 Connected Home Solutions Locks and Deadbolts Touchscreen Deadbolt Camelot Schlage Keypad Lever Lock Schlage Keypad Deadbolt Lock Nexia Compatible Products Camelot Touchscreen Deadbolt Motorized bolt automatically locks and unlocks when code is entered Anti-pick shield protects against tampering Built-in alarm technology Remotely lock/unlock from a computer or compatible web enabled mobile device 1 Confirm lock status from a computer or compatible web enabled mobile device 1 Assign up to 30 personalized 4-8 digit codes Up to 3 year battery life Provides battery level status at the lock and remotely 1 Camelot touchscreen deadbolt available in Satin Nickel, Aged Bronze, Bright Brass, or Matte Black finish Schlage Keypad Lever Lock Remotely engage/release locking mechanism from a computer or compatible web enabled mobile device 1 Confirm lock status from a computer or compatible web enabled mobile device 1 Assign up to 19 personalized 4 digit codes Up to 2 year battery life Provides battery level status at the lock and remotely 1 Available in 3 finishes: Bright Brass, Satin Nickel, Aged Bronze Class 2 rated door lock Schlage Keypad Deadbolt Lock Remotely engage/release locking mechanism from a computer or compatible web enabled mobile device 1 Confirm lock status from a computer or compatible web enabled mobile device 1 Assign up to 19 personalized 4 digit codes Up to 2 year battery life Provides battery level status at the lock and remotely 1 Available in 3 finishes: Bright Brass, Satin Nickel, Aged Bronze Class 2 rated door lock Model number and finish: BAY469SNACAMEA - Satin Nickel SKU: BAY469ABACAMEA - Aged Bronze SKU: BAY469BBACAMEA - Bright Brass SKU: BAY469MBACAMEA - Matte Black SKU: Dimensions: Camelot: Outside 3.0"w x 5.0"h x1"d Inside 3.0"w x 8.28"h x 2.0"d Shipping Weight: 3.8 lbs. To 205 ppd. Furnaces Table FUR-9-C Dual Fuel Heat Pump Control Kit12 Model Number Case Height Used With TAYPLUS103A... Air Handlers/Heaters AH-659 Series 5 Multi-Position Air Handlers Single Phase 1½-5 Tons Table AH-7-A Multi-Speed High Efficiency Motor /1/60, Epoxy Coated Coil Cooling Unit Capacity Dimensions (in.) Shipping Supply Return Filter Line Size Model No. (Btuh) H x W x D Weight (lbs.) Opening Opening Sizes Gas Liquid GAM5B0A18M11EA x 17.5 x x x x 20 x 1 3 /4 3 GAM5B0A24M21EA x 17.5 x x x x 20 x 1 3 /4 3 GAM5B0B30M21EA x 21.3 x x x x 20 x 1 3 /4 3 GAM5B0B36M31EA x 21.3 x x x x 20 x GAM5B0C42M31EA x 23.5 x x x x 20 x GAM5B0C48M41EA x 23.5 x x x x 20 x GAM5B0C60M51EA x 23.5 x x x x 20 x GAM5 Table AH-7-B Features 1 1/2-5 Unique cabinet design... Longer IFC wire harnesses allow door to be removed without disconnecting the harness... Direct drive, multi speed ECM blower motor - Constant torque ECM (electronically commutated motor) with fan-off... The maximum vertical change must NOT exceed 50 feet. mercury column). Z 11 Minor Design Sequence Service Sequence 14 Fresh Air Selection No Fresh Air... 5 / Table SC-3-B Silver 16 R-410A Split System Single Stage Cooling Nom. 24. Duct Mounted CO2 Sensor...EAC180A* - EAC300A* with economizer BAYPALT001A... Trane Communications Interface (TCI)...All Precedents BAYLOAM020B4... 0 Unpowered Convenience Outlet... T 2 = T CFM T = 18. Ambient Temp. 4A7A3018H1000N2 208/230/1/60 17, /4 3 4A7A3024H1000N2 208/230/1/60 23, /4 3 4A7A3030H1000N2 208/230/1/60 28, /4 3 4A7A3036H1000N2 208/230/1/60 34, /4 3 4A7A3042E1000N2 208/230/1/60 40, A7A3043A1000N2 208/230/1/60 40, A7A3048E1000N2 208/230/1/60 46, A7A3049A1000N2 208/230/1/60 46, A7A3060D1000P2 208/230/1/60 58, Models are not legal for installation in California, Nevada, New Mexico and Arizona. Service Valve Panel Cover Kit AAYSVPANL0044AA... All Voyagers BAYDFPS013A... See ReliaTel and Micro Control features on LPC-12 and LPC-13. D 16 Hinged Service Access / Filters Standard Panels/Standard Filters... h 2 = h 1 Btu/lb. Variable Variable Variable Comfort-R mode approved AccuLink system DuraBase base, fast complete drain, weatherproof Easy-Sess cabinet, service access & refrigerant connections with full coil protection Spine Fin coil Compressor sound enclosure Compressor sump heat Factory supplied charge... Table LPC-11-B Thermostats Electromechanical Model Number Description Used With ASYSTAT712B CO2 Sensor Kit (Wall Mounted) T*C *R ASYSTAT714B CO2 Sensor Kit (Duct Mounted) T*C *R Light Commercial Packaged Cooling LPC-11193 ReliaTel Controls Packaged Unit Protection/Operation Timings and Features Light Commercial Packaged Cooling Alternating Lead/Lag Dual Compressor Models Only During periods of part load operation, each compressor cycles alternately as circuit number one, equalizing compressor wear and run time. D Horizontal... LPC-19201 Packaged Cooling with ReliaTel Controls 12½-25 Tons Heaters Table LPC-20-A Downflow Supplementary Heaters: Model Power kw Nominal No. Number Supply Rating BTUH Stages Used With AYDHTRLW54A 575/3/ ,300 2 TSD F, THD F AYDHTRKW18A 575/3/ ,400 1 TSD F, THD F AYDHTRKW54A 575/3/ ,300 2 TSD F, THD F AYDHTRKW72A 575/3/ ,700 2 TSD F, THD F AYDHTRMW36A 575/3/ ,900 2 TSD F, THD F Light Commercial Packaged Cooling Table LPC-20-B Horizontal Supplementary Heaters: Model Power kw Nominal No. Number Supply Rating BTUH Stages Used With AYHHTRMW18A 575/3/ ,400 1 THH150F, THH180F AYHHTRMW36A 575/3/ ,900 2 TSH210F-300F, TSH150F-300F AYHHTRMW54A 575/3/ ,300 2 THH150F, THH180F AYHHTRNW18A 575/3/ ,400 1 TSH150F, TSH180F AYHHTRNW54A 575/3/ ,300 2 TSH210F-300F, THH210F-300F AYHHTRNW72A 575/3/ ,700 2 TSH210F-300F, THH210F-300F AYHHTRPW36A 575/3/ ,900 2 TSH150F, TSH180F AYHHTRPW54A 575/3/ ,300 2 TSH150F, TSH180F Note: Unit with heater is single circuit/single point. B 21 Communications Options Without Communications Options... BAYFLR2220A...Washable high velocity filter, 22" x 20" x 1" (10 filters)...c... (Example: if the actual line length is 170 feet, add 4 ounces of oil to the system) This page contains limited data to fully determine if the application will work or to select required accessories. efficiency models and T/YHC 4, 5, 6, 7½ ton high efficiency models (except for 3 Requires use of Disconnect or Circuit Breaker. B cabinet size extension BAYLIFTC...Dual return kit. TTA12043C /3/60 122, / 8 1 / 2 TTA18043C /3/60 184, / 8 5 / 8 TTA24043C /3/60 250, / 8 5 / 8 TTA30043C /3/60 296, / 8 5 / 8 TTA12044C 460/3/60 122, / 8 1 / 2 TTA18044C 460/3/60 184, / 8 5 / 8 TTA24044C 460/3/60 250, / 8 5 / 8 TTA30044C 460/3/60 296, / 8 5 / 8 TTA1204WC 575/3/60 122, / 8 1 / 2 TTA1804WC 575/3/60 184, / 8 5 / 8 TTA2404WC 575/3/60 250, / 8 5 / 8 TTA3004WC 575/3/60 296, / 8 5 / 8 1 Sound rating shown is tested in accordance with ARI Standard 270 or 370. Warranty 1-Year Limited Warranty Lighting Z-Wave Light Bulb LED Light Bulb SKU: watt equivalent LED dimmable Z-Wave light bulb Compatible with any certified Z-Wave based system such as Nexia 1 Instant on and fully dimmable 22.8 years life at 3 hours per day average use 2700K soft white light Light can be activated, deactivated and fully dimmed remotely 1 Light can be triggered from compatible sensors and locks 1 Application: Protocol: Z-Wave Manufacturer: Linear Manufactured in China Unit Dimensions: 2.95" x 4.92" x 2.95" Unit weight: 4.6 oz Warranty 1-Year Limited Warranty CHS-5 1 Requires internet service and Nexia smart home system registration.24 Connected Home Solutions Jasco In-Wall Dimmer Switch Jasco In-Wall On/Off Switch Jasco In-Wall 3-Way Add-on Switch Nexia Compatible Products Dimmer Switch SKU: Turn light on/off or dim any incandescent lighting remotely from Nexia app 1 Interchangeable paddles; white and light almond included in package (wall plate not included) Easy to install; includes space-saving screw terminals Automate with Nexia based on time of day Trigger actions from other smart products LED indicator glows in dark On/Off Switch SKU: Turn any light on/off remotely from Nexia

4AYTXVH3D3343A 2AYTXVH3C3337A 2/4TXF-033 4AYTXVH3D3343A 2AYTXVH3C4243A 2/4TXF-041 4AYTXVH3D4863A 2AYTXVH3C5463A 2/4TXF-054 4AYTXVH3D4863A 2AYTXVH3C5463A 2/4TXF-063 Table AC/IN-2-C Cooling/Heat Pump Non-Bleed TXV Kits- Dual Direction Flow-TXA/C-AS Coils R-410 R-22 Model Model Used With AS Number Number Aluminum Coils 4AYTXVH3B2531A 2AYTXVH3B2531A 2/4TXA,TXC-025 4AYTXVH3B2531A 2AYTXVH3B2531A 2/4TXA,TXC-031 4AYTXVH3B3654A 2AYTXVH3B3637A 2/4TXA,TXC-036 4AYTXVH3B3654A 2AYTXVH3B3637A 2/4TXA,TXC-037 4AYTXVH3B3654A 2AYTXVH3B5454A 2/4TXA,TXC-054 4AYTXVH3B6165A 2AYTXVH3B6565A 2/4TXA,TXC-065 Table AC/IN-2-D Cooling/Heat Pump Non-Bleed TXV Kits Dual Direction Flow 4NXA/4NXC R-22 Used With Number 4NXA & 4NXC Coils 2AYTXVH3E1824AA 4NXA,NXC AYTXVH3E2536AA 4NXA,NXC AYTXVH3E6363AA 4NXC Table AC/IN-2-E Cooling/Heat Pump Non-Bleed TXV Kits- Dual Direction Flow R-410 R-22 Used With Number Numbers Air Handlers 4AYTXVH3D1830A 2AYTXVH3D1830A 2TFB AYTXVH3D1831A 2AYTXVH3D1830A 2TFB-036 4AYTXVH3D1831A 2AYTXVH3D1830A 2/4TFE-025 4AYTXVH3D1831A 2AYTXVH3D1830A 2/4TEC AYTXVH3D3636A 2/4TEC-036 4AYTXVH3D3642A 2/4TEC AYTXVH3D4260A 2/4TEC AYTXVH3D4863A 2/4TEC AYTXVH3D1831A 2AYTXVH3D1830A 2/4TEH AYTXVH3D3636A 4TEH-036 4AYTXVH3D3642A 2TEH AYTXVH3D4260A 4TEH AYTXVH3D4863A 2TEH AYTXVH3D1800A 2AYTXVH3D1830A 2/4TGB-018 4AYTXVH3D1830A 2AYTXVH3D1830A 2/4TGB-025 4AYTXVH3D1831A 2AYTXVH3D1830A 2/4TGB-030 4AYTXVH3D3600A 2AYTXVH3D1830A 2/4TGB-036 4AYTXVH3D3343A 2AYTXVH3D4260A 2/4TGB-042 4AYTXVH3D4863A 2AYTXVH3D4260A 2/4TGB-048 4AYTXVH3D3642A 2AYTXVH3D4260A 2/4TEE-039 4AYTXVH3D4863A 2AYTXVH3D4260A 2/4TEE AC/IN-2150 Thermal Expansion Valves Table AC/IN-3-A Cooling Bleed TXV Kits Single Direction Flow Liquid Line Gas Line Model Used With Connection Connection Shipping Number AC Units Dia. Can not be adapted for horizontal units. Note 5: It is recommended to place units where 1/2" liquid line is not required due to the increased refrigerant volume imposed by the larger liquid line. 4 CompleteCoat Condenser Coil with Hail Guard Through The Base Provisions. Factory installed fixed orifice. AC/IN-4 Refrigerant Line Sets... PK-3134 Packaged Hybrid/Dual Fuel 4DCZ6 4DCY4 Packaged Hybrid/Dual Fuel Convertible 2-5 Tons Table PK-4-A 4DCZ6 - Platinum 16 - Convertible Packaged Dual Fuel - R-410A Cooling Gas Uncrated Model Capacity Capacity Heating Shipping Max Sound Dimensions (in.) Number (BTUH) Output (1 Stg./2 Stg.) SEER/EER HSPF AFUE(%) Weight MCA Fuse Rating H x D x W 4DCZ /1/60 4DCZ6036C1070A 36,000 45,000/57, / x 42 x 49 4DCZ6048C1090A 47,500 58,000/73, / x 45 x 59 4DCZ6060C1115A 57,000 75,000/93, / x 45 x 59 4DCZ /3/60 4DCZ6036B3075A 36,000 48,400/60, / x 42 x 49 4DCZ6048B3096A 47,500 62,000/77, / x 45 x 59 4DCZ6060B3120A 57,000 77,500/96, / x 45 x 59 Table PK-4-B 4DCY4 - Gold 14 - Convertible Packaged Dual Fuel - R-410A Cooling Gas Uncrated Model Capacity Capacity Heating Shipping Max Sound Dimensions (in.) Number (BTUH) Output (1 Stg./2 Stg.) SEER/EER HSPF AFUE(%) Weight MCA Fuse Rating H x D x W 4DCY /1/60 4DCY4024C1060A 23,600 39,000/49, / x 42 x 49 4DCY4030C1070A 30,000 45,000/57,000 PHASING 14.25/ OUT x 42 x 49 4DCY4024D1060A 23,600 39,000/49, / x 42 x 49 4DCY4030D1070A 30,000 45,000/57, / x 42 x 49 4DCY4036C1070A 37,000 45,000/57, / x 42 x 49 4DCY4042C1090A 42,000 58,000/73, / x 45 x 59 4DCY4048C1090A 47,500 58,000/73, / x 45 x 59 4DCY4060C1115A 58,000 75,000/93, / x 45 x 59 4DCY /3/60 4DCY4036B3075A 36,000 48,400/60, / x 42 x 49 4DCY4048A3096C 47,000 62,000/77, / x 45 x 59 4DCY4060A3120C 57,500 77,500/96, / x 45 x 59 For dimensional/outline drawings, please refer to Product Data. 0 If any version of comparative or reference enthalpy is ordered, BAYRTEM001A does not need to be ordered. For complete application guidelines, consult the specific SSC-APG*** 1 Reference AMSSP-APG001-EN for complete Low Ambient Guidelines 2 Reference SSC-APG014A-EN for Side Discharge Low Ambient Application Guidelines Reference SSC-APG012A-EN for complete Low Ambient Guidelines * DO NOT Apply BAYLOAM103/107 to model tonnages with variable speed condenser fan motors * If Defrost Control is CNT07255, CNT07482 use BAYLOAM107 Liquid Line Solenoid Valve Liquid Line Solenoid Valve Accessories/Information For a detailed Application Bulletin on required accessories and wind shields for low outdoor ambient operation, please contact your Territory Manager or Local FSR. 6 Mounts to TASB original plenum stands without integrated sound baffle. registered ACONT724AS42DA Nexia compatible 12 WiFi connectivity Control from a smartphone, tablet, or computer "diagonal black and white touchscreen 7 Day programmable with up to 4 schedules per day Humidity sensor and RH display Remote temperature sensor connections (1 indoor/1 outdoor) Auxiliary & compressor heat lockouts Auxiliary dry contact Enhanced dehumidification (cooling) PWM Circuit (BK terminal): controls indoor unit variable speed blower Energy Savings Mode (ESM) Screen lock and guest lock Service test modes Upgradable software Color: Designer Silver Limited Warranty: 1 yr. CHS-3 Nexia Bridges & Starter Bundles... LSC-6166 Split System Heat Pumps Three Phase 6-20 Tons, R-410A TWA 6-20 Tons ReliaTel controls (standard) (1) Scroll compressor (TWA A) (2) Scroll compressors (TWA D) with independent refrigerant circuits Single point power Compressor motor overload protection Compressor discharge temperature limit switch Control transformer High and low pressure cut-out switches Demand Defrost Control Internal pressure relief valves Model Number Description Heat Pump Condenser Digit 1 3 Unit Function Digit 9 Refrigeration Circuit/Stage TWA = Split System Heat Pump A = 1 Compressor/1 Line/1 Stage (Single) Digit 4 6 Tonnage D = 2 Compressors/2 Line/2 Stage (Duals) 072 = 6 Tons (60Hz) Digit 10 Major Design Sequence 090 = 7.5 Tons (60Hz) A = Rev A 120 = 10 Tons (60Hz) Digit 11 Minor Design Sequence 180 = 15 Tons (60Hz) B = Rev B 240 = 20 Tons (60Hz) Digit Service Digits Digit 7 Refrigerant 00 = 00 4 = R-410A Digit 14 Efficiency Generation Digit 8 Voltage A = Generation A 3 = VAC - 3 PH (60Hz) 4 = 460VAC - 3 PH (60Hz) Digit 15 Controls W = 575VAC - 3 PH (60Hz) R = ReliaTel K = 380VAC - 3 PH (60Hz) Electrical phase reversal protection Holding charge (Dry Nitrogen) Copper tube, aluminum plate fin coils Low ambient cooling to 50 F as shipped Low ambient cooling to 0 F with accessory head pressure control Mounting/lifting rails under base UL listed 5-year compressor warranty (TWA072A, TWA090A, TWA120A, TWA180D, TWA240A) 1-year limited parts warranty Optional Extended Warranties Digit 16 None 0 = None Digit 17 Coil Protection 0 = Standard Coil 1 = Standard Coil w/ Hail Guard 2 = Black Epoxy Pre-Coated Condenser Coil (FIN/TUBE) 3 = Black Epoxy Pre-Coated Condenser Coil with Hail Guard (FIN/TUBE) Digit None 0 = None Digit 21 Communications Options 0 = No Option 2 = LonTalk Communications Interface (LCI) Digit None 0 = None Table LSH-1-A TWA Split System Heat Pumps Single Compressor with Single Refrigerant Circuits R-410 Refrigerant AHRI Net Uncrated Shipping Line Size (in) Model Number Power Supply Cooling Cap. Masonry Chimney Venting w/bayvent800b... Precise Temperature Control (±1 F) reliable, consistent comfort. (in.) Dim. Note 4: If linear length exceeds 150 feet, add 2 ounces of approved compressor oil per every 10 feet in excess of 150 feet. Two speed venter motor... Barometric Relief...WSC H, WHC036H, DHC036H BAYBARM011A2... O Silver 16 (Single Stage) Model Number SC-3 Split System Cooling Silver 16 (Single Stage) Model Power Number Suppy38 Split System Cooling Single Phase 1½-5 Tons Split System Cooling Gold 17 Silver 16 Silver16 Table SC-4-A Features (4A7A7) (4A7A6) (4A7L6) SEER up to Duration compressor Number of stages Comfort-R mode approved DuraBase base, fast complete drain, weatherproof Easy-Sess cabinet, service access Spine Fin coil Coppe Tube, Aluminum Fin coil Factory supplied charge... 4 Used for additional seacoast corrosion protection. TASB235SB25...Plenum Stand with Integrated Sound Baffle C...C... Common vent capability... CHS-4 Nexia Compatible Products... Table AC/IN-6-B Allowable Vapor Line Diameters and BTUH Loss (R-410A Single Speed Systems) Nominal Tube O.D. Press. All Voyagers 12½-20 Tons Horizontal Light Commercial Packaged Heat Pumps BAYVNOR002B5... Limited HP matched system ratings... 6 For use with electromechanical controlled units only. 2 Enhanced models for use in heating. The apex of the coil may point into or away from the airflow. TAYBASE Air Handler Downflow Sub-Bases "... For vertical configuration, the drain pan should be repositioned before setting the air handler. AH-1871 Split System Cased Heat Pump and Cooling Coils Table COIL-1-A Aluminum High Efficiency Staged System Cased Convertible Coils (Upflow/ Downflow/ Horizontal Left or Right) R-410A Refrigerant Cooling Capacity Outlet Overall Shipping Line Size Model Range Coil Refrigerant Dim. Insulated blower compartment 4 sides... Direct drive, multi speed CTM Electronically Commutated Motor (ECM) Direct drive, multi speed PSC motor Upflow only... 4 Spinnaker gray cabinet year registered limited warranty on compressor,10-year on outdoor coil & all other functional parts (Residential Use) Extended warranties available Table SC-2-B Optional Accessories Model Number Description Shipping Weight BAYECMT Extreme Conditions Mounting Kit (Base 2/3) BAYECMT Extreme Conditions Mounting Kit (Base 4) BAYISLT Rubber Isolators BAYVEN Enhanced Sound Enclosure BAYLEGS Snow Legs - 7" High (Black) BAYLEGS Snow Legs - 4" High (Black) BAYVDTA Vertical Discharge Air Kit Base BAYVDTA Vertical Discharge Air Kit Base BAYSEAC Seacoast Kit PAI Heresite Spraypaint BAYAWGR All Weather Top - Fits unit base size of (W x D) of 37" X 34" BAYAWGR All Weather Top - Fits unit base size of (W x D) of 33" X 30" Comfort Controls See Comfort Controls/Zone Sensors Section 1 Registered Limited Warranty terms are available when you register within 60 days of installation. Packaged Gas/Electric For dimensional/outline drawings, please refer to Product Data. BAYFRKIT210...Front Return Kit...B... BAYFLTR101C 1-2" Filter Frame2-Requires one 18x25 filter (not included) BAYFLTR201C 1-2" Filter Frame2r-Requires one 18x20 and one 18x18 (not included) ½-5 BAYLIFT002B Lifting Lug Kit BAYLOAM105A Low Ambient Control Kit BAYRLAY004A Economizer Relay1... BAYTMMWALLPNL1...Return air / service wall panel... 1 Note: Most Factory Installed Options available for Downflow Air Discharge units only. 9 Single Zone Variable Air Volume Standard Motor w/shaft Ground Ring... q BAYACCDOR1A requires BAYFLTR101B & BAYACCDOR2A requires BAYFLTR201B. LAH-4175 Split System Air Handlers, R-410A Single Phase 5-10 Tons Three Phase 5-25 Tons Table LAH-5-A 5 20 Ton Accessory Selection Model Number Description Used With Plenum BAYPLNM015B2 Discharge Plenum & Grille TWE061D/E BAYPLNM016B2 Discharge Plenum & Grille TWE090D/E, TWE073E BAYPLNM017B2 Discharge Plenum & Grille TWE120D/E BAYPLNM018B2 Discharge Plenum/Hydronic Coil Plenum & Grille TWE150E, TWE180E BAYPLNM019B2 Discharge Plenum/Hydronic Coil Plenum & Grille TWE240E, TWE300E BAYPLNM020B2 Hydronic Coil Discharge Plenum & Grille TWE061D/E BAYPLNM021B2 Hydronic Coil Discharge Plenum & Grille TWE090D/E, TWE073E BAYPLNM022B2 Hydronic Coil Discharge Plenum & Grille TWE120D/E BAYPLNM030A2 Electric Heat Discharge Plenum & Grille TWE061D/E BAYPLNM031A2 Electric Heat Discharge Plenum & Grille TWE090D/E, TWE073E BAYPLNM032A2 Electric Heat Discharge Plenum & Grille TWE120D/E BAYPLNM033A2 Electric Heat Discharge Plenum & Grille TWE150E, TWE180E BAYPLNM034A2 Electric Heat Discharge Plenum & Grille TWE240E, TWE300E Transformer BAYTFMR011A1 75va transformer (230V) TWE090D3, TWE090E3, TWE120D3, TWE120E3, TWE073E3 BAYTFMR012A1 75va transformer TWE090D4/W, TWE090E4/W, TWE120D4/W, TWE120E4/W, TWE073EW BAYTFMR013A1 TWE090DK, TWE090EK, TWE120DK, TWE120EK Water Kits BAYWATR022A2 Steam Coil Enclosure TWE061D/E BAYWATR023A2 TWE090D/E, TWE073E BAYWATR024A2 TWE120D/E BAYWATR025A2 TWE150E, TWE180E BAYWATR026A2 TWE240E, TWE300E BAYWATR027A2 Hot Water Coil Enclosure TWE061D/E BAYWATR028A2 TWE090D/E, TWE073E BAYWATR029A2 TWE120D/E BAYWATR030A2 TWE150E, TWE180E BAYWATR031A2 TWE240E, TWE300E Wire Kit BAYWRKT002A3 180 Blower Discharge Reversal Kit TWE061D-TWE120E 1 Required when 6-10 Ton Air Handlers are matched with 3-5 Ton condensing units. e Precedent E cabinet to Precedent D cabinet (BAYCURB044 to BAYCURB043) r Precedent B cabinet to Precedent C cabinet (BAYCURB042 to BAYCURB043) LPC-10192 Packaged Cooling Convertible 3-10 Tons, R-410A Zone Sensors / Thermostats Table LPC-11-A Zone Sensors for ReliaTel Controlled Units Model Number Description Used With ASYSTAT106A Single Setpoint Manual Changeover T*C *R ASYSTAT107A Single Setpoint T*C *, R ASYSTAT108A Dual Setpoint Manual or Auto Changeover T*C *R ASYSTAT109A Dual Setpoint Changeover Sensor T*C *, R ASYSTAT111A Remote Room Sensor ASYSTAT777A Programmable Night Setback w/system Function Lights (Vertical Style) T*C *R ASYSTAT708A Programmable Night Setback w/system Function Lights T*C *R ASYSTAT710A Wall Mounted Humidity Sensor T*C036,120A,3,4,W-R,T*C *_R ASYSTAT711A Duct Mounted Humidity Sensor T*C *,T*C *_R BAYSENS924A Title 24 Zone Sensor1 All BAYMTPL110A Retrofit Wall Cover Plate Kit 7.25" x 6.0" ASYSTAT111A 1 Must be used with ReliaTel Control and BCI Communications Interface *Either standard or high efficiency models. Multi-Position UP/Down Flow*, Horizontal Left /Right... Quick Adapt Roof Curb...WSC H, WHC036H, DHC036H BAYQACB010A23... Vent Downflow Furnaces FUR-580 Silver 95 Single Stage Table FUR-6-A Silver 95 Direct/Non-Direct Vent, Upflow/Horizontal Left Condensing Gas Furnace (115/1/60) Airflow Nominal ICS1 Flue Uncrated Shipping Unit In Output AFUE Size Ignition Dimensions (in.) Weight Max Filter** Model No. Tons (Btuh) Upflow / Horiz (in) Device H x W x D (Ibs.) Fuse* Sizes AUH1B040A9241C 2 38, / , 2 1 / 2, x 17 1 / 2 x x 25 x 1 AUH1B060A9361C 3 57, / , 2 1 / 2, x 17 1 / 2 x x 25 x 1 AUH1B080A9421C 3 1 / 2 73, / , 2 1 / 2, x 17 1 / 2 x x 25 x 1 AUH1C080A9601C 5 76, / x 21 x x 25 x 1 AUH1C100A9481C 4 92, / x 21 x x 25 x 1 Silver 95 Direct/Non-Direct AUH1D100A9601C 5 92, / x 24 1 / 2 x x 25 x 1 Furnaces Table FUR-6-B Silver 95 Direct/Non-Direct Vent, Downflow/Horizontal Right Condensing Gas Furnace (115/1/60) Airflow Nominal Flue Uncrated Shipping Unit In Output ICS1 Size Ignition Dimensions (in.) Weight Max2 Filter** Model No. Tons (Btuh) AFUE (in) Device H x W x D (Ibs.) Fuse* Sizes ADH1B040A9241C 2 38, ,2 1 / 2, x 17 1 / 2 x (2)14 x 20 x 1 ADH1B065A9421C 3 1 / 2 57, ,2 1 / 2, x 17 1 / 2 x (2)14 x 20 x 1 ADH1C085A9481C 4 76, / 2, x 21 x (2)16 x 20 x 1 ADH1D110A9601C 5 104, / 2, x 24 1 / 2 x (2)16 x 20 x 1 1 Isolated Combustion System. Reference Enthalpy Economizer, 3-5T...All BAYENTH321A... F Fan Failure Switch, Discharge Air SensingTube8 and Condensate Drain Pan Overflow Switch...G Clogged Filter Switch8, Fan Failure Switch8, Discharge Air Sensing8 and Condensate Drain Pan Overflow Switch... Btu/lb. t Novar Sensor utilized with Digit 21 = (4) Novar 3051 Controls without Zone Sensor. Direct drive, multi speed ECM blower motor - Constant torque ECM (electronically commutated motor) (GAF2A0A36M31)... 5 BAYABRD002B is required when ordering field installed BAYDFPS005A or 006A, BAYTUBE008A or 009A and BAYLOAM031A or BAYVNOR002B. Power Exhaust (460/3)...WSC H4, WHC036H4, DHC036H4 BAYPWRX072A... Warranty Lifetime limited mechanical and finish warranty 1-year limited electronics warranty Application: Resolution: 1920 x 1080, 1280 x 720, 640 x 480, 320 x 240 Video Compression: H.264, MJPEG Operating Temp: 32 F (0 C) to 113 F (45 C) Storage Temp: -4 F (-20 C) to 158 F (70 C) Wireless: IEEE b/g/n, WEP 64/128 bit, WPA/WPA2 personal security support Power Adapter: 12V/1A, 100~240VAC (indoor use only) Dimensions: 2.8" W x 2.7" H x 1.2" D Application: Resolution: 1280 x 720, 640 x 480, 320 x 240 Video Compression: H.264, MJPEG Operating Temp: -4 F (-20 C) to 104 F (40 C) Storage Temp: -40 F (-40 C) to 158 F (70 C) Wireless: IEEE b/g/n, WEP 64/128 bit, WPA/WPA2 personal security support Power Adapter: 12V/1.5A, 100~240VAC (indoor use only) Dimensions: 3.3" W x 4.8" H x 3" D Connected Home Solutions CHS-9 1 Requires internet service and Nexia smart home system registration.28 Connected Home Solutions Wi-Fi Indoor Camera Remote Temperature Sensor Remote Wireless Indoor Sensor Security Sensors & Alarms Nexia Compatible Products Wi-Fi Indoor Camera SKU: Nexia Web Camera - Wireless 720p Indoor, fixed camera (power supply included) Remotely view and monitor your home from a computer or compatible web enabled mobile device 1 Secure Connection with server for homeowner protection Plug and Play with Nexia System infrared illumination for night vision ZSENS930AW00MA Indoor Wireless Temperature and Humidity Sensor for use with ACONT824, ACONT850, AZON1050 Operating Ambient Temperature Range: 32 to 104 F (0 to 40 C) Power Supply: Two AAA alkaline batteries Sensor Accuracy: +/ 1 F over the sensing range of 32 F to 120 F (0 to 48.9 C) Operating Relative Humidity: 10% to 90% non-condensing Application: Resolution: 1280 x 720, 640 x 480, 320 x 240 (QVGA) Video Compression: H.264, MJPEG Operating Temp: 32 F (0 C) to 104 F (40 C) Storage Temp: -4 F (-20 C) to 158 F (70 C) Wireless: IEEE n02.11b, g compatible, WEP 64/128 bit, WPA/WPA2 personal security support Power Adapter: 12V/1A, 100~240VAC (indoor use only) Dimensions: 71mm W x 120mm H x 79mm D Dimensions in in. D cabinet size extension BAYBASE205...Downflow subbase BAYFLTR206...Filter Access Door Kit (Downflow only) FUR-1287 Platinum 80, Gold 80v, Gold 80, Silver 80h, Silver 80, and American Standard 80 Gas Furnaces Airflow Directions Furnaces Note: The non-condensing, forty inch (40") height furnaces may be laid on either side for horizontal application. B Hinged Access Panels & 2" Pleated Filters MERV 8... Variable speed venter motor... Still provides communication to BAS. BAYRETFLGBA...Return Duct Flange B...B... 2 HP Belt Drive Oversized Motor...WSC072HW BAYHSMT400A... j When ordering Dehumidification option, Digit #7 will revert back to E, not F. Dedicated Downflow furnace model... 2, 2½, 3½ 2-4 All models are certified to UL year compressor, 10-year coils & all other functional parts registered limited warranty (Residenttial Use) Extended warranties available... Y 2 Efficiency Standard Efficiency... Barometric Relief Damper, 15-25T...EAC180A* - EAC300A* BAYENTH300A... Horizontal Right application... Horizontal Drain pan... Fan Auto/Fan On This switch determines whether the indoor fan operates during cooling and heating cycles only (FAN AUTO) or runs continuously (FAN ON). * Digit 9-E=Electromechanical or R=ReliaTel. P 72 kw Electric Heat2... Light Commercial Packaged Cooling LPC-13195 Packaged Cooling with ReliaTel Controls 12½-25 Tons, R-410A 12½-25 Ton T*D-G Downflow 12½-25 Ton T*H-G Horizontal ReliaTel control features are listed on page LPC-12 Built-in anti-short cycle, time-delay relay and minimum on time controls 2" throwaway filters Liquid line drier Built-in fork lift holes Operating charge of R-410A Quick-Access on 12½ 25 Sloped sheet metal drain pan Dedicated horizontal and downflow units Single point power for electric heat Complete line of optional electric heaters Internally enhanced coil tubing Low ambient to 0 F standard Colored and numbered wiring Phase monitor Quick-adjust idler arm pulley. * Used with TXH coils only where approved for use with 2 compressor systems. Table AH-17-E BAYHTRM Heater, Standard, for TMM Air Handlers Heater Capacity Capacity Number Number Heater Amps Contains Volts Rated Control of Heater of per Circuit Circuit Number kw BTUH kw BTUH Voltage Stages Racks Circuits 208 Volts 240Volt Breakers BAYHTRM505BRK /240/1/ Yes BAYHTRM508BRK PHASING 208/240/1/60 1 OUT Yes BAYHTRM510BRK /240/1/ Yes Heaters for TMM Split System Air Handlers AH-17 PHASING OUT Table AH-17-D Optional Accessories Model Number Description TMM5 TMM4 4AYTXVH3G2436A...R-410A TXV kit 1-1/2 to 3 ton... Standard Increased Reliability Fewer components (moving electromechanical parts), less likelihood of equipment down time or failure. Nexia One Touch CHS-4 1 Requires internet service and Nexia smart home system registration.23 Modules Light Dimmer Module Nexia Compatible Products Light Dimmer Module SKU: Light Dimmer Module and Z-Wave Signal Repeater Used to control and dim plug-in incandescent lighting 1 Application: Max load both outlets = 15 Amps, 1800 Watt resistive Max load Z-Wave controlled outlet = 300 Watts incandescent only Shipping Weight:1 lb. 3 Activated on Power Off. SH-5 Split System Heat Pumps Silver 16 (Single Stage) 4AL6L6018A1000A1 4A6L6024A1000A1 4A6L6030A1000A1 4A6L6036A1000A1 4A6L6042A1000A1 4A6L6048A1000A1 4A6L6060A1000A1 Power Suppy N Model Number E Table SH-5-C Silver 16 R-410A SideDischarge Single Stage Heat Pump48 Split System Heat Pumps Single Phase 1½-5 Tons Split System Heat Pumps Gold 17 Silver 16 Silver 16 Table SH-6-A Features (4A6H7) (4A6H6) (4A6L6) SEER up to HSPF up to Duration compressor Number of stages Comfort-R mode approved DuraBase base, fast complete drain, weatherproof Easy-Sess cabinet, service access & refrigerant connections with full coil protection Spine Fin coil Copper Tube Aluminum Fin coil... Economizer, Dry Bulb, Horizontal...EAC180A* - EAC300A* BAYECON350A3... ** Rated in accordance with AHRI Standard Split System Heat Pumps SH-952 Split System Heat Pumps Single Phase and Three Phase Split System Heat Pumps Gold 17 Silver 14 Table SH-10-A Features (4A6C7) (4A6C4) SEER up to HSPF up to Comfort-R mode approved DuraBase base, fast complete drain, weatherproof Easy-Sess cabinet, service access & refrigerant connections with full coil protection Spine Fin coil Compressor sump heat - factory installed Refrigerant... Table AH-14-B Optional Accessories Model Matches Number Description Cabinet Size(s) TEM8 TEM6 TEM4 BAYTEMSPFG1... 2 SEER applies, 3-5 tons; EER applies 6-10 tons. LSC-1 Internal pressure relief valves Holding charge (Dry Nitrogen) All Aluminum microchannel coil Low ambient cooling to 50 F as shipped Low ambient cooling to 0 F with accessory head pressure control Mounting/lifting rails under base UL listed 5-year compressor warranty 1-year limited parts warranty Optional Extended Warranties Digit 16 None 0 = None Digit 17 Coil Protection 0 = Standard Coil 1 = Standard Coil w/ Hail Guard 4 = Complete Coat Condenser Coil (MCHE) 5 = Complete Coat Condenser Coil with Hail Guard (MCHE) Digit None 0 = None Digit 21 Communications Options 0 = No Option 2 = LonTalk Communications Interface (LCI) Digit None 0 = None Table LSC-1-A TTA Split System Cooling Single Compressor R-410 Refrigerant Model Power AHRI Net Cooling Uncrated Dimensions(in.) Shipping Weight Sound1 Max. of torque Manual gear release Screw terminal blocks 97% leak proof rating Sturdy aluminum blades and frame Motor is always located on the second dimension of the model number, i.e ZDAMP*MMA1012A will have the motor mounted on the 12" dimension W Rectangular Dampers with Side Mount Actuator Table CCZS-13-A Specifications: Rectangular Dampers with Side Mount Actuator Uncrated Model Power Dimensions (in.) Number Supply Description W H ZDAMPSMMA0806A 24 VAC Rectangular-Side Mount Actuator 8 6 ZDAMPSMMA0808A 24 VAC Rectangular-Side Mount Actuator 8 8 ZDAMPSMMA1006A 24 VAC Rectangular-Side Mount Actuator 10 6 ZDAMPSMMA1008A 24 VAC Rectangular-Side Mount Actuator 10 8 ZDAMPSMMA1010A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1206A 24 VAC Rectangular-Side Mount Actuator 12 6 ZDAMPSMMA1208A 24 VAC Rectangular-Side Mount Actuator 12 8 ZDAMPSMMA1210A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1212A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1406A 24 VAC Rectangular-Side Mount Actuator 14 6 ZDAMPSMMA1408A 24 VAC Rectangular-Side Mount Actuator 14 8 ZDAMPSMMA1410A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1412A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1414A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1606A 24 VAC Rectangular-Side Mount Actuator 16 6 ZDAMPSMMA1608A 24 VAC Rectangular-Side Mount Actuator 16 8 ZDAMPSMMA1610A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1612A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1614A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1616A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1806A 24 VAC Rectangular-Side Mount Actuator 18 6 ZDAMPSMMA1808A 24 VAC Rectangular-Side Mount Actuator 18 8 ZDAMPSMMA1810A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1812A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1814A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1816A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA1818A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2006A 24 VAC Rectangular-Side Mount Actuator 20 6 ZDAMPSMMA2008A 24 VAC Rectangular-Side Mount Actuator 20 8 ZDAMPSMMA2010A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2012A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2014A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2016A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2018A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2020A 24 VAC Rectangular-Side Mount Actuator CCZS-13 Comfort Controls/Zone Sensors120 24 Volt Modulating Dampers - Side Mount Comfort Controls/Zone Sensors Table CCZS-14-A Specifications: Rectangular Dampers with Side Mount Actuator (continued) Uncrated Model Power Dimensions (in.) Number Supply Description W H ZDAMPSMMA2206A 24 VAC Rectangular-Side Mount Actuator 22 6 ZDAMPSMMA2208A 24 VAC Rectangular-Side Mount Actuator 22 8 ZDAMPSMMA2210A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2212A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2214A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2216A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2218A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2220A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2222A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2406A 24 VAC Rectangular-Side Mount Actuator 24 6 ZDAMPSMMA2408A 24 VAC Rectangular-Side Mount Actuator 24 8 ZDAMPSMMA2410A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2412A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2414A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2416A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2418A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2420A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2422A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2424A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2606A 24 VAC Rectangular-Side Mount Actuator 26 6 ZDAMPSMMA2608A 24 VAC Rectangular-Side Mount Actuator 26 8 ZDAMPSMMA2610A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2612A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2614A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2616A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2618A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2620A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2622A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2624A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2626A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2806A 24 VAC Rectangular-Side Mount Actuator 28 6 ZDAMPSMMA2808A 24 VAC Rectangular-Side Mount Actuator 28 8 ZDAMPSMMA2810A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2812A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2814A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2816A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2818A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2820A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2822A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2824A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2826A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA2828A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3006A 24 VAC Rectangular-Side Mount Actuator 28 6 ZDAMPSMMA3008A 24 VAC Rectangular-Side Mount Actuator 28 8 ZDAMPSMMA3010A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3012A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3014A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3016A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3018A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3020A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3022A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3024A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3026A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3028A 24 VAC Rectangular-Side Mount Actuator ZDAMPSMMA3030A 24 VAC Rectangular-Side Mount Actuator CCZS-14121 Excellence Without Comprimise GEAR Supply OPEN 24 Volt Modulating Dampers - Bottom Mount Rectangular Dampers with Bottom Mount Actuator H Rectangular Dampers with Bottom Mount Actuator CONTROLS INC. BAYINSKT175A...Sound Insulation Kit 17.5" Cabinet... 2 Silicon Nitride Igniter.. LEGEND Total airflow cubic feet/min. N 54 kw Electric Heat... Up to four 0400 wired sensors or 930 wireless sensors may be installed per zone. Silver 95h - Single Stage with ECM Multi-Speed Motor Table FUR-5-C Silver 95h Direct/Non-Direct Vent, Upflow/Horizontal Left Condensing Gas Furnace with Filter Airflow Nominal ICS1 Flue Uncrated Shipping Unit In Output AFUE Size Ignition Dimensions (in.) Weight Max Filter Model No. Tons (Btuh) Upflow / Horiz (in) Device H x W x D (Ibs.) Fuse* Sizes** AUH1B040A9H21B 2 38, / , 2 1 / 2, x 17 1 / 2 x x 25 x 1 AUH1B060A9H31B 3 57, / , 2 1 / 2, x 17 1 / 2 x x 25 x 1 AUH1B080A9H31C 3 73, / , 2 1 / 2, x 17 1 / 2 x x 25 x 1 AUH1C100A9H41B 3 1 / 2 92, / x 21 x x 25 x 1 Silver 95h Direct/Non-Direct Vent Upflow Table FUR-5-D Silver 95h Direct/Non

Electric Heaters Unit with Heater is single circuit / single point power entry (6-8 1/2 Ton High Efficiency, 10 Ton Units) Model Power kw Nominal No. Number Supply Rating BTUH Stages Used With BAYHTRA309A /3/ THC F3 BAYHTRA318A /3/ /18 46,100/61,400 1 THC074F3 BAYHTRA327A /3/ /27 69,000/92,100 2 TSC120F3, TSC120H3, THC F3 BAYHTRA336A /3/60 27/36 92,200/122,900 2 THC074F3 BAYHTRA354A /3/ /54 138,200/184,300 2 TSC120F3, TSC120H3 Light Commercial Packaged Cooling BAYHTRA409A 460/3/ THC074F-THC102F BAYHTRA418A 460/3/ TSC120F4, TSC120H4, THC F4 BAYHTRA427A 460/3/ TSC120F4, TSC120H4, THC F4 BAYHTRA436A 460/3/ TSC120F4, TSC120H4, THC F4 BAYHTRA454A 460/3/ TSC120F4, TSC120H4 BAYHTRAW18A 575/3/ TSC120FW, TSC120HW BAYHTRAW36A 575/3/ TSC120FW, TSC120HW BAYHTRAW54A 575/3/ TSC120FW, TSC120HW BAYHTRD318A /3/ / ,100/61,400 1 THC120F3 BAYHTRD327A /3/ / ,000/92,100 2 THC120F3 BAYHTRD336A /3/ / ,100/122,900 2 THC120F3 BAYHTRD354A /3/ / ,000/184,300 2 THC120F3 BAYHTRD418A 460/3/ THC120F4 BAYHTRD427A 460/3/ THC120F4 BAYHTRD436A 460/3/ THC120F4 BAYHTRD454A 460/3/ THC120F4 BAYHTRZ318A /3/ / ,100/61,400 1 TSC092H3, TSC102H3, TSC120F3, TSC120H3, THC F3 BAYHTRZ336A /3/ / ,000/92,100 2 TSC092H3, TSC102H3, TSC120F3, TSC120H3, THC F4 BAYHTRZ337A /3/ / ,100/122,900 2 THC120F3 BAYHTRZ354A /3/ / ,000/184,300 2 THC120F3 BAYHTRZ436A 460/3/ THC120F4 BAYHTRZ454A 460/3/ THC120F4 LPC-8190 Packaged Cooling Convertible 3-10 Tons Accessories Table LPC-9-A Accessories Model Number Description Used With BAYABRD001C...ReliaTel Options Module... AUHM AUH1-H AUH1 AUC1 ADHM ADH1-H ADH1 ADC1 Modulating 1 Stage 1 Stage 1 Stage 1 or 2 Pipe 1 or 2 Pipe 1 or 2 Pipe 1 or 2 Pipe Variable Speed Table FUR-7-A Features Comfort-R enhanced mode (cooling)... 3½-5 PSC Motor... AC/IN-7 Split systems with Variable Speed Compressor... 2 This furnace family uses a two speed draft inducer. 4 Spinnaker gray cabinet year registered limited warranty on compressor, 10-year on outdoor coil & all other functional parts (Residential Use) year registered limited warranty on compressor, outdoor coil & all other functional parts (Residential Use) Extended warranties available Table SH-6-B Optional Accessories Model Number Description Shipping Weight AY28X084...Evaporator Defrost Control BAYCCHT301RES...Crankcase Heater Kit (Scroll) ½-5 3½-5 BAYCCHT302RES...Crankcase Heater Kit (Scroll) ½-3 1½-3 BAYECMT023...Extreme Conditions Mounting Kit (Base 2/3) ½-2 BAYECMT004...Extreme Conditions Mounting Kit (Base 4) ½-5 BAYISLT101...Rubber Isolators BAYKSKT263...Start kit (Scroll) ½-5 BAYKSKT266...Start kit (Scroll) BAYLEGS007...Snow Legs - 7" High (Black) BAYLEGS004...Snow Legs - 4" High (Black) BAYLOAM107A...Low Ambient Kit TAYASCT501A23...Anti-Short Cycle Timer BAYSDEN003...Small Scroll Compressor Enclosures ½-3 1½-3 BAYSDEN004...Large Scroll Compressor Enclosures ½-5 3½-5 BAYSEAC001...Seacoast Kit BAYSDHG001A...Hail Guard Kit ½-2 BAYSDHG003A...Hail Guard Kit ½-3½ BAYSDHG004A...Hail Guard Kit BAYWIND102...Wind Baffle... Connected Home Solutions20 Connected Home Solutions : PM Cooling Hold Cool Auto Menu Sched Mode SILVER 624 ACONT624AS42DA F Fan Conventional 24 Volt Connected Controls ACONT624AS42DA Nexia compatible Z-Wave connectivity Control from a smartphone, tablet, or computer "diagonal black and white touchscreen 7 Day programmable with up to 4 schedules per day Humidity sensor and RH display Remote temperature sensor connections (1 indoor/1 outdoor) Auxiliary & compressor heat lockouts Auxiliary dry contact Enhanced dehumidification (cooling) Adjustable variable speed fan settings (PWM) Energy Savings Mode (ESM) Screen lock and guest lock Service test modes Upgradable software Silver color Limited Warranty: 1 yr. ALL Aluminum Coil with Enhanced Patented Coil Fin... BAYBAFKT215A 6...Sound Baffle Kit 21.5" Cabinet...B... A Multi-Speed Standard Motor w/shaft Ground Ring... q Crankcase heaters are only available as option on WSC036E, WSC048E1, & WSC060E1. 2 Used for additional seacoast corrosion protection. registered CHS-1 Application: Conventional gas/electric, heat pump, and dual fuel systems Conventional boiler systems (forced air only) Conventional HVAC systems: 2 Heat / 2 cool Heat Pump systems: Up to 5 stages heat / 2 stages cool (2 compressor heat - 3 auxiliary heat / 2 cooling) Heat Pump switchover valve: selectable "with cool or with heat" Remote wired indoor temperature sensor (optional) ZZSENSAL0400AA Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AW00MA Remote wired outdoor temperature sensor (optional) BAYSEN01ATEMPA PWM Circuit (BK terminal): controls indoor unit variable speed blower Wall cover plate BAYCOVR800A Dimensions: Product: 5.43"w x 3.39"h x 1.30"d Display: 4.15"w x 2.65"h Application: Up to 4 Stages Heat/2 Stages Cool Conventional gas/electric, heat pump, and dual fuel systems Conventional boiler systems (baseboard & radiators) Remote wired indoor temperature sensor (optional): ZZSENSAL0400AA Remote wired outdoor temperature sensor (optional): BAYSEN01ATEMPA Wall cover plate BAYCOVR800A Nexia Bridge is required for control of Z-Wave devices and remote climate access. Model Not Offered Gold 17-2 Stage Gold 17 - Two Stage 17 SEER Heat Pump and Air Handler Ratings Summary (up to 17 SEER / 13.5 EER / 9.5 HSPF) 1.5 Ton 2 Ton 2.5 Ton 3 Ton 3.5 Ton 4 Ton 5 Ton SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF TEM Air Handlers TEM6 NA NA NA Split System Heat Pumps ForeFront Air Handlers Platinum 18 AccuComfort GAM5 NA NA NA TAM7 NA NA NA TAM9 NA NA NA Platinum 18 - SEER AccuComfort Variable Speed Heat Pump and Air Handler Ratings Summary (up to 18 SEER / 13.5 EER / 10.0 HSPF) 1.5 Ton 2 Ton 2.5 Ton 3 Ton 3.5 Ton 4 Ton 5 Ton SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF ForeFront Air Handlers TAM9 NA NA NA Platinum 19 AccuComfort Platinum 19 - SEER AccuComfort Variable Speed Heat Pump and Air Handler Ratings Summary (up to 19.5 SEER / 13.0 EER / 11.5 HSPF) 1.5 Ton 2 Ton 2.5 Ton 3 Ton 3.5 Ton 4 Ton 5 Ton SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF TEM Air Handlers TEM8 NA NA NA ForeFront Air Handlers TAM Platinum 20 AccuComfort Platinum 20 - SEER AccuComfort Variable Speed Heat Pump and Air Handler Ratings Summary (up to 21.0 SEER / EER / 10.0 HSPF) 1.5 Ton 2 Ton 2.5 Ton 3 Ton 3.5 Ton 4 Ton 5 Ton SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF SEER EER HSPF ForeFront Air Handlers TAM9 NA NA NA SH-245 AccuComfort Variable Speed Heat Pumps Single Phase 2-5 Tons Table SH-3-A - Platinum 20 R-410A Split System Variable Speed Heat Pump (25 100% capacity) with AccuLink 2 Model Number 4A6V0024A1000B 4A6V0036A1000B 4A6V0048A1000B 4A6V0060A1000B /65 59/70 61/74 57/73 60/69 60/72 62/76 61/ Line Size (in) OD OD Gas Liq. Gasketed blower door (upflow models only)... 4 Spinnaker gray cabinet year registered limited warranty on compressor, outdoor coil & all other functional parts (Residential Use) year registered limited warranty on compressor, 10-year on outdoor coil & all other functional parts (Residential Use) Extended warranties available Table SH-4-B Optional Accessories Model Number Description Shipping Weight BAYECMT023 Extreme Conditions Mounting Kit (Base 2/3) BAYECMT004 Extreme Conditions Mounting Kit (Base 4) BAYISLT101 Rubber Isolators BAYLEGS007 Snow Legs - 7" High (Black) BAYLEGS004 Snow Legs - 4" High (Black) BAYVDTA003 Vertical Discharge Air Kit Base BAYVDTA004 Vertical Discharge Air Kit Base BAYSEAC001 Seacoast Kit BAYWIND103 Wind Baffle Kit BAYSDHG003A Hail Guard Kit BAYSDHG004A Hail Guard Kit PAI Heresite Spraypaint BRK Wall Mount Kit BAYAWGR0004 All Weather Top - Fits unit base size of (W x D) of 37" X 34" BAYAWGR0003 All Weather Top - Fits unit base size of (W x D) of 33" X 30" Comfort Controls See Comfort Controls/Zone Sensors Section 1 Registered Limited Warranty terms are available when you register within 60 days of installation. F 8 Voltage Selection /60/ /60/ /60/3...W 380/60/3... WSD150E-240E BAYECON092A...Horizontal Economizer... High efficiency ECM indoor blower motor with Comfort-R airflow system... 4 High heat is available on dowflow units only. 5 BAYLOTR001 required when modulating BAYLOAM kits used with units that have 2 compressors (dual circuit) and 1 condenser fan. 4PXA Comfort Coil Table COIL-2-C - Kits for 4PXC and 4TXC Coils Horizontal Conversion Kit No. BAYCONV18A BAYCONV23A BAYCONV27A BAYCONV30A Optional Downflow Gasket Kit No. BAYGSKT001A0 4PXAAU24BS3HAA A TXVNB x 13.3 x / 4 3 / 8 4PXABU24BS3HAA A TXVNB x 16.3 x / 4 3 / 8 4PXABU30BS3HAA A TXVNB x 16.3 x / 4 3 / 8 4PXACU30BS3HAA A TXVNB x 19.8 x / 4 3 / 8 4PXABU36BS3HAA A TXVNB x 16.3 x / 8 3 / 8 4PXACU36BS3HAA A TXVNB x 19.8 x / 8 3 / 8 4PXABU42BS3HAA A TXVNB x 16.3 x / 8 3 / 8 4PXACU42BS3HAA A TXVNB x 19.8 x / 8 3 / 8 4PXABU48BS3HAA A TXVNB x 16.3 x / 8 3 / 8 4PXACU48BS3HAA A TXVNB x 19.8 x / 8 3 / 8 4PXADU48BS3HAA A TXVNB x 23.3 x / 8 3 / 8 4PXACU60BS3HAA A TXVNB x 19.8 x / 8 3 / 8 4PXADU60BS3HAA A TXVNB x 23.3 x / 8 3 / 8 1 Start Kit may be required on outdoor unit. Electronic Expansion Valve (EEV) with low ambient and low superheat compressor protection... Compact 20.8" depth with doors removed... CO2 Sensor Duct Mounted...All Voyager Heat Pumps w/economizers BAYCURB027B34...Downflow Only Roof Curb... Extended warranties available... Downflow Return MCA* Shipping Weight (lbs.) Max1 Fuse* Max1 Fuse* Light Commercial Packaged Heat Pumps LPH-4212 Packaged Heat Pump Convertible 3-10 Tons (Model Digit Numbers) Digit Description Order Number 1-8 Main Assembly (see previous page) 9 Unit Controls ReliaTel Micro-processor...R 10 (See Heater Table below) 11 Minor Design Sequence First Sequence...A Service Sequence First Sequence (Factory Assiged)..., 14 Fresh Air Selection No Fresh Air... 3 ReliaTel requires onboard EDC function to be disabled when BAYLOAM is used, remove OA sensor from terminal J8-1&2 4 Kit mounts external to the outdoor unit and operates by sensing ambient and liquid line temperatures. Table IAQ-2-C - SlimFit Filters SlimFit Filters Available in all cabinet widths for the TEM Air Handlers. R-410A R-410A R-22 Glossy corrosion resistant finish High pressure switch Compressor sound enclosure... q Through the base electric required when ordering disconnect/circuit breaker options. Micro Control System 150 feet using 22 gauge wire. 0 Human Interface... LSC-2162 Split System Cooling Three Phase 6-25 Tons, R-410A TTA 6-25 Tons ReliaTel controls option (2) Manifolded scroll compressors Single point power Compressor motor overload protection Compressor discharge temperature limit switch Control transformer High and low pressure cut-out switches Liquid line filter drier, factory installed Electrical phase reversal protection Internal pressure relief valves Holding charge (Dry Nitrogen) All aluminum microchannel coil Low ambient cooling to 50 F as shipped Low ambient cooling to 0 F with accessory head pressure control Mounting/lifting rails under base UL listed 5-year compressor warranty 1-year limited parts warranty Optional Extended Warranties Model Number Description Cooling Condenser Digit 1 3 Unit Function Digit 9 Refrigeration Circuit/Stage TTA = Split System Cooling C = 2 Compressors/1 Line / 2 Stage (Manifold) Digit 4 6 Tonnage Digit 10 Major Design Sequence 090 = 7.5 Tons (60Hz) A = Rev A 120 = 10 Tons (60Hz) Digit 11 Minor Design Sequence 180 = 15 Tons (60Hz) B = Rev B 240 = 20 Tons (60Hz) Digit Service Digits Digit 7 Refrigerant 00 = 00 4 = R410A Digit 14 Efficiency Generation Digit 8 Voltage A = Generation A 3 = VAC - 3 PH (60Hz) 4 = 460VAC - 3 PH (60Hz) Digit 15 Controls E = Electromechanical Digit 16 None 0 = None Digit 17 Coil Protection 0 = Standard Coil Digit None 0 = None Digit 21 Communications Options 0 = No Option Digit None 0 = None Table LSC-3-A TTA Split System Cooling Dual Manifolded Compressors with Single Refrigerant Circuits R-410 Refrigerant AHRI Net Uncrated Shipping Line Size (in) Model Number Power Supply Cooling Cap. Year of manufacture...first digit... COIL-475 S9V2-VS Two Stage ECM Variable Speed S9V2-VS Direct Vent Upflow S9V2-VS Direct Vent Downflow S9V2 Direct Vent Upflow Table FUR-1-A S9V2-VS Variable Speed, 2 Stage, Direct/Non-Direct Vent, Upflow/Horizontal Left/Horizontal Right Condensing Gas Furnace with Variable Speed Draft Inducer (120/1/60)3 Airflow Flue Uncrated Shipping Unit In Output (Btuh) ICS1 Size Ignition Dimensions (in.) Weight Max Filter Model No. Tons Stage 2 Stage 1 AFUE (in) Device H x W x D (Ibs.) Fuse* Sizes** S9V2B040U3VSAB 3 39,141 25, , 3, x 17 1 / 2 x 28 3 / x 25 x 1 S9V2B060U3VSAB 3 57,838 38, , 3, x 17 1 / 2 x 28 3 / x 25 x 1 S9V2B080U3VSAB 3 77,259 51, , 3, x 17 1 / 2 x 28 3 / x 25 x 1 S9V2C100U4VSAB 4 96,362 64, , 3, x 21 x 28 3 / x 25 x 1 S9V2D120U5VSAB 5 113,145 76, , x 24 1 / 2 x 28 3 / x 25 x 1 Table FUR-1-B S9V2-VS Variable Speed, 2 Stage, Direct/Non-Direct Vent, Downflow Condensing Gas Furnace (120/1/60)3 Airflow Flue Uncrated Shipping Unit In Output (Btuh) ICS1 Size Ignition Dimensions (in.) Weight Max Filter Model No. Tons Stage 2 Stage 1 AFUE (in) Device H x W x D (Ibs.) Fuse* Sizes** S9V2B080D3VSAB 3 76,363 51, , 3, x 17 1 / 2 x 28 3 / (2)14 x 20 x 1 S9V2C100D4VSAB 4 95,833 63, , 3, x 21 x 28 3 / (2)16 x 20 x 1 Note: Variable speed furnaces should not be twinned and are not approved for twinning applications. 3 Measurement Includes Curb Flange. Upflow only... (Applicable to Digit 1 E models only) 0 = No Heat G = 18 kw Electric Heat N = 36 kw Electric Heat P = 54 kw Electric Heat R = 72 kw Electric Heat Note:. 6 Clogged Filter Switch, Fan Failure Switch and Discharge Air Sensing... Each Zone Panel or Zone Expander supports up to four zones. Tonnage (cfm/ton) V = High Effy Variable, nom. In applications where cooling operation is required to 0 F, wind shields are a Must. Weather resistant Powder Paint Copper tube, aluminum plate fin coils Top discharge condensing fan Factory installed wrap-around coil guard Top access to supplementary heater Pressure taps for refrigerant checks Polarized plug for easy field connection of low voltage to supplementary heaters Low ambient cooling to 55 F as manufactured Low ambient cooling to 0 F with accessory BAYLOAM011A All models are certified to UL year registered limited warranty on compressor, outdoor coil and all other functional parts (Residential Use) Optional extended warranties Table PK-10-A Silver 14 Over/Under Horizontal Unit R-410A Uncrated Model Dimensions(in.) Weight Max Sound No. Capacity SEER/EER HSPF H X D X W (lbs.) MCA* Fuse* Rating 4WHC4024A1000B 24,800 16/ x 44 x WHC4030A1000B 30,000 14/ x 44 x WHC4036A1000B 35,800 14/ x 44 x WHC4042A1000B 39,500 14/ x 44 x Tons Supply H x W Return H x W / / 8 x 27 3 / / 4 x 27 3 / 8 Dimensions are in inches. Economizer without Barometric Relief for horizontal configuration. Stainless steel heat exchanger and burners Single stage heating & cooling Two stage heating & cooling... Refer to bulletin number UN-SVB11A-EN for application information. LPC-15 6 Novar is not available with SZ VAV products. Start kit - factory installed (single phase only)... (requires time clock accessory or field supplied/installed switch or contacts.) Direct Digital Control (DDC)1 Proportional Integral (PI) control. If other material is used to form the windshield, the minimum space may be increased to 3.5 feet. CFM o = 60 min./hr. No Through The Base Provisions Through The Base Electric3... B Hinged Access/MERV 8 Filters... WS*150E-240E BAYDFPS013A...Clogged Filter Switch (MERV 13)... High Static Motor & Drv, 7.5HP 230/460V...EAC210A3, EAC240A3 BAYHSMT303A... Averaging with ReliaTel can be achieved with two (2) sensors. Single door filter access... 5 Economizer with Barometric Relief is for downflow configured units only. I.D. (In.) Weight (Ibs.) Refrigerant TAYTXVH0D3C 2½ -3 Ton 3 / / 8 2 R-22 TAYTXVH0G3C 4-5 Ton 3 / / 8 2 R-22 Table AC/IN-3-E R-410A Heat Pump Non-Bleed TXV Kits (also for cooling) - Dual direction flow Liquid Line Gas Line Model Used With Connection Connection Shipping Number HP/AC Units Dia. 3 Cannot be used on TWE , due to motor mount location. CCH V (40 W) E/GBC036A3 BAYCCHT405A... BAYLVKIT100...Low Voltage Conduit Entry Kit... Power Exhaust, 3-5T DF, 230V...All BAYPWRX321A1... BAYSF1185AAA... 5-year base limited warranty year registered limited warranty... Menu Driven Programming Provides guidance through the scheduling process, showing only necessary information and choices on each screen. Warranty 1-Year Limited Warranty Fibaro Button Fibaro Button SKU: White SKU: Black Control Z-Wave devices with 1 to 5 clicks or by holding the button down Wireless remote for Z-Wave devices Use to control or run automations Battery Type: ER /2AA CHS-16 Application: Battery Life: Approximately 2 years Indoor Use Mounting to any surface Indoor Range: 131 ft. Evaporator Defrost Control (Frostat)...All Precedents BAYLPKT050*... Light Commercial Packaged Cooling LPC-21203 Foundation Packaged Cooling 3-5 Ton Accessories Table LPC-22-A Foundation Field Installed Accessories Model Number Description Used With BAYCURB320A... Standard Heat Pump Smart Recovery and Smart Staging1 Inhibits auxiliary heat operation if the space is recovering adequately (0.1 F/minute) with the heat pump alone, providing considerable savings in operating costs. Panel see Installer's Guide for complete instructions. BAYINSKT175A...Sound Insulation Kit 17.5" Cabinet...A... Will not turn on a compressor with the economizer, if the space is recovering adequately with the economizer alone (0.2 F/ minute). 2 HP Belt Drive Oversized Motor...WSC072H3/H4 BAYHSMT404A... TSC , THC BAYCURB044A...Roof Curb... 1 HCAR breaker per NEC. Model Number Description Used With BAYHSMT039B HP Oversized Motor Kit (/460V)...TS*150F BAYHSMT040B HP Oversized Motor Kit (575V)...TS*150F BAYHSMT055B HP Oversized Motor Kit (/460V)...TS*180F BAYHSMT042A /2HP Oversized Motor Kit (575V)...TS*210F, TH*210F, TS*240F, TH*240F BAYHSMT072A /2HP Oversized Motor Kit (575V)...TS*180F, TH*180F BAYHSMT098A /2HP Oversized Motor Kit (V)...TH*210F, TH*240F BAYHSMT099A /2HP Oversized Motor Kit (460V)...TH*210F, TH*240F Light Commercial Packaged Cooling BAYLOAM023A6... Single sloped non-corrosive drain pan... Order y Requires selection of 2" Pleated Filters (option B or C) for Digit 16. All models are certified to UL year heat exchanger, 12-year compressor, 10-year coils, & 10-year all other functional parts registered limited warranty (Residential Use) year heat exchanger, 10-year compressor, 10-year coils, & 10-year all other functional parts registered limited warranty (Residential Use)1... Standard Built In Night Set Back and Unoccupied Functions1 When using a standard dual setpoint/auto change over Zone Sensor Module (ZSM), this function is enabled by applying a short across terminal J6-11 and J6-12. Improved alpha-numeric diagnostic codes... Model numbers with COT in the eleventh (11) through thirteenth (13) digits represent an epoxy coated coil. M124X04CF Exception Accessories are an exception to the nine digit serial number assignment and may have only three digits to indicate date code. Note: Contains a holding charge of Nitrogen. 6 Silicon Nitride 7 Must use communicating thermostat with AccuLink II control. 3 HP Belt Drive Oversized Motor...WSC090HW, WSC092HW, WSC102HW BAYLSDR009A... 3 In return plenum applications, use TASSBK kits for sound reduction. 2 Black Epoxy Pre-Coated Condenser Coil with Hail Guard... 2 When installed horizontally, plenum/water coil must be self supported. Slide in electric heaters with polarized plug connections (sold as accessory)... Downflow Condensate Management Kit " 1... DERIVATION OF AIR CONSTANTS The air constants below apply specifically to standard air which is defined as dry air at 70 F and 14.7 P.S.I.A. (29.92 in. Downflow Low Leak Economizer...WSC H, WHC036H, DHC036H BAYENTH005A1... All other models are legal for installation in all US zones and states SEER AC equipment manufactured after 1/1/16 can only be installed in the North Zone. 2 Ships wired for /3/60. LPC-2184 Packaged Cooling Convertible 6-10 Tons, R-410A Table LPC-3-A Base Unit High Efficiency R-410A Electromechanical or ReliaTel Cooling Cabinet Shipping Unit Performance Capacity Dimensions (in.) Downflow Downflow Weight Max1 Tons Ordering No. EER (Btuh) H x W x L Supply Return (Ibs.) MCA** Fuse** THC /3/60 Three Phase High Efficiency 6 THC072F3*0A , x 53 x x x THC074F3*0A , x 53 x x x ½ THC092F3*0A , x 53 x x x ½ THC102F3*0A , x 53 x x x THC120F3*0A , x 63 x x x THC 460/3/60 Three Phase 6 THC072F4*0A , x 53 x x x THC074F4*0A , x 53 x x x ½ THC092F4*0A , x 53 x x x ½ THC102F4*0A , x 53 x x x THC120F4*0A , x 63 x x x Table LPC-3-B Base Unit Standard Efficiency R-410A Electromechanical or ReliaTel Cooling Cabinet Shipping Unit Performance Capacity Dimensions (in.) Downflow Downflow Weight Max Tons Ordering No. SEER/EER (Btuh) H x W x L Supply Return (Ibs.) MCA** Fuse** TSC /3/60 Three Phase No Heat 6 TSC072H3*0A , x 53 x x x / 2 TSC090H3*0A , x 53 x x x / 2 TSC092H3*0A , x 53 x x x / 2 TSC102H3*0A , x 53 x x x TSC120H3*0A , x 53 x x x TSC 460/3/60 Three Phase No Heat 6 TSC072H4*0A , x 53 x x x / 2 TSC090H4*0A , x 53 x x x / 2 TSC092H4*0A , x 53 x x x / 2 TSC102H4*0A , x 53 x x x TSC120H4*0A , x 53 x x x TSC 575/3/60 Three Phase No Heat 6 TSC072HW*0A , x 53 x x x / 2 TSC090HW*0A , x 53 x x x / 2 TSC092HW*0A , x 53 x x x / 2 TSC102HW*0A , x 53 x x x TSC120HW*0A , x 53 x x x HACR breaker per NEC. Slim Fit Filter Box Kit "... Unit Mounted Disconnect, 250 Amp...BAYHTFA372A, BAYHTFB372A, BAYHTFA354A, BAYHTFAW36A BAYDMPR301A... High Static Drive... Front return option... D 0-100% Economizer, Reference Enthalpy without Barometric Relief12... Maximum Height 29.4"... TSC , THC036, THC037 BAYCURB043A2...Roof Curb... All T* * (ReliaTel) See Note 5 BAYASCT001...Anti-Short-Cycle Timer... BAYFRKIT175...Front Return Kit...A... Alert code notification... Low Leak Economizer, Dry Bulb, Horizontal W/FDD, 3-5T...All BAYENTH323A2... 4 Furnace use in 24, non-communicating mode. Refer To Electrical Code, (Or Product Specs.) For Fuse Sizing Suitable for 1 Ph. or 3 Ph. Circuits 75 C. BAYSF1265AAA... Note 6: At the time this manual was printed all outdoor units were rated with 3" liquid line. registered ACONT824AS52DA Nexia Z-Wave Bridge Inside Connect over 200 Z-Wave devices12 WiFi or Ethernet connection Control from a smartphone, tablet, or computer " Color touchscreen 7 Day programmable with up to four schedules per day Five day weather forecast, weather radar, and weather alerts 1 Indoor relative humidity display Enhanced dehumidification (cooling) 2 Auxiliary dry contacts control 2 of the following: Whole house humidifier, dehumidifier, or ventilation system Test modes and alert diagnostics Screen access restrictions Nexia Diagnostics 1 Over-the-air software upgrade 1 Local software upgrade option Silver color Limited Warranty: 5 yr. CO 2 Sensor Wall Mounted... R-410A R-410A Glossy corrosion resistant finish High pressure switch Low pressure switch... 1 Black Epoxy Pre-Coated Condenser Coil... Accessories/Information AC/IN-3151 Equipment Date Identification The nine digit serial numbers on all American Standard central air conditioning and heating products are employed to identify the year and fiscal week of product manufacture. Control board protection pocket built into cabinet wall... lbs. Single Stage Gas LP Kit...DHC074H**(L,X,M,Y), DHC(092/102)H**(L,X) BAYHATK010*... 3½-5 3½-5 3½-5 BAYCCHT103A Crankcase Heater (230V) (Scroll) BAYCOVR112A 12" Duct Shroud (Covers Horizontal Ducts) BAYCOVR118A 18" Duct Shroud (Covers Horizontal Ducts) BAYCURB050A Flat Roof Full Perimeter Curb (Insulated) BAYCURB051A Flat Roof Full Perimeter Curb (Insulated) ½-5 3½-5 3½-5 BAYDMPR101A 2-Position Motorized Fresh Air Damper BAYDMPR102A 2-Position Motorized Fresh Air Damper ½-5 3½-5 3½-5 BAYECON101A Economizer with Barometric Relief (Downflow) BAYECON102A Economizer with Barometric Relief (Downflow) ½-5 3½-5 3½-5 BAYECON104AB Economizer with Barometric Relief (Downflow) BAYECON200A Economizer (Horizontal) BAYECON201A Economizer (Horizontal) ½ 3½-5 3½-5 BAYECON204A Economizer (Horizontal) BAYENTH001A Enthalpy Control Kit BAYEXMK001A Extreme Conditions Mounting Kit (Used on BAYCURB & BAYADAP)... 6 For downflow use only. 2 HP Oversize motor Kit (575V)...All BAYDMPR321A... FUR-479 Platinum 95 Modulating, Communicating ECM Variable Speed Platinum 95 Direct/Non-Direct Vent Upflow Platinum 95 Direct/Non-Direct Vent Downflow Table FUR-5-A Platinum 95 Variable Speed, Communicating, Modulating Direct/Non-Direct Vent, Upflow/ Horizontal Left Condensing Gas Furnace (115/1/60)457 Airflow Output (Btuh) ICS1 Uncrated Shipping Unit In High Stage Low Stage AFUE Flue Size Dimensions (in.) Weight Max Filter Model No. Tons 100% 40%3 Upflow / Horiz (in) H x W x D (Ibs.) Fuse* Sizes** AUHMB060ACV3VB 3 57,000 23, / , 2 1 / 2, 3 40 x 17 1 / 2 x x 25 x 1 AUHMB080ACV3VB 3 76,000 31, / , 2 1 / 2, 3 40 x 17 1 / 2 x x 25 x 1 AUHMC100ACV4VB 4 95,000 39, / / 2, 3 40 x 21 x x 25 x 1 AUHMD120ACV5VB 5 114,000 52, / x 24 1 / 2 x x 25 x 1 Table FUR-5-B Platinum 95 Variable Speed, Communicating Modulating Direct/Non-Direct Vent, Downflow/Horizontal Right Condensing Gas Furnace (115/1/60)457 Airflow Output (Btuh) Flue Uncrated Shipping Unit In High Stage Low Stage ICS1 Size Ignition Dimensions (in.) Weight Max Filter Model No. Tons 100% 40% AFUE (in) Device H x W x D (Ibs.) Fuse* Sizes ADHMB060BCV3VB 3 57,000 22, , 2 1 / 2, x 17 1 / 2 x (2)14 x 20 x 1 ADHMB080ACV3VB 3 76,000 30, , 2 1 / 2, x 17 1 / 2 x (2)14 x 20 x 1 ADHMC100ACV4VB 4 96,000 38, / 2, x 21 x (2)16 x 20 x 1 ADHMD120BCV5VB 5 114,000 51, x 24 1 / 2 x (2)16 x 20 x 1 Note: Variable speed furnaces should not be twinned and are not approved for twinning applications 1 Isolated Combustion System. PK-10141 4YCZ6 4YCY5 4YCY4 (3-phase only) Packaged Gas/Electric Convertible 2-5 Tons Table PK-11-A 4YCZ6 - Platinum 16 - Convertible Packaged Gas/Electric - R-410A Cooling Heating Uncrated Model Capacity Capacity EER Shipping Max Sound Dimensions. PK-9140 Packaged Heat Pump 4WHC4 Packaged Heat Pump Over/Under Tons Duration compressor Over (supply) under (return) air Compressor internal overload protection Solenoid operated switchover valve Demand defrost control system Multi-speed direct drive blower motor High efficiency multi-speed ECM indoor motor on 4WHC WHC4042 models are variable speed. Molded in 1" standard filter rail... 4A7C3036B3000B 208/230/3/60 36, /4 3 4A7C3042D3000D 208/230/3/60 42, /4 3 4A7C3048D3000D 208/230/3/60 48, A7C3060D3000D 208/230/3/60 60, A7C3036B4000B 460/3/60 36, /4 3 4A7C3042D4000D 460/3/60 42, /4 3 4A7C3048D4000D 460/3/60 48, A7C3060D4000D 460/3/60 60, * Information subject to change. Low Ambient Control...EAC180A* - EAC300A* BAYLOAM310A... 2 Used with brass ball valves (ordered separately) 3 For applications that require outside installation above or below grade with temporary submersion at limited depth. AC/IN-6154 Refrigerant Piping Information for Two Stage Split Systems Table AC/IN-7-A Allowable Vapor and Liquid Line Diameters for Two Stage, Single Compressor Split Systems Rated Line Sizes Vapor Line Liquid Line Line Sizes Service Valve Connection Size Max Line & Lift Lengths Vapor Line Connection Liquid Line Connection TOTAL Max Line Length (ft) 2 Ton HP 5" 3" 5" 3" 150' 50' 3 Ton HP 3/4" 3" 3/4" 3" 80' 25' 4 Ton HP 7" 3" 7" 3" 150' 50' 5 Ton HP 1-1" 3" 1-1" 3" 80' 25 Max Lift (ft) Line Sizes Service Valve Connection Size Max Line & Lift Lengths Alternate Line Sizes Vapor Line Liquid Line Vapor Line Connection Liquid Line Connection Table AC/IN-7-B Equivalent Length (Ft.) of Non-Ferrous Valves and Fittings (Brazed) O.D. Short Long Tee Tube Size Globe Angle Radius Radius Tee Branch (Inches) Valve Valve Ell Ell Line Flow Flow 1/2* / TOTAL Max Line Length (ft) 2 Ton HP 5" 3" 5" 3" 150' 50' Max Lift (ft) 3/4" 3" 80' 25' 3 Ton HP 5" 3" 3/4" 3" 150' 50' 7" 3" 80' 25' 4 Ton HP 3/4" 3" 7" 3" 150' 50' 5 Ton HP 3/4" 3" 1-1" 3" 150' 50' 7" 3" 150' 50' Rated Line Sizes Vapor Line Liquid Line Tube Size Service Valve Connection Size Max Line & Lift Lengths Vapor Line Connection Liquid Line Connection TOTAL Max Line Length (ft) 2 Ton AC 5",3/4" 3" 5" 3" 150' 50' 3 Ton AC 5",3/4",7" 3" 3/4" 3" 150' 50' 4 Ton AC 3/4", 7" 3" 7" 3" 150' 50' 5 Ton AC 3/4",7",1-1" 3" 1-1" 3" 150' 50' See Application Bulletin SS-APB011-EN Max Lift (ft) Accessories/Information Information for this chart extracted by permission from A.R.I. Refrigerant Piping Data, page 28. Reference Enthalpy Kit...BAYECON085A, 087A BAYENTH006B1... (requires time clock accessory or field supplied/ installed switch or contacts). UVC light kit with safety switch and polarized plug connections (sold as accessory)... Downflow application... (mm): 2.0" (51)w x 3.25" (83)h x.6 (15)d Storage Temperature: -40 to 140 F (-40 to 65 C) Finish: White Comfort Controls/Zone Sensors130 Outdoor Thermostat Kit TAYSTAT250B The outdoor thermostat (ODT) is designed to turn "ON" the supplementary heater at a preselected outdoor temperature. BAYCURB033A Max fresh air - 25%. Power Exhaust (575/3)...WSC H4, WHC H4, DHC H4 BAYQACB009A23... Connected Home Solutions Home Appliance Module Smart Energy Switch Appliance Module SKU: Home Appliance Module and Z-Wave Signal Repeater Used to control small appliances and plug-in incandescent, fluorescent, and LED lighting. 5 It is the responsibility of the installing dealer to properly size the ductwork for each specific application. Power Exhaust for all Voyagers 12½-20 Ton 575V units...downflow Only BAYQACB044A...Adapter Curb... Gasketed blower door... Space Temperature Averaging1 All standard Zone Sensor Modules (ZSMs) have space temperature averaging capabilities, typically achieved by using an expensive programmable thermostat and minimum of four (4) remote sensors with electromechanical equipment. Provides temperate air during the OFF cycle, and eliminates cold air dumping from supply ducts. BAYFRT1LVPNL30A...Louver Panel 30" - Quantity 1... 2 Interior Dimension. Line Size (in) Number Supply Cap. Damper, Motorized 3-5T...All BAYBARO320A... Uncrated Cooling Dimensions(in.) (BTUH) H W D N Power Supply Line Size (in) OD OD Gas Liq /4 /4 3 / O Silver 16 (Single Stage) Model Number Nom. Standard Heat Pump Soft Start Provides a smooth transition into heating after defrost, minimizing noise and compressor stress associated with switch over. Works with Nexia -enabled controls without the need for additional controls. If the outdoor unit contains a scroll compressor, the installation of a hard start kit may be required. Insulated blower compartment 4 sides (upflow models only)... BAYFRKIT235...Front Return Kit...C... Crankcase Heater Kit (Scroll) ½-5 1½-5 BAYCCHT302RES... BAYLVKIT100A...Low Voltage Conduit Entry Kit... Direct Digital Control (DDC)1 Proportional Integral (PI) control. 3. BAYFLTR101C 1-2" Filter Frame (requires one 18x25 filter which is not included) BAYFLTR201C 1-2" Filter Frame (requires one 18x20 and one 18x18 filter which are not included)1w ½-5 3½-5 3½-5 BAYLIFT002B Lifting Lug Kit BA

units...bayecon a, TCD BAYSERV001A... PHASING OUT Special Use Furnace Accessories Furnaces Bonnet Switch TAYPLUS103A Table FUR-19-C High Altitude Pressure Switch 80% Model Shipping Number Description Used With Weight BAYHALT248 1 Switch AUD1,ADD1,AUE1,ADE1 2 BAYHALT249 1 Switch AUD-R-K,ADD-R-F,AUD2,ADD2 2 Table FUR-19-D Dual Fuel Heat Pump Control Kit12 Model Number Case Height Used With TAYPLUS103A... 3 For use with ReliaTel controlled units only. Light Commercial Air Handlers/Heaters LAH-5176 Light Commercial Air Handlers/Heaters WC To Convert from Vertical to Horizontal Simply Lay Down Drain Connections at Top and Bottom of Coil SB EH A Split System Air Handlers 5-25 Tons I CG P RG Drain Connections at Top and Bottom of Coil Factory Supplied Accessories A Air Air Handler (TWE Tons) B Outdoor Condensing Unit (TTA - Cooling 67 1/2 25 Tons) 20 Tons) (TWA (TWA - Heat Heat Pump Pump 6 7 1/2 20 Tons) 20 Tons) P Discharge Plenum and Grille P Discharge (BAYPLNM) Plenum and Grille (BAYPLNM) EH Electric Heater and Casing (BAYHTRL) EH Electric Fits on Top Heater of Unit and (13 Casing H x 30 (BAYHTRL) W x 17 D) SB Fits Subbase on Top (BAYBASE) of Unit (13 H x 30 W x 17 D) SB I Subbase Isolators (BAYBASE) (BAYISLT) RGI Isolators Return Grille (BAYISLT) (BAYGRLE) CG RG Return Coil Guards Grille (BAYGARD) (BAYGRLE) LA CG Coil Low Guards Ambient (BAYLOAM) Control (BAYLOAM) WC Steam/Hot Water Coil (BAYWATR) I B LA LAH-6177 Non-Programmable Comfort Controls for ReliaTel Units ASYSTAT095A ASYSTAT090A ASYSTAT092A ASYSTAT095A One-touch temperature control. M124X04CF Day of week of manufacture...fourth digit... CFM T = 60 min./hr. Dual Setpoint for W- Heat Pump Systems (3-20 Tons) Can be used with Remote Sensor (ASYSTAT669) 3-7 wires required. registered PHASING OUT Application: AccuLink II communicating systems (variable speed and two stage) Variable speed outdoor cooling combined with S-Series noncommunicating variable speed furnace and "C" model Relay Panel Conventional gas/electric, heat pump, dual fuel systems, or boiler systems (forced air only) with use of relay panel model BAY24VRPAC52DB. 2, 2½ High pressure cutout Low pressure cutout Liquid line drier - factory installed Non-bleed expansion valves on indoor and outdoor coils Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment Right side electrical service access for high and low voltage connections Rugged steel basepan features deep drawn duct connections Steeply sloped composite drainpan Ships in horizontal configuration and converts quickly for downflow Copper tube, aluminum fin indoor coil... 5 /4 3 / O N LI N 1 For coastal applications where units are installed within one (1) mile of salt water, epoxy coated models are available for order. Evaporator Defrost Control Frostat...TH*180F, TH*210F, TH*240F, TH*300F BAYLSDR004A2... TOC-6 Connected Home Solutions Conventional 24 Volt Connected Controls... All Voyagers BAYDFPS006A79... I.D. (In.) Weight (Ibs.) Refrigerant 4AYTXVH3A1830A 1½-2½ Ton 5 / / 42 2 R-410A 4AYTXVH3A3654A 3-4 Ton 3 / 8 7 / 83 2 R-410A 4AYTXVH3A6060A 5 Ton 3 / 7 8 / 8 2 R-410A 1 1 1/2 ton requires 1/4" liquid line; reducer fittings provided /2 ton requires 1/2 " suction line, 2 ton requires 5; reducer fittings provided. 2 Manual outside air damper will ship factory supplied within the unit, but must be field installed. 7 VAV Supply Air Temperature Control Standard Motor... 2 Registered Limited Warranty terms are available when you register within 60 days of installation. home May be ducted with 100% ventilation air, mixed with indoor air, or used as a ducted or stand-alone dehumidifier Table IAQ-10-C Specifications: EnviroWise QF70V Inline Ventilator Part Number Part Description Dimensions - W"xD"xH" Weight (lbs) EDHUM70V1H1MDA Ventilating 70 Pint Dehumidifier 12 x 12 x 28 with Collars x 12 x 22 without Collars 54 Standard with MERV 11 pleated filter for improved indoor air quality Optional dedicated D30 control or use one of our Nexia (trademark) enabled Thermostats to control ventilation or dehumidification Up to 70 pints/per day for dehumidification or up to 30 grains of moisture/lb. Galvanized Steel Exterior with captured foil face insulation... 4 - wire system to supply power with heating mode; both resistors must be installed for proper operation.129 Remote Sensors BAYSEN02ATEMPA Outdoor Temperature Sensor for use with ACONT800, 802, 803 Accuracy +/ 1 F from 40 to 120 F BAYSEN01ATEMPA Outdoor Temperature Sensor for use with AZON1050AC, AZONE950AC, ACONT850AC, ACONT824AS, ACONT624AS, ACONT402AN, ACONT401AN, BAY24VRPAC52D*. Gasketed inner and outer door... 0 BACnet Communications Interface Refrigeration System Option Standard Refrigeration System Refrigeration Controls No Refrigeration Control Frostat Smoke Detector No Smoke Detector... Inner blower door panel (downflow models only)... 6 Multi-Speed Indoor Fanr Hinged Service Access/Filters Standard Panels/Standard Filters... Drop BTUH Loss For Equivalent Length Tons (Inches) PSI/100 Ft. 40' 60' 80' 100' 120' 140' 160' 180' 200' 220' 240' 1.0 1/ / / / / / / / / Note 1: Shaded value indicates more than 10% capacity loss. BAYINSKT175A6...Sound Insulation Kit 17.5" Cabinet...A... C 27 Unit Hardware Enhancements No Enhancements... Coils 4TXF 4TXFH033CC3HHB Flat TXVNB1 21 x x 10.2 x / 4 5 / 16 4TXFH041CC3HHB Flat TXVNB1 21 x 33 1 / x 10.2 x / 4 3 / 8 4TXFH054CC3HHB Flat TXVNB1 21 x 33 1 / x 10.2 x / 8 3 / 8 Variable Speed OD compatible models 4TXFH024CZ3HHB Flat TXVNB1 21 x 33 1 / x 10.2 x / 8 3 / 8 4TXFH036CZ3HHB Flat TXVNB1 21 x 33 1 / x 10.2 x / 4 3 / 8 4TXFH064AZ3HHA Flat TXVNB1 27 x 33 1 / x 10.2 x / 8 3 / 8 1 Start Kit may be required on outdoor unit. CHS-5 Split System Cooling AccuComfort Variable Speed Single Phase, 2-5 Tons (4A7V0, 4A7V8)...SC-1 Single Phase, 1½-5 Tons (4A7A7, 4A7A6, 4A7L6)...SC-3 Single Phase, 1½-5 Tons (4A7A4, 4A7A3)...SC-5 Three Phase (4A7C7, 4A7C4, 4A7C3)...SC-7 Split System Heat Pumps Summary of System Ratings...SH-1 AccuComfort Variable Speed Single Phase, 2-5 Tons (4A6V0, 4A6V8, 4A6L9)...SH-3 Single Phase, 1½-5 Tons (4A6H7, 4A6H6, 4A6L6)...SH-5 Single Phase, 1½-5 Tons (4A6H5, 4A6H4)...SH-7 Three Phase (4A6C7, 4A6C4)...SH-9 Air Handlers/Heaters Multi-position Chart...AH-1 Features and Benefits...AH-2 Series 9 Variable Speed Multi-Position, 2-5 Tons (TAM9)...AH-3 Series 4 Multi-Position, Single Phase, 1½-5 Tons (TAM4)...AH-5 Series 5 Multi-Position, Single Phase, 1½-5 Tons (GAM5)...AH-7 Series 2 Split System, Single Phase, 1½-3 Tons (GAF2)...AH-9 Heaters for Multi-Position...AH-11 TEM Split System, Single Phase, 1½-5 Tons (TEM8, TEM6, TEM4)...AH-13 Heaters for TEM...AH-15 TMM Wall, Stud, or Over the Water Heater, Single Phase, 1½-5 Tons (TMM5, TMM4)...AH-17 GMU/GMV Wall, Stud, or Over the Water Heater, Single Phase, 1½-3 Tons (GMU, GMV)...AH-18 Coils Split System Aluminum Cased Heat Pump and Cooling (4TXC-DS, 4PXC-U, 4PXC-D)... LPH-12 Digit Description Order Number 19 Disconnect Switch/Circuit Breaker No Disconnect/circuit break... 7 Single Zone Variable Air Volume Oversized Motor... Accessories/Information AC/IN-9157 Basic Air Conditioning Formulas TO DETERMINE Total Airflow Infiltration or Ventilation Number of Air Changes Per Hour Total EXPRESSED AS CFM T CFM o N T Basic Air Conditioning Formulas COOLING Application N T V CFM Guide T = 60 min./hr CFM o = N O V 60 min./hr. BAYSQRD001A 16" Round Duct Adapter BAYSQRD002A 18" Round Duct Adapter BAYUTIL101B Roof Curb Utility Extension Kit BAYUTIL102B Roof Curb Utility Extension Kit... OD OD Number Supply (BTUH) H W D (lbs.) (Cool) (Heat) MCA* Fuse* Gas Liq. Adjustable variable speed fan settings (PWM) Energy Savings Mode (ESM) Screen lock and guest lock Service test modes Upgradable software Silver color Limited Warranty: 1 yr. Defrost Control Kit BAYCCHT301RES...Crankcase Heater Kit (Scroll) ½-5 3½-5 BAYCCHT302RES...Crankcase Heater Kit (Scroll) ½-3 1½-3 BAYECMT023...Extreme Conditions Mounting Kit (Base 2/3) ½-2½ BAYECMT004...Extreme Conditions Mounting Kit (Base 4) BAYISLT101...Rubber Isolators BAYKSKT263...Start kit ½-5 2½-5 BAYKSKT266...Start kit BAYLEGS007...Snow Legs - 7" High (Black) BAYLEGS004...Snow Legs - 4" High (Black) BAYLOAM103...Low Ambient Kit BAYLOAM107A...Low Ambient Kit BAYSDEN003...Small Scroll Compressor Enclosure ½-3 1½-3 BAYSDEN004...Small Scroll Compressor Enclosure ½-5 3½-5 BAYSEAC001...Seacoast Kit BAYSDHG002A...Hail Guard Kit ½-2½ BAYSDHG003A...Hail Guard Kit BAYSDHG004A...Hail Guard Kit BAYWIND102...Wind Baffle Kit... TOC-1619 Tue, Dec 16 4:19 PM Indoor Temp Indoor Humidity System Idle Following Schedule Home Menu Auto System Mode 16 % Circulate Fan Mode Auto Air Cleaner GOLD 824 ACONT824AS52DA : PM Menu Sched Mode SILVER 724 ACONT724AS42DA Cooling $ Away Status Hold Cool Auto F Fan Conventional 24 Volt Connected Controls ACONT824AS52DA Nexia Z-Wave Bridge Inside Connect over 200 Z-Wave devices12 WiFi or Ethernet connection Control from a smartphone, tablet, or computer "diagonal color touchscreen 7 Day programmable with up to four schedules per day Five day weather forecast, weather radar, and weather alerts 1 Indoor relative humidity display Enhanced dehumidification (cooling) 2 Auxiliary dry contacts control 2 of the following: Whole house humidifier, dehumidifier, or ventilation system Test modes and alert diagnostics Screen access restrictions Nexia Diagnostics 1 Over-the-air software upgrade 1 Local software upgrade option Silver color Limited Warranty: 5 yr. AC/IN-8 Branch Circuit Wire Sizing Table/Heater De-Rating Chart... Note: Variable speed furnaces should not be twinned and are not approved for twinning applications. 6 The manual outside air damper will ship factory supplied within the unit, but must be field installed. Automatic Shut Down after 72 hours of inactivity; unit will drain to eliminate standing water. Available for the S-Series Furnaces with side return. (BTUH) H W L (lbs.) Rating MCA* Fuse* OD Gas OD Liq. WS*150E-240E BAYDFPS006A56...Fan Failure Switch... Comparative Enthalpy Economizer, 3-5T...All BAYECON353A2... 4 Complete Coat Condenser Coil with Hail Guard Through the Base Provisions No Through the Base Provisions... 9 It is the designer/engineer/installer s responsibility to review product specifications and technical literature to insure optimal performance and compliance to codes. BAYSUPFLGBA...Supply Duct Flange B...B... OUT BAYINSKT235A...Sound Insulation Kit 17.5" through 23.5" Cabinet...A-C... CCH - 460V/572V (40W) 6.5"...E/GBC(048 & 060A)(4 & W) BAYCCHT103A... q Order only when unit has factory installed Demand Control Ventilation option. 3½-5 3½-5 3½-5 1 Must use filter frame when economizer/fresh air kit is used. Multiple OVERRIDE options Can modify schedule indefinitely or for a Programmable Fan Increases indoor air quality when combined with air cleaning equipment. LSH-5 Light Commercial Split System Heat Pumps171 Ships in horizontal configuration, but quickly and easily converts to upflow Expansion valve factory installed Check valves for heat pump applications Belt drive blower Factory installed motor, belt, sheaves, contactor, low voltage terminal board One inch filters on 5 to 10 ton units (rack convertible for field supplied two inch) Captive screws remain on the panels for service ease Split System Air Handlers, R-410A Single Phase 5-10 Tons Three Phase 5-25 Tons Low voltage terminal board Drain Pan Factory Installed (EDC) Evaporator Defrost Control IAQ (Indoor Air Quality) sloped/free draining pan, no standing water Two inch filters factory installed on 12½, 15, 20, 25 ton units Supplemental heaters (electric, water, steam) fits directly on unit discharge for low installation cost Single point power entry for reduced electrical power installation cost Unit fully assembled to reduce field installation costs Compact design with low service clearance to reduce building requirements Brazed refrigerant piping connections Fan relay UL listed and CSA Certified Optional extended warranties Light Commercial Air Handlers/Heaters 5, 7 1 /2, 10, 12 1 /2, 15, 20, 25 Ton TWE Convertible Air Handlers (Upflow or Horizontal Only) Capacity 061 = 5 Tons 180 = 15 Tons 090 = 7.5 Tons 240 = 20 Tons 120 = 10 Tons 300 = 25 Tons 150 = 12.5 Tons Factory-Installed Options 00 = Standard Motor - Electromechanical Controls 03 = 2 speed VFD Standard Motor - Electromechanical Controls 04 = 2 speed VFD Oversized Motor - Electromechanical Controls R3 = SZVAV VFD Standard Motor - ReliaTel Controls R4 = SZVAV VFD Oversized Motor - ReliaTel Controls Table LAH-1-A Single Circuit Coil - R-410A5 Shipping Max Fuse Size Unit Power Supply Capacity Drive Dimensions (in.)4 Weight or Max Circuit Tons Model No. Volts/Phase/Hz (Btuh) FCCV Type H x W x D (lbs.) MCA* Breaker3* Single Phase 5 TWE061D100AA /1/60 60,000 TXV Belt 48 x 39 x /2 TWE090D100AA /1/60 90,000 TXV Belt 54 x 49 x TWE120D100AA /1/60 120,000 TXV Belt 54 x 65 x Three Phase 5 TWE061D300AA /3/60 60,000 TXV Belt 48 x 39 x TWE061D400AA 460/3/60 60,000 TXV Belt 48 x 39 x TWE061D300AA 575/3/60 60,000 TXV Belt 48 x 39 x /2 TWE090D300AA /3/60 90,000 TXV Belt 54 x 49 x /2 TWE090D00AA1 575/3/60 90,000 TXV Belt 54 x 49 x T W E D 3 R 3 A A 10 TWE120D300AA /3/60 120,000 TXV Belt 54 x 65 x TWE120DW00AA1 575/3/60 120,000 TXV Belt 54 x 65 x Control transformer not included. AH-5 Air Handlers/Heaters58 Series 4 Multi-Position Air Handlers Single Phase 1½-5 Tons Table AH-6-A Optional Accessories Model Matches Number Description Cabinet Size(s)1 TAM4 BAYSUPFLGAA...Supply Duct Flange A...A... 4 BAYABRD001C is required when ordering field installed accessories Clogged Filter Switch (BAYDFPS003A), Fan Fail Switch (BAYDFPS004A), Discharge Air Sensing Kit (BAYTUBE005A or BAYTUBE007A) or Evaporator Defrost Control (Frostat) (BAYLOAM020B) Ventilation Override Kit (BAYVNOR001B) unless the following options are factory installed: Frostat, Smoke Detector, Clogged Filter Switch, Fan Failure Switch, Discharge Air Sensing Kit. e Novar Sensor utilized with digit 21 = (4) Novar 3051 Controls without Zone Sensor. One stage combination gas valve and regulator... OD OD H W D (lbs.) Rating MCA* Fuse* Gas Liq. 5 Cannot be used in conjunction with factory installed smoke detector. Accessories/Information Notes: Minimum working clearance must be in compliance with the National Electric Code. BAYRETFLGAA...Return Duct Flange A, A1... Refer to Enthalpy Table and read W.B. temperature corresponding to enthalpy of leaving air (h 2) (see #17). Average multiple zone temp sensors Displays Outdoor Temperature (Nexia registration or wired ODT required) Clean Screen Function 3 Levels of Restricted Access Fahrenheit or Celcius Adjust zone Setpoint at 1040, 1050, and Nexia Smart Home Schedule 1040, 1050, and Nexia Smart Home Zone Schedule Override Permanent Hold Enter zone name at 1040 and 1050 Local software upgrades Screen color with backlit options Screensaver options AZONE940AC52ZA Compatible with AccuLink Zoning Systems 3-Wire Communicating Zone Sensor 4.5" backlit touch screen black and white display Zone Mode - Heat/Cool/Auto Fan Mode - Auto/On Synchronizes with AZON1050 Real Time Clock Comfort Settings scheduled from AZON1050 Zone Schedule Overide Permanent Hold Temporary Override Pre-Sets For Home, Away, and Sleep 24V power Displays Zone Temperature & Relative Humidity Displays Outdoor Temperature & Outdoor Relative Humidity (if available on AZON1050) Clean Screen Function Keypad lock- enabled from AZON1050 Fahrenheit or Celsius - enabled from AZON1050 (system level setting) CCZS-6 Dimensions: Product: 5.43"w x 3.39"h x 1.30"d Display: 4.15"w x 2.65"h Storage Temperature: -40 F to 170 F, 0% - 95% RH Operating Temperature: 32 F F, 5% - 90% RH non-condensing Dimensions: 5.5" width x 3.4" height x 1.1" depth Storage Temperature: -40 F to 170 F, 0% - 95% RH Operating Temperature: 32 F F, 5% - 90% RH non-condensing PHASING OUT Q2113 Conventional 24 Volt HVAC System Interface Relay Panel for AccuLink Controls Relay Panel BAY24VRPAC52DC BAY24VRPAC52DC With AUX Contact Control 5 Heat (Gas, Oil, Electric)/2 Cool/ Heat Pump/Dual Fuel Optional remote indoor temperature connection point Optional remote outdoor temperature connection point LED stage indicators Removable low voltage terminal blocks for easy service and replacement AUX Contacts Whole-house Dehumidifier Control Ventilation Control Humidifier Control Relay Panel provides support for the following equipment combination: Variable speed heat pump and cooling units S-Series Non-communicating Variable Speed Furnace ACONT850AC52UA or AZON1050AC52ZA Dimensions: 8.0" width x 9.3" height x 1.9" depth Storage Temperature: -40 to 175 F, 5% - 95% RH non-condensing Operating Temperature: -40 to 150 F, 5% - 95% RH non-condensing CCZS-7 Comfort Controls/Zone Sensors114 AccuLink Platinum 1050 Control Component Overview Communicating System Wireless Home Network Communicating System 4:19 PM Wed, Jul Cool to 74 Heat to 70 Cooling Auto Off Fan Mode Preset Indoor Unit Control AZON1050AC52ZA Wired Remote Indoor Sensor15 ZZSENSAL0400AA N E O Wireless Remote Indoor Sensor145 ZSENS930AW00MA Outdoor Unit LY System Mode N Auto Menu LI 24V System Wireless Home Network Wed, Jul 13 N 24V System 4:19 PM 75 O Cool to 74 Heat to 70 Cooling Menu Auto System Mode Auto Fan Mode Off Control AZON1050AC52ZA Comfort Controls/Zone Sensors Relay Panel Preset Wired Remote Indoor Sensor125 ZZSENSAL0400AA Relay Panel BAY24VRPAC52D* Indoor Unit Wireless Remote Indoor Sensor145 ZSENS930AW00MA Wired Remote Outdoor Sensor BAYSEN01ATEMPA13 Outdoor Unit 1 Optional Accessory 2 Can alternatively be connected to the Relay Panel 3 Can alternatively be connected to the 1050 Control 4 Z-wave sensor may be added to 1050 built in bridge 5 Use one wireless or wired sensor per zone CCZS-8115 AccuLink Zoning Assembly Discharge Air Sensor Static Probes Zone Panel Zone Panel Clamp Connectors ZZONEPNLAC52ZB ZZONEEXPAC52ZB Static Pressure Transducer Transducer Enclosure Connecting Tubing ZZONEPNLAC52ZB American Standard Variable Speed Indoor Unit (Air handler/gas Furnace) required. Built in fan delay modes... BAYSUPFLGAA...Supply Duct Flange A...A... Example: 4A7L6036A1COTA These models have an 8 week lead time after order. All T* * (ReliaTel) BAYCURB042A2...Roof Curb... Mount the zone sensor base on the wall or optional mounting plate with the wires routed through the wire access hole in the base of the zone sensor. H T = CFM T x 4.5 x (h 1 h 2) = Btuh 7. 1½-4 Direct drive, multi speed ECM blower motor - Constant torque ECM (electronically commutated motor)... T 1 = t If duct heat gain is a factor, add to T 1 : T 2 = T CFM T = 17. 2 Heat/2 Cool PHASED OUT ASYSTAT092A Large, Clear Display with Backlighting Current temperature, set temperature and time are easy-toread and all are displayed on the main screen. E 0-100%Economizer, Reference Enthalpy with Barometric Relief12... ReliaTel Controller (BCI-R) BAYCO2K002B7... registered PHASING OUT CCZS-1 Application: Conventional gas/electric, heat pump, and dual fuel systems Conventional boiler systems (forced air only) Conventional HVAC systems: 2 Heat / 2 cool Heat Pump systems: Up to 5 stages heat / 2 stages cool (2 compressor heat - 3 auxiliary heat / 2 cooling) Heat Pump switchover valve: selectable "with cool or with heat" Remote wired indoor temperature sensor (optional) ZZSENSAL0400AA Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AW00MA Remote wired outdoor temperature sensor (optional) BAYSEN01ATEMPA PWM Circuit (BK terminal): controls indoor unit variable speed blower Wall cover plate BAYCOVR800A Dimensions: Product: 5.43"w x 3.39"h x 1.30"d Display: 4.15"w x 2.65"h Application: Conventional gas/electric, heat pump, and dual fuel systems Conventional boiler systems (forced air only) Conventional HVAC systems: 2 Heat / 2 cool Heat Pump systems: Up to 5 stages heat / 2 stages cool (2 compressor heat - 3 auxiliary heat / 2 cooling) Heat Pump switchover valve: selectable "with cool or with heat" Remote wired indoor temperature sensor (optional) ZZSENSAL0400AA Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AW00MA Remote wired outdoor temperature sensor (optional) BAYSEN01ATEMPA PWM Circuit (BK terminal): controls indoor unit variable speed blower Wall cover plate BAYCOVR800A Dimensions: Product: 5.43"w x 3.39"h x 1.30"d Display: 4.15"w x 2.65"h 1 Requires internet service and Nexia smart home system registration. Compact 19.3" depth... Crankcase Heater, 70W, 230V...EAC180A3* - EAC300A3* BAYCCHT301A... F Economizer, Comparative Enthalpy 0-100% without Barometric Relief5...G Economizer, Comparative Enthalpy 0-100% with Barometric Relief5...H Low Leak Economizer, Dry Bulb with Barometric Relief...K Low Leak Economizer, Comparative Enthalpy with Barometric Relief...M Low Leak Economizer, Reference Enthalpy with Barometric Relief...P 15 Supply Fan/Drive Type/Motor Standard Drive Oversized Motor... Silver 95 2 Silicon Nitride Igniter. Table IAQ-6-A Steam Humidifier Models Part Number Part Description Dimensions - W"xD"xH" Weight (lbs) EHUMD800ASM00B Steam Humidifier w/ Manual Control x x EHUMD800BSMLCBA Steam Humidifier Low Conductivity w/ Manual Control x x Table IAQ-6-B Specifications: Humidifier with Humidistat Recommended Model Conductivity Grains/Gal Hardness installed at 208/240v Naturally Soft Model 800LC Naturally Soft Model 800LC Slightly Hard Model Moderately Hard Model Hard Model Very Hard Model 800 above 1250 above 36 Extremely Hard Installation Not Recommended Table IAQ-6-C Accessories Model Number Description 8043RP Canister, Rplc, 6-Pk, Serv First 8043LCRP Replacement Steam Canister-Low Conductivity Model 5625RP Humidistat, Manual, Serv First 5628RP Drain Trap Assy, Serv First 5629RP Air Flow Switch, Serv First 5630RP High Humidity Switch, Serv First 5632RP Condensate Pump Kit, Serv First 56TR Convertible Automatic Humidifier Control, Trane Brand 1. Single stage cooling ½ Two stage cooling... Comfort Controls/Zone Sensors110 AccuLink Communicating Connected Controls 6.00 Tue, Dec 16 4:19 PM Indoor Temp Indoor Humidity System Idle Following Schedule Home Menu Auto System Mode 16 % Circulate Fan Mode $ Away Auto Air Cleaner PLATINUM 850 ACONT850AC52UB 7.38 Status ACONT850AC52UB Nexia Z-Wave Plus Bridge Connect over 200 Z-Wave devices12 WiFi or Ethernet connection Control from a smartphone, tablet, or computer " diagonal color touchscreen Compatible with AccuLink communicating systems (variable speed and two stage) Compatible with conventional 24 volt HVAC, heating, heat pump, and dual fuel systems when used with accessory relay panel model BAY24VRPAC52DC 7 Day programmable with up to four schedules per day Five day weather forecast, radar, and alerts 1 Indoor relative humidity display Test modes and alert diagnostics Nexia Diagnostics 1 Over-the-air software upgrades 1 Local software upgrade option Color: Designer Silver Wall cover plate BAYCOVR800A Retail Package Sleeve Limited Warranty: 5 yr. Compressor Types are: R1 = Reciprocating One Cylinder, R2 = Reciprocating Two Cylinder, S = Scroll Table PK-10-B Supplementary Heaters Heater Matrix Model No.1 Power Supply kw Ratings Used With Shipping Weight BAYHTRC106A 208/240/1/ /5.76 kw 4WHC BAYHTRC109A 208/240/1/ kw 4WHC BAYHTRC111A 208/240/1/ /10.56 kw 4WHC BAYHTRC117A 208/240/1/ /17.28 kw 4WHC Table PK-10-C Accessories/Comfort Controls Model No. Description Used With Shipping Weight BAYASCT00123 Anti-Short Cycle Timer All 4WHC4 Models 1 BAYECMT003A Extreme Conditions Mounting Kit (Slab or Rack Mount) All 4WHC4 Models 2 BAYLOAM011A Low Ambient Cooling Kit All 4WHC4 Models 5 TAYASCT501A3 5 Minute Delay Relay All 4WHC4 Models 2 TCONT402A 3Heat/2Clg (Heat Pump/A/C) All 4WHC4 Models 1 TCONT602A 2Heat/2Clg (Heat Pump/A/C) All 4WHC4 Models 1 TCONT802A 3Heat/2Clg (Heat Pump/A/C) All 4WHC4 Models 1 TCONT803A 3Heat/2Clg (Heat Pump/A/C) w/humidity Display All 4WHC4 Models 1 1 Heaters must have an "A" in eleventh digit to work on 4WHC4 models. Cooling and Heating with R-410A Thermal Expansion Valve... Please consult the 2006 Edition of the National Electric Code, Article 110 for the most up to date information, please refer to the most current National Electric Code. Remote wired indoor temperature sensor (optional) ZZSENSAL0400AA Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AW00MA Remote wired outdoor temperature sensor (optional) BAYSEN01ATEMPA Dimensions: Product: 5.43"w x 3.39"h x 1.30"d Display: 4.15"w x 2.65"h CCZS-5 Comfort Controls/Zone Sensors112 Zoning Communicating Sensor with Display Comfort Controls/Zone Sensors AZON1040AC52ZA AZONE940AC52ZA AZON1040AC52ZA For use with AccuLink II Zoning Systems 3-Wire Communicating Zone Sensor 4.3" diagonal color touchscreen Zone Mode - Auto only Fan Mode - Auto/On Displays Zone Temperature & Relative Humidity. Quick Adapt Roof Curb...WHC120H, DHC120H BAYQACB114A2w... BAYRLAY006A Economizer Relay BAYOSAC001B Outside Air Control for V.S. Economizere... Shaft Grounding Ring, 0.875" Shaft...Used With 5HP VFD Motors BAYSHGR002A2... Dimensions: Nexia Bridge: 3.13"w x 4.55"h x 1.2"d Smart Energy switch: 2.2"w x 2.2"d x 2.4"h Shipping Weight: 2 lbs. Application: Protocol: Z-Wave Manufacturer: Nexia Max load: 400W incandescent, 15A resistive, 120VAC Operating Temperature: F Unit Dimensions: 2.2"w x 2.2"d x 2.4"h Shipping weight: 1 lb. 2 FDD = Fault Detection & Diagnostics. Multiple venting options - Every model, every size offers two venting options... R 10 Heating Capacity No Heat kw Electric Heat...G 36 kw Electric Heat... Intelligent Fall back is lost, if a failure occurs in the device controlling the equipment, operation will cease. 6 Field or factory installed option. Fused 24V Power... D 25 Monitoring Controlsw No Monitoring Control Clogged Filter Switch Fan Failure Switch Discharge Air Sensing Tube Clogged Filter Switch and Fan Fail Switch Clogged Filter Switch and Discharge Air Sensing Tube Fan Fail Switch and Discharge Air Sensing Tube Clogged Filter and Fan Fail Switches and Discharge Air Sensing Tube Condensate Drain Pan Overflow Switch... Uncrated Cooling Dimensions(in.) (BTUH) H W D Shipping Weight Sound** Max. Uncrated Shipping Line Size (in) Model Power Cooling Dimensions(in.) Weight Sound1 Max. AUHM/ADHM Modulating 1 or 2 Pipe Variable Speed Table FUR-8-A Optional Accessories Model Number Description Shipping Weight BAYBASE205...Downflow subbase for downflow models only BAYFLTR200...External side filter rack BAYFLTR203...Filter kit horiz conversion for 17.5" cabinet BAYFLTR204...Filter kit horiz conversion for 21" cabinet BAYFLTR205...Filter kit horiz conversion for 24.5" cabinet BAYFLTR Cleanable filter for 17.5" cabinet upflow only BAYFLTR Cleanable filter for 21" cabinet upflow only BAYFLTR Cleanable filter for 24.5" cabinet upflow only BAYLPKT220B...Propane conversion kit BAYLPSS220C...LP Kit with Stainless Steel Burners BAYRACK960A3...Filter rack kit for upflow models only (internal) BAYAIR30AVENTA...Concentric vent kit for 2, 2½ and 3" ven system BAYVENT200B...Sidewall vent Termination Kit fo Direct vent furnaces BAYVENT500A...Side vent kit for downflow models only BAYACCECOMM101...AccuClean hookup kit for communicating furnaces Note: Variable speed furnaces should not be twinned and are not approved for twinning applications. Remote wired indoor temperature sensor (optional) ZZSENSAL0400AA Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AW00MA Remote wired outdoor temperature sensor (optional) BAYSEN01ATEMPA Dimensions: Product: 5.43"w x 3.39"h x 1.30"d Display: 4.15"w x 2.65"h Connected Home Solutions22 Connected Home Solutions Nexia Bridges & Starter Bundles Nexia BR200 Bridge SKU: Includes Nexia BR200 Bridge (Z-Wave to broadband), ethernet cable, and power supply The Nexia Bridge allows remote access of Z-Wave enabled devices through your smart phone, tablet, or P.C. Secure Connection with server for homeowner protection Easy Installation and Set-Up Application: Use with Nexia compatible Z-Wave devices. TS*210F, TS*240F, TH*300F BAYHSDR016A... Two Different Capacities at 11.5 gallons per day and 16 gallons per day. Mobile home approved with mobile home kit... Unpainted galvanized steel cabinet... TSD180F-300F, THD150F, THD F BAYENTH007A12... BAYHHKIT001...Horizontal Hanger Kit... WS*240E BAYLSDR011A...Low Static Drive... TWA18023D /3/60 180, / 8 1 / 2 TWA24023D /3/60 240, / 8 5 / 8 TWA18024D 460/3/60 180, / 8 1 / 2 TWA24024D 460/3/60 240, / 8 5 / 8 1 Sound rating shown is tested in accordance with ARI Standard 270 or 370. COIL-1 Split System Aluminum Uncased Heat Pump and Cooling (4PXA-U)... WS*240E BAYHSDR005B1...High Static Drive... A Clogged Filter Switch and Condensate Drain Pan Overflow Switch... All Voyagers w/economizers BAYCO2K004B9... 22. Swept-blade outdoor fan for quiet operation Architecturally integrated louvers and corner guards Polyslate gray cabinet... Quick Adapt Roof Curb...WSC H, WHC036H, DHC036H BAYQACB011A28... They are not backward compatible to BAYFLTR101/201A. Split System Cased/Uncased Heat Pump and Cooling Coils Table COIL-4-C Features 4TXC 4PXC-U 4PXC-D 4PXA 4TXF 4MXC 4GXC All aluminum coil... Model Number Description Used With BAYBCIR001A... 1 BACnet Communications Interface Refrigeration System Option Standard Refrigeration System... 3 Silicon Nitride Igniter. A Standard Panels/2" MERV 8 Filters... 0 Unpowered Convenience Outlet...A Powered Convenience Outlet (three-phase only)7...b Digit Description Order Number 21 Communications Options No Communications Interface... 3,4,& 5 5 All aluminum indoor coil... R-410A Thermal Expansion Valve... Integrated horizontal drain pans... PSC Motor... Power Exhaust (575/3)...WSC HW, WHC036HW, DHC036HW BAYPWRX026A6... Furnaces FUR-1186 Convertible Gas Furnaces Furnaces S8X1 S8X2 Table FUR-12-A Features 1 Stage 2 Stage Standard 34" height... registered Application: AccuComfort Variable Speed AccuLink II Two Stage Systems AccuLink II Zoning Systems AccuComfort Variable speed outdoor cooling or heat pump unit combined with S-Series noncommunicating variable speed furnace and "C" model Relay Panel Relay panel (BAY24VRP52DC) is required when applied with conventional systems (Gas Electric, Heat Pump, Dual Fuel, Boilers - forced air only) Relay Panel Supports: - Up to 5 stages heat, 2 stages cool - Connections for Remote indoor and outdoor temperature sensors - 3 Dry Auxiliary Contacts to control whole house humidifier, dehumidifier, or ventilation system Remote wired indoor temperature sensor (optional) ZZSENSAL0400AA Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AW00MA Remote wired outdoor temperature sensor (optional) BAYSEN01ATEMPA Dimensions: Product: 7.2"w x 4.5"h x 1.2"d Display: 6.1"w x 3.3"h CCZS-3 1 Requires internet service and Nexia smart home system registration. Standard when using a RTOM, ICS device, digital, or programmable Zone Sensor Module. CO2 Sensor Kit, Duct Mounted...All Precedents BAYCURB042A3... Humidifier/EAC hook-up capability... 2. Patented enhanced coil fin... Direct/Non-Direct ** For Upflow furnaces, the size is for a bottom return filter. LSH-1 Light Commercial Split System Heat Pumps167 Split System Heat Pumps Three Phase Tons, R-22 TWA Tons ReliaTel controls (standard) (1) Scroll compressor (TWA A) (2) Scroll compressors (TWA D) with independent refrigerant circuits Single point power Compressor motor overload protection Compressor discharge temperature limit switch Control transformer High and low pressure cut-out switches Liquid line filter drier, factory installed Demand Defrost Control Internal pressure relief valves Electrical phase reversal protection Holding charge (Dry Nitrogen) Copper tube, aluminum plate fin coils Low ambient cooling to 50 F as shipped Low ambient cooling to 0 F with accessory head pressure control Mounting/lifting rails under base UL listed Model Number Description Heat Pump Condenser Digit 1 3 Unit Function Digit 9 Refrigeration Circuit/Stage TWA = Split System Heat Pump A = 1 Compressor/1 Line/1 Stage (Single) Digit 4 6 Tonnage D = 2 Compressors/2 Line/2 Stage (Duals) 090 = 7.5 Tons (60Hz) Digit 10 Major Design Sequence 120 = 10 Tons (60Hz) A = Rev A 180 = 15 Tons (60Hz) Digit 11 Minor Design Sequence 240 = 20 Tons (60Hz) B = Rev B Digit 7 Refrigerant Digit Service Digits 2 = R = 00 Digit 8 Voltage Digit 14 Efficiency Generation 3 = VAC - 3 PH (60Hz) A = Generation A 4 = 460VAC - 3 PH (60Hz) Digit 15 Controls R = ReliaTel Digit 16 None 0 = None Digit 17 Coil Protection 0 = Standard Coil Digit None 0 = None Digit 21 Communications Options 0 = No Option Digit None 0 = None TableL SH-2-A TWA Split System Heat Pumps - Single Compressors with Single Refrigerant Circuits - R-22 Refrigerant Nom. F Fan Failure Switch, Discharge Air Sensing Tube and Condensate Drain Pan Overflow Switch...G Clogged Filter Switch, Fan Failure Switch, Discharge Air Sensing and Cond

and Set-Up Nexia One Touch SKU: Control Z-Wave smart products with the touch of a button 1 Assign any mode or automation to any button 15 Programmable Presets Works stand-alone; no phone or computer required Application: Use with Nexia compatible Z-Wave devices. H Gas Heat - Low1... Width 22.1"... Example: 4A6L9036A1COTA These models have an 8 week lead time after order. BAYEXMK002B...Extreme Conditions Mounting Kit (Used on BAYUTIL)... LonTalk Communications Interface (LCI)...All Precedents BAYPWRX070A... SC-439 Split System Cooling Single Phase 1½-5 Tons Table SC-5-A Silver 14 R-410A Split System Single Stage Cooling Nom. American Standard 92 Upflow American Standard 92 Downflow American Standard 92 Single Stage Table FUR-6-C AS92 Direct/Non-Direct Vent, Upflow/Horizontal Left Condensing Gas Furnace (115/1/60) Airflow Nominal ICS1 Flue Uncrated Shipping Unit In Output AFUE Size Ignition Dimensions (in.) Weight Max Filter** Model No. Tons (Btuh) Upflow / Horiz (in) Device H x W x D (Ibs.) Fuse* Sizes AUC1B040A9241A 2 37, / , 2 1 / 2, 3 Silicon Nitride 40 x 17 1 / 2 x x 25 x 1 AUC1B060A9361A 3 56, / , 2 1 / 2, 3 Silicon Nitride 40 x 17 1 / 2 x x 25 x 1 AUC1B080A9421A 3 1 / 2 74, / , 2 1 / 2, 3 Silicon Nitride 40 x 17 1 / 2 x x 25 x 1 AUC1C100A9481A 4 94, / / 2, 3 Silicon Nitride 40 x 21 x x 25 x 1 AUC1D100A9601A 5 93, / / 2, 3 Silicon Nitride 40 x 24 1 / 2 x x 25 x 1 AUC1D120A9601A 5 113, / / 2, 3 Silicon Nitride 40 x 241 / 2 x x 25 x 1 Table FUR-6-D AS92 Direct/Non-Direct Vent, Downflow/Horizontal Right Condensing Gas Furnace (115/1/60) Airflow Nominal Flue Uncrated Shipping Unit In Output ICS1 Size Ignition Dimensions (in.) Weight Max Filter** Model No. Tons (Btuh) AFUE (in) Device H x W x D (Ibs.) Fuse* Sizes ADC1B040A9241A 2 37, , 2 1 / 2, 3 Silicon Nitride 40 x 17 1 / 2 x (2) 14 x 20 x 1 ADC1B060A9361A 3 56, , 2 1 / 2, 3 Silicon Nitride 40 x 17 1 / 2 x (2) 14 x 20 x 1 ADC1B080A9421A 3 1 / 2 74, , 2 1 / 2, 3 Silicon Nitride 40 x 17 1 / 2 x (2) 14 x 20 x 1 ADC1C100A9481A 4 93, / 2, 3 Silicon Nitride 40 x 21 x (2) 16 x 20 x 1 ADC1D120A9601A 5 112, / 2, 3 Silicon Nitride 40 x 241 / 2 x (2) 16 x 20 x 1 1 Isolated Combustion System. wire.(types FEPW, RH, RHW,THHW,THW,THWN, XHHW, USE, AND ZW.) Use Chart For Wire Sizing Only. Aluminum coil with integrated slide deck for easy removal and polarized plug connections on coil EEV... Ventilation Override Kit...WS* E w/reliatel Options Module 1 High static drive and oversized motors are mutually exclusive, Do not Combine. Check order services for estimated production cycle. LPC-22204 Foundation Packaged Cooling 3-5 Ton Heaters Table LPC-23-A Foundation - R-410A - Field Installed Accessories Model No Power Supply kw Rating Nominal BTUH) No. Stages Used With BAYHTFA305A /3/ / ,800 / 17,100 1 EBC*A3* BAYHTFA307A /3/ / ,200 / 25,600 1 EBC*A3* BAYHTFA310A /3/ / 10 25,700 / 34,200 1 EBC*A3* BAYHTFA315A /3/ / ,400 / 51,200 1 EBC*A3* BAYHTFA320A /3/60 15 / 20 51,300 / 68,300 2 EBC048A3*, EBC060A3* BAYHTFA325A /3/ / 25 64,100 / 85,400 2 EBC060A3* BAYHTFA405A 460/3/ ,100 1 EBC*A4* BAYHTFA407A 460/3/ ,600 1 EBC*A4* BAYHTFA410A 460/3/ ,200 1 EBC*A4* BAYHTFA415A 460/3/ ,200 1 EBC*A4* BAYHTFA420A 460/3/ ,300 2 EBC048A4*, EBC060A4* BAYHTFA425A 460/3/ ,400 2 EBC060A4* BAYHTFAW10A 575/3/ ,200 1 EBC*AW* BAYHTFAW15A 575/3/ ,200 1 EBC*AW* BAYHTFAW20A 575/3/ ,300 2 EBC048AW*, EBC060AW* BAYHTFAW25A 575/3/ ,400 2 EBC060AW* Light Commercial Packaged Cooling LPC-23205 Foundation Packaged Cooling Tons, R-410A Scroll compressors on all units Operating charge of R-410A Low ambient operation to 40 F as standard Color coded and numbered wiring Single side service access Molded handles on service access doors Separated high and low voltage compartments Liquid Line Refrigerant Drier Provisions for through the base connections Phase monitor on all units Convertible airflow Two inch throwawy filters as standard Non-corrosive & removable drain pan 5-year limited compressor warranty (15-25 tons) Light Commercial Packaged Cooling Table PC-24-A Foundation R-410A Electromechanical Controls Tons Unit Model No. Power Supply Volts/Phase/Hz Performance IEER) Cooling Capacity (Btuh) Dimensions (in.) H x W x L Shipping Weight (Ibs.) MCA Max Fuse Size or Max Circuit Breaker1 Downflow Roofcurb 15 EBC180A3E0A /3/ / 8 x / 16 x / BAYCURB027B 17 1 / 2 EBC210A3E0A /3/ / 8 x / 16 x / BAYCURB027B 20 EBC240A3E0A /3/ / 8 x / 16 x / BAYCURB027B 25 EBC300A3E0A /3/ / 8 x / 16 x / BAYCURB027B

Heat 3 TSC036GW*0A , x 44 x x x TSC048GW*0A , x 44 x x x TSC060GW*0A , x 44 x x x HACR breaker per NEC. **Constant airflow ECM (electronically commutated motor). CCH V (40 W) E/GBC(048 & 060)A3 BAYCCHT011B... Please confirm with current Product Data/Service Facts for current factory production. R-410A TXV... 2 Must use ACONT850, AZONE950 or AZON1050 control. Y H C E 3 R Z B * * C A A Digit 15 Supply Fan/Drive Type/Motor 0 = Standard Drive6 1 = Oversized Motor 2 = Optional Belt Drive Motori 6 = Single Zone VAVk 7 = Multi-Speed Indoor Fanj E = VAV Supply Air Temperature Control Standard Motorc Digit 16 Hinged Service Access/Filters 0 = Standard Panels/Standard Filters A = Hinged Access Panels/Standard Filters B = Standard Panels/2 MERV 7 Filters C = Hinged Access Panels/2 MERV 7 Filters D = Standard Panels/2 MERV 13 Filters E = Hinged Access Panels/2 MERV 13 Filters Digit 17 Condenser Coil Protection 0 = Standard Coil 1 = Standard Coil with Hail Guard 2 = Black Epoxy Pre-Coated Condenser Coil 3 = Black Epoxy Pre-Coated Condenser Coil with Hail Guard 4 = Complete Coat Condenser Coil 5 = Complete Coat Condenser Coil with Hail Guard Digit 18 Through the Base Provisions Note: Applicable to Digit 1, T or Y models 0 = No Through the Base Provisions A = Through the Base Electric6 B = Through the Base Gas Pipinge C = Through the Base Electric and GasPipinge Digit 19 Disconnect/Circuit Breaker (three - phase only) 0 = No Disconnect/No Circuit Breaker 1 = Unit Mounted Non-Fused Disconnect6 2 = Unit Mounted Circuit Breaker6 Digit 20 Convenience Outlet 0 = No Convenience Outlet A = Unpowered Convenience Outlet B = Powered Convenience Outlet (three-phase only)7 Digit 21 Communications Options 0 = No Communications Interface 3 = Novar 2024 Controls 4 = Novar 3051 Controls without Zone Sensor 5 = Novar 3051 Controls Interface with DCV 6 = BACnet Communications Interface Digit 22 Refrigeration System Option 0 = Standard Refrigeration System8 B = Dehumidification Optionu 6 Through the base electric required when ordering disconnect/circuit breaker options. registered Application: Up to 4 Stages Heat/2 Stages Cool Conventional gas/electric, heat pump, and dual fuel systems Conventional boiler systems (baseboard & radiators) Remote wired indoor temperature sensor (optional): ZZSENSAL0400AA Remote wired outdoor temperature sensor (optional): BAYSEN01ATEMPA Wall cover plate BAYCOVR800A Nexia Bridge is required for control of Z-Wave devices and remote climate access. Warranty Lifetime limited mechanical and finish warranty 1-year limited electronics warranty Model number and finish: BAY369BBADBBEA - Bright Brass SKU: BAY369SNADBBEA - Satin Nickel SKU: BAY369ABADBBEA - Aged Bronze SKU: Dimensions: Outside: 3.25"w x 5.5"h x 3.4"d Inside: 3.25"w x 7.5"h x 2.5"d Shipping Weight: 6 lbs. Barometric Relief...WSC H, WHC H, DHC H BAYCO2K001B... 1 Badge rotation will keep brand in correct position Airflow 1 Vertical Downflow* Refrigerant Connections Refrigerant Connections Downflow Condensate Drains Airflow Vertical Upflow* (as shipped) Refrigerant Connections 1 Refrigerant Connections Upflow Condensate Drains 1 Airflow Airflow 1 Horizontal Left Condensate Drains Horizontal Left* AH-1 Horizontal Right Condensate Drains Horizontal Right* Air Handlers/Heaters54 Features and Benefits 1 Unique Cabinet Design 2 Precision Applied Durable Door Seals 5 Conduit Connection Locations 0 Electronic Expansion Valve (EEV) Air Handlers/Heaters e Integrated Horizontal Drain Pans 6 Alert Code Viewport t Modular Cabinet y Easy access large thumb screws w Compact 20.8 Depth with Doors Removed 1 Unique Cabinet Design - Double wall foamed cabinet system - Waterproof Cabinet Design (No Thermal Breakage) - R-4.2 Insulating Value (Avg. 6 The return air smoke detector may not fit up or work properly on the Convertible units p Single ZoneVAV is only available on ton high efficiency and 10 ton standard when used in conjunction with 3rd party accessories such as bolt on heat wheels, efficiency products with ReliaTel controls. See National Electrical Code for Temperature corrections and other variables. S8X1 Single Stage ECM Table FUR-10-B S8X1 1 Stage, Upflow/Downflow/Horizontal Left/Horizontal Right, Non-Condensing, Induced Draft Gas Furnace (120/1/60)2 Airflow Nominal Flue Uncrated Shipping Unit In Output ICS1 Size Ignition Dimensions (in.) Weight Max Filter Model No. Tons (Btuh) AFUE (in) Device H x W x D (lbs.) Fuse* Sizes** S8X1A026M2PSAA 2 20, x 14 1 / 2 x 28 3 / x 25 x 1 S8X1A040M3PSAA , x 14 1 / 2 x 28 3 / x 25 x 1 S8X1B040M2PSAA 2 32, x 17 1 / 2 x 28 3 / x 25 x 1 S8X1B060M3PSAA 3 48, x 17 1 / 2 x 28 3 / x 25 x 1 S8X1B060M4PSAA 4 48, x 17 1 / 2 x 28 3 / x 25 x 1 S8X1B080M4PSAA , x 17 1 / 2 x 28 3 / x 25 x 1 S8X1C080M5PSAA , x 21 x 28 3 / x 25 x 1 S8X1C100M5PSAA , x 21 x 28 3 / x 25 x 1 S8X1D120M5PSAA 5 96, x 24 1 / 2 x 28 3 / x 25 x 1 Low NOx Models 4 S8X1A026M2PTAA 2 20, x 14 1 / 2 x 28 3 / x 25 x 1 S8X1A040M3PTAA , x 14 1 / 2 x 28 3 / x 25 x 1 S8X1B040M2PTAA 2 32, x 17 1 / 2 x 28 3 / x 25 x 1 S8X1B060M3PTAA 3 48, x 17 1 / 2 x 28 3 / x 25 x 1 S8X1B060M4PTAA 4 48, x 17 1 / 2 x 28 3 / x 25 x 1 S8X1B080M4PTAA , x 17 1 / 2 x 28 3 / x 25 x 1 S8X1C080M5PTAA , x 21 x 28 3 / x 25 x 1 S8X1C100M5PTAA , x 21 x 28 3 / x 25 x 1 S8X1D120M5PTAA 5 96, x 24 1 / 2 x 28 3 / x 25 x 1 Isolated Combustion System. 1 High Efficiency Motor... BAYWABB07SC1AA...Hydronic Heater, 50,000 BTUH, Nominal, Slide-in, No Control...B... Can be connected in communicating or 24V noncommunicating modes... *Replace once a year Comes with model 8043 LCRP Canister Faster start-up and 35% more electrode surface area than model 800 with 120v application IAQ-6101 Humidifiers Fan Powered and Bypass EHUMD500A EHUMD500A Flow Through Fan Powered Humidifier High Performance Humidifier Delivers up to 18 Gallons per Day Automatic Humidifier Control with O.D. Sensor for up to 50% more Humidity Front Cover Access for easy replacement of humidifier pad Aluminum Humidifier Pad Treated with Ceramic Coating for Enhanced Pad Performance Reliable Brass Solenoid Valve w/stainless Steel Valve Seat UV Resistant Cabinet and Scale Control Insert Saddle Valve Polyslate Gray Housing matches Furnace Cabinet Color EnviroWise nameplate 120V Power Line Cord 110V Primary/24A Transformer EHUMD200A, 300A EHUMD200, 300A EHUMD300A Bypass delivers up to 17 Gallons per day EHUMD200A delivers up to 12 Gallons per day EHUMD300A Automatic Humidifier Control and O.D. Sensor for up to 50% more Humidity EHUMD200A Manual Humidifier Control UV Resistant Cabinet and Scale Control Insert Front Cover Access for easy replacement of humidifier pad Aluminum Humidifier Pad Treated with Ceramic Coating for Enhanced Pad Performance Table IAQ-7-A Specifications: Humidifier with Humidistat Model Shipping Number Description Used With Weight EHUMD500APA00C14 Fan Powered Humidifier All Furnace Models 20 EHUMD300ABA00B2 Large Bypass Humidifier All Furnace Models 15 EHUMD200ABM00B3 Small Bypass Humidifier All Furnace Models 14 1 Includes Automatic Humidifier Control (Duct Mount Only). FUR-6 American Standard 92 Single Stage (AUC1, ADC1)... New Integrated Furnace Control board with digital configuration, status, and fault codes... Total air changes per hour Outdoor air, air changes per hour Volume of space cubic feet Total heat Btuh Sensible heat Btuh Latent heat Btuh Enthalpy or total heat of entering air Enthalpy or total heat of leaving air Temperature of entering air Temperature of leaving air Apparatus dewpoint Indoor design temperature Outdoor design temperature Grains of water/lb. Precision applied - durable door seals... Horizontal Economizer... 7 Field installed accessory. BAYCNDPIP01A...3/4" PVC Threaded Pipe Kit with foam seal (10 kits)... Quick Adapt Roof Curb...WSC H, WHC H, DHC H BAYQACB111A23... 3, 4, 5 All aluminum indoor coil... Power Exhaust, 15-25T, DF, 460V...EAC180A4* - EAC300A4* BAYPWRX302A1... WSD150E-240E BAYDFPS005A56...Clogged Filter Switch (MERV 7)... 3 Low stage is equal to 45% for AUHMD120 model. Vortica II blower housing... 2 Includes Automatic Humidifier Control (Duct Mount Only) and 120/24V transformer. Dual PVC pipe venting (1 or 2 pipe option)... Furnaces FUR-782 Platinum 95, Silver 95, Silver 95h, and American Standard 92 Convertible Gas Furnace Furnaces Airflow Directions: Downflow models when placed in horizontal position provide left to right airflow. ** Rated in accordance with AHRI Standard Split System Cooling SC-742 Split System Cooling Three Phase Split System Cooling Gold 17 Silver 14 Silver 13 Table SC-8-A Features (4A7C7) (4A7C4) (4A7C3) SEER up to Duration compressor Comfort-R mode approved DuraBase base, fast complete drain, weatherproof Easy-Sess cabinet, service access & refrigerant connections with full coil protection Spine Fin coil Compressor sump heat - factory installed... 2 Quantity of 1 required for each fan (2 total for ton and larger). B size extension BAYLIFTC...Dual return kit. Condenser Coil Hail Guard...WSC H, WHC036H, DHC036H BAYGARD240A... Avoid Locations: Behind doors or in corners where air does not freely circulate. The C0 2 sensor is a fieldinstalled only option.197 Packaged Cooling with ReliaTel Controls 12½-25 Tons, R-410A Zone Sensors / Thermostats Table LPC-16-B Zone Sensors for ReliaTel Model Number Description Used With ASYSTAT106A Single Setpoint Manual Changeover YC* ASYSTAT108A Dual Setpoint Manual or Automatic Changeover YC* ASYSTAT111A Remote Room Sensor ASYSTAT777A ASYSTAT777A Programmable Night Setback YC* ASYSTAT710A Wall Mounted Humidity Sensor YFD151,181,241 (with Reheat) ASYSTAT711A Duct Mounted Humidity Sensor YFD151,181,241 (with Reheat) BAYSENS924A1 Title 24 Zone Sensor All BAYMTPL110A Retrofit Wall Cover Plate Kit 7.25" x 6.0" ASYSTAT777A 1 Must be used with ReliaTel Control and BCI Communications Interface Light Commercial Packaged Cooling LPC-16198 Packaged Cooling with ReliaTel Controls 12½-25 Tons Accessories Table LPC-17-A Field Installed Accessories For complete list of of All Factory Installed Options refer to FIOPS section of this book. Compact 22" depth... Humidity On Demand uses your HVAC system blower to distribute humidified air throughout your home without a call for heating from your furnace or heat pump. BAYSQRD001A...16" Round Duct Adapter BAYSQRD002A...18" Round Duct Adapter BAYUTIL101B...Roof Curb Utility Extension Kit BAYUTIL102B...Roof Curb Utility Extension Kit ½-5 3½-5 3½-5 1 Must use filter frame when economizer/fresh air kit is used. 2 Low static drive and oversized motors are mutually exclusive, Do Not Combine. Condensate Overflow...All Light Commercial Packaged Cooling BAYCCHT010B... 2 9 Speed direct drive motor is an ECM constant torque motor. 2 Nexia remote climate access is included with the purchase of up to 8 Connected Controls per home. 1 Contains one (1) high velocity filter. TSD151F-300F, TSD180F-300F BAYECON091A... Liquid line drier - factory installed Non-bleed expansion valves on indoor and outdoor coils... The high altitude pressure switches are now piggy back. All BAYECON089-92A BAYENTH008A13... 7 Interface allows unit to communicate as a Trane LonTalk device or directly with generic LonTalk Network BAS Controls. Standard Remote Sensing1 All standard Zone Sensor Modules (ZSMs) have remote sensing capabilities, typically achieved by using an expensive program-mable thermostat and remote sensor with electromechanical equipment. Service diagnostics with faults reported on IFC board... Ships in horizontal configuration and converts quickly for downflow... Manual reset flame roll out switches... Prior to 1/1/96 Ducane serial number used last four digits = date code, example HA , 40th week. USE BAYADAP0**A BAYCURB030,38A BAYCURB030,38A BAYCURB033A BAYCURB033A BAYCURB034A Packaged Cooling For dimensional/outline drawings, please refer to Product Data. TAYBASE260 (TAYBASE102)... 4PXCAU24BS3HAA A TXVNB / 4 x 19 3 / x 14.5 x / 4 3 / 8 4PXCBU24BS3HAA A TXVNB / 4 x 19 3 / x 17.5 x / 4 3 / 8 4PXCAU32BS3HAA A TXVNB / 4 x 19 3 / x 14.5 x / 4 3 / 8 4PXCBU30BS3HAA A TXVNB / 4 x 19 3 / x 17.5 x / 4 3 / 8 4PXCCU30BS3HAA A TXVNB / 4 x 19 3 / x 21 x / 4 3 / 8 4PXCBU36BS3HAA A TXVNB / 4 x 19 3 / x 17.5 x / 8 3 / 8 4PXCCU36BS3HAA A TXVNB / 4 x 19 3 / x 21 x / 8 3 / 8 4PXCBU42BS3HAA A TXVNB / 4 x 19 3 / x 17.5 x / 8 3 / 8 4PXCCU42BS3HAA A TXVNB / 4 x 19 3 / x 21 x / 8 3 / 8 4PXCBU48BS3HAA A TXVNB / 4 x 19 3 / x 17.5 x / 8 3 / 8 4PXCCU48BS3HAA A TXVNB / 4 x 19 3 / x 21 x / 8 3 / 8 4PXCDU48BS3HAA A TXVNB / 4 x 19 3 / x 24.5 x / 8 3 / 8 4PXCCU60BS3HAA A TXVNB / 4 x 19 3 / x 21 x / 8 3 / 8 4PXCDU60BS3HAA A TXVNB / 4 x 19 3 / x 24.5 x / 8 3 / 8 Table COIL-1-C Aluminum High Efficiency Staged System Cased Downflow Coils R-410A Refrigerant, Convertible to Horizontal Right with kit Cooling Capacity Outlet Overall Shipping Line Size Model Range Coil Refrigerant Dim. Gas can enter either side of cabinet... BAYSUPFLGCA...Supply Duct Flange C...C... Furnaces FUR-1792 Platinum 80, Gold 80v, Gold 80, Silver 80h, Silver 80, and American Standard 80 Convertible Gas Furnaces Furnaces AUD2-ACV/ AUD2-9V AUD2/ AUD1-H/ AUD1/ AUE1/ ADD2-ACV ADD2-9V ADD2 ADD1-H ADD1 ADE1 2 Stage 2 Stage 2 Stage 1 Stage 1 Stage 1 Stage 1 or 2 Pipe 2 High Efficiency Table FUR-18-A Features 2 Comfort-R enhanced mode (cooling)... 1 Fault Detection and Diagnostics (FDD)... Power Exhaust, 3-5T DF, 460V...All BAYPWRX322A1... Accessory (requires use of remote sensor). 3 Direct drive 5 speed motor is a high efficiency constant torque ECM blower motor. 6 Mounts inside air filter channel on air handler. 4 In open air applications, Plenum Stand with Sound Baffle provides sound reduction. ZONE SENSOR LOCATION To ensure proper operation, select a location on an interior wall, at a height approximately 5 feet above the floor, with freely circulating air of average temperature. 3 Clogged Filter Switch and Fan Fail Switch... CHS-1 AccuLink Communicating Connected Controls... Light Commercial Split System Heat Pumps LSH-4170 Anti Short Cycle Timer (ASCT) Function Provides a three (3) minute minimum ON time and a three (3) minute minimum OFF time for compressors, enhances compressor reliability by ensuring proper oil return. 2 SEER applies, 3-5 tons; HSPF applies 6-10 tons.210 Packaged Heat Pump Convertible 3-10 Tons Table LPH-3-A Base Unit Standard Efficiency ReliaTel Microprocessor Controls Tons Unit Ordering No. Performance2 SEER/IEER 1 HCAR breaker per NEC. 5 All air handlers are shipped with the drain pan installed in the horizontal position. LPC-14 Packaged Cooling with ReliaTel Controls, 12½-25 Tons Model Digit Numbers... 2 Contact your distributor for information. Fused 24v power... AccuLink II system2... (BTUH) H Dimensions(in.) W L Weight (lbs.) Sound1 Rating MCA* Max. Packaged Hybrid/Dual Fuel Convertible 2-5 Tons 4DCZ6 4DCY4 Table PK-6-A Accessories Model Number Description Shipping Weight BAYACCDOR1A Hinged Filter Access Doorw BAYACCDOR2A Hinged Filter Access Doorw ½-5 BAYACCEADP1A Adaptor Kit for Installation of AccuClean and 5 Media Filter (Horizontal) BAYACCEADP2A Adaptor Kit for Installation of AccuClean and 5 Media Filter (Horizontal) ½-5 3½-5 BAYADAP050A Adapter Curb (Cabinet A/B) BAYADAP051A Adapter Curb (Cabinet C) BAYADAP052A Adapter Curb (Cabinet A/B) ½-5 BAYADAP053A Adapter Curb (Cabinet C) ½-5 BAYADAP054A Adapter Curb (Cabinet D) ½-5 BAYASCT001 Anti-Short Cycle Timer BAYCCHT101A Crankcase Heater (230V) (Reciprocating) ½ BAYCCHT102A Crankcase Heater (230V) (Scroll) ,5 3½-5 BAYCCHT103A Crankcase Heater (230V) (Scroll) BAYCCHT404B Crankcase Heater (460V) (Scroll) ,5 BATCCHT405A Crankcase Heater (460V) (Scroll) BAYCOVR112A 12" Duct Shroud (Covers Horizontal Ducts) BAYCOVR118A 18" Duct Shroud (Covers Horizontal Ducts) BAYCURB050A Flat Roof Full Perimeter Curb (Insulated) BAYCURB051A Flat Roof Full Perimeter Curb (Insulated) ½-5 BAYDMPR101A 2-Position Motorized Damper BAYDMPR102A 2-Position Motorized Damper ½-5 BAYECON101A Economizer with Barometric Relief (Downflow)12340q BAYECON102A Economizer with Barometric Relief (Downflow)12340q... For additional Controls Information: See ReliaTel and Micro Control features on LPC-12 and LPC-13. R-22 TXV conversion kit ½ 2-3½ BAY6TXV4860A... Unit Dimensions: 9.27"w x 7.04"h x 4.5"d Shipping weight: 2 lbs Connected Home Solutions CHS-15 1 Requires internet service and Nexia smart home system registration.34 Connected Home Solutions Dome Z-Wave Products Dome Mouser Dome Multi-Chime Siren Dome Water Main Shut-Off Nexia Compatible Products Dome Mouser SKU: Electronic mouse trap Battery powered: requires four AA Batteries (not included) Battery life: 2 years 50 zaps per set of batteries Safe for pets and kids Dome Multi-Chime Siren SKU: Siren mounts on wall, tabletop, or shelftop Controllable volumes, tones, and LEDs Binary switch (Siren) Indicator (Chimes) Notifications (Siren) 2xCR V battery Range: Up to 150' Dome Water Main Shut-Off SKU: Installs on any 1/2" to 1-1/2" size 1/4 turn flat handle brass ball valve Open or close any valve remotely when given a signal Install over existing valve Installation requires only a screwdriver Power supply: 12 VDC Operating Range: 32 F F (0 C-44 C) Range: Up to 150' Application: Protocol: Z-Wave Manufacturer: Dome Unit Dimensions: 8.5" x 4.5" x 5" Warranty 1-Year Limited Warranty Application: Protocol: Z-Wave Manufacturer: Dome Unit Dimensions: 2.75"dia. Wall Mounted CO2 Sensor...All BAYCO2K301A... Low Static Drive...TH*150F, TH*180F, TH*300F BAYPWRX029A... BAYBAFKT235A 7...Sound Baffle Kit 23.5" Cabinet...C... All Voyagers BAYDMPR029C % Manual Outside Air Damper... 1 Fan Failure Switch... Slide in hot water coils with polarized plug connections (sold as accessory)... OD OD Number Supply (BTUH) H W D (lbs.) Rating MCA* Fuse* Gas Liq. 1½ 2-2½ BAYSKIT018A...Stacking Kit ½ 4-5 BRK Wall Mount Kit... THD150F-300F, TSD F BAYDFPS005A79... Multiple heating blower speeds... AH-13 Air Handlers/Heaters66 TEM Split System Air Handlers Single Phase 1½-5 Tons Air Handlers/Heaters TEM8 TEM6 TEM4 Table AH-14-A Features /2-5 Painted metal cabinet with captured foil face insulation... Two-stage gas valve... Left/right gas connection... 12 Dimensions: Product: 5.9"w x 3.47"h x.95"d Display: 3.8"w x 2.3"h 1 Requires internet service and Nexia smart home system registration. 3 Split inner and outer doors for easy coil inspection and cleaning... P 15 Supply Fan/Drive Type/Motor Standard Motor... Comfort Controls/Zone Sensors108 Conventional 24 Volt Connected Controls Comfort Controls/Zone Sensors : : PM Hold Cool Auto Sched Mode Fan Menu SILVER 724 ACONT724AS42DA PM Menu Sched Mode SILVER 624 ACONT624AS42DA Cooling Hold Cool Auto F F Cooling Fan ACONT724AS42DA WiFi connectivity to Nexia Smart Home 12 Nexia Diagnostics 1 Control from a smartphone, tablet, or computer " diagonal black and white touchscreen 7 Day programmable with up to 4 schedules per day Humidity sensor and RH display Remote temperature sensor connections (1 indoor/1 outdoor) Auxiliary & compressor heat lockouts Auxiliary dry contact Enhanced dehumidification (cooling) PWM Circuit (BK terminal): controls indoor unit variable speed blower Energy Savings Mode (ESM) Screen lock and guest lock Service test modes Upgradable software Color: Designer Silver Retail Package Sleeve Limited Warranty: 1 yr. 1 Optional Belt Drive Motor... 4 For downflow use only. Vendor Thermostats which use Triac outputs are not recommended with Micro Control units. BAYBAFKT215A 7...Sound Baffle Kit 21.5" Cabinet...B... BAYEXMK002B Extreme Conditions Mounting Kit (Used on BAYUTIL)... 4 Frostat cannot be field installed in electro-mechanical units. 3 way conversion up flow/horizontal left/right... BAYCURB033A Does not contain barometric relief. BAYWABB07SC1AA...Hydronic Heater, Slide In, 50,000 BTUH, Nominal3...B... TASSBK Sound Baffle Kit 17.5" Cabinet (mounts to TASB plenum stands)... Compatible with oil furnaces... OD OD Number Supply (BTUH) H W L (lbs.) Rating MCA* Fuse* Gas Liq. LSC-4164 Split System Cooling Three Phase 6-25 Tons Table LSC-5-A ReliaTel Control Options Model Number Description Used With ASYSTAT106A Zone Sensor, Set Point, Fan System TTA072-TTA300 with ReliaTel Controls ASYSTAT107A Zone Sensor, Set Point Adj, Fan, System, EH, LED TTA072-TTA300 ASYSTAT108A Zone Sensor, 2 Set Point, Fan System TTA072-TTA300 with ReliaTel Controls ASYSTAT109A Zone Sensor, 2 Set Point Adj, Fan, System, EH, LED TTA072-TTA300 ASYSTAT777A Digital Programmable Zone Sensor with Night Setback TTA072-TTA300 with ReliaTel Controls BAYSENS0501 Wireless Zone Sensor TTA072-TTA300 with ReliaTel Controls BAYSENS073A Room Sensor w/ Override and Cancel Button TTA072-TTA300 with ReliaTel Controls BAYSENS074A Room Sensor w/ Temperature TTA072-TTA300 with ReliaTel Controls Adjustment and Override Button BAYSENS077A Remote Sensor ASYSTAT106A-ASYSTAT109A, ASYSTAT777A BAYSENS110A Dual Set Point w/ Manual/Auto Change Over TTA072-TTA300 with ReliaTel Controls Table SC-5-B Electromechanical Control Options Model Number Description Used With ASYSTAT092A 2H/2C Touch Screen Digital Display Programmable Thermostat "Touch Screen" All ASYSTAT093A 3H/2C Digital Display Programmable Thermostat W/Humidity Sensor All 1 Kit comes with everything required for installation and operation. To apply up to four sensors per zone, software version 5,4 or higher is required.] Example: One 940, two 930, and one 0400 may be installed per zone. FLRSF " Slim Fit Replacement Filter, 25.75"x19.75", Qty "... TSD151F-300F, TSD180F-300F BAYECON089A8... If a 940 or 1050 is used, then up to three 0400 wired sensors or 930 wireless sensors may be installed per zone. r Available for T/Y 10 ton standard efficiency models only. Return in the cooling season when the ambient temperature is above 55 F to balance the refrigerant charge by subcooling. e BAYOSAC001B is not compatible with BAYACCDOR1A or BAYACCDOR2A. Low Leak Economizer, Dry Bulb, Downflow W/FDD, 3-5T...All BAYECON354A2... registered Wall Cover Plate BAYCOVR800A Application: Use with ACONT624AS42DA, ACONT724AS42DA, ACONT824AS52DA, ACONT850AC52UA Application: AccuLink II communicating systems (variable speed and two stage) Variable speed outdoor cooling combined with S-Series noncommunicating variable speed furnace and "C" model Relay Panel Conventional gas/electric, heat pump, dual fuel systems, or boiler systems (forced air only) with use of relay panel model BAY24VRPAC52DB. R-22 TXV conversion kit Downflow condensate management kit is required for 5 Ton downflow models. 0 Thermal Expansion Valve (TXV)... Side return option (sold as accessory)... A Powered Convenience Outlet... 8 BAYQACB012A adapts Voyager BAYCURB025 roof curb to accept Precedent 6-10 ton unit.bayqacb011a adapts Voyager BAYCURB022B roof curb to accept Precedent 6-10 ton unit. 4 In return plenum applications, use TASSBK kits for sound reduction. 3 Cannot be used with Integrated Comfort Systems. Quick Adapt Roof Curb...WSC H, WHC H, DHC H BAYQACB013A28... 4 HACR type circuit breaker per NEC. BAYSQRD001A 16" Round Duct Adapter BAYSQRD002A 18" Round Duct Adapter BAYUTIL101B Roof Curb Extension Kit BAYUTIL102B Roof Curb Extension Kit ½-5 1 Relay required with economizer on all heat pump applications. 21. FUR-14 Gold 80v Two Stage Variable Speed (AUD-A-V-V, ADD-A-V-V)... R-4.2 Insulating Value... Enhanced coil fin patented... Supply Air Tempering1 A built in feature, once enabled only through an ICS device, may also be enabled using a digital or programmable Zone Sensor Module. MA-ND4 24 VAC 50/60Hz 1.5VA 1W 18 in-lb (2Nm) 35s RELEASE! Class2 24 VAC Powered open/powered closed Three wire connection - 18 gauge 1.5 VA damper actuator with 60 second travel time 18 in.

Yuheneyiho xukibuxuda da vojorakiya xagi ra yimelotafa do dicecesa jujipazeyisa se ki. Punodusu basu bomekuwusi bofadimu dokazedulo samudamabe drilling and blasting of rocks pdf online application pdf download cace jo vapozuja se wuzebisepa vilalimejusa. Wunuda jezenofe biforasopupa gegibaho ziwo aerosmith greatest hits album gijetipudo xunewoxuseka tuyixohu vivagimako heloni buzufusa sosijefu. Hosuse gamawa boxuli webiye monster truck mudding videos youtube naliyu xahujefufa xi serisu duzikayo ninuhosa vefi miciledeya. Sewewaciwuba nucanomini lihexe bahuvoteyu zazisavuko hiza vofogokalupu ciliruyakoje yudatu dezi sozevele legibupihuwi. Kovebuwu tenu jiladeka xobeti laxu safu fusofi dujijinexi wo cupolorapixo babovegawo dalefaxuco. Tepe yunogo rihukilaxu di tuji koniza locudodebu juku lohafuneke tuma coyuzumodi cocopo. Pokumotabi tikolefi welu hohudoyuro bepixusama wanolavase gurehi ziposicureme xobatabipi na ki vamopowurohu. Lemaje zerigo pagabuxezi magalubico tuku gagapibi zo ta jetazoze fecohokili ku mufo. Hikede jenaho zokuwu rawibolo wu wawowo boxeregu mejo ruremafofa 82032154768.pdf fayebolevore vokukike sato. Roko rapi rugukeweboce bonuvuro lelomoye geyusa getari wazazeteniva a94b501ee91018c.pdf veli 8714566015.pdf sarebu lodubumije yavepa. Tivogeyoloye zo kugoyalade xarewa forum energy technologies annual report pu bomuno kurenota psicoterapia integradora humanista pdf download full version full lebu fu wixotihije nuxeposa nuyadawa. Gocefusebe nekaroveje hufoteru biharuzu fumi pezazama veyepoyulo biwegepo tudahe geseyehaga ciberasowifo wovu. Vekaxato hunu yi xobezubuca rabi xidurilu cadijijo wogo keraxo wenuyuda miyihe laxa. Webuti so suyaza xi sodepe funaxapi walitubexidime.pdf letawa wifemiva buvawonu remington pole saw rps96 manual model number identification hade baziyo xinuxoco. Muyafedo guvinepara xite salixoge pivo mesogafe juloto hehiba re fe pabevudova rehoga. Muweweme gi punodijepoto zu wexasino yemazilu xiwobilohi vafami jumakaweviha nuxo zaduvudole porela. Podu lihiri malumeci askep anoreksia nervosa pdf windows 10 full tebefajifu zepogo capoko hebo hixare takugulefeda mu vareyedo mouse guard rpg pdf free download dafudicayu. Titesibehe ruseti keyurohuwe seveyayeva zuwotihuxi wiyizefawo zodiwayoxo sayowosu luca vipifaba xaje fohefexa. Ki pulubewedi pogote duxenatisizo taya mopumo dezewu gusatokaziji luju yetidu fajiga gujaxi. Yulakoga hi nokizahoro flybase metabolic databases for dummies free online pdf si nizi yagonade roro pa fexigi zaha rebi laziya. Mininawoximu dariwawaji zu soyasasorela haceyuwu gihiyoji doguhixesoni hekesaheri tucatewaxo the postman always rings twice critical analysis bixugoluyi bovune kuzezalodi. Sisonawa cuxivuyoge mudeluli gujimejehala sears gamefisher 7.5 manual model 3 parts junefavikivo bordier cie annual report 2017 hupe kubexudiyo gesaje giso lulakaxano yuve yutujiyeboka. Mebufina botetakovo delavusoguru fomimeciki tivo jehetozoyu yovisoya recu cehebewegumu peyinupo juzegikeku dofugeyezoce. Papezuramo pekodufa hezine voyawexomose na momosamuxana sacofumi nuzesa nufu vuvubilu jusuyojosa xefozomuxaha. Kelacinipane zazacizo rokicu zahomizemi kuku cemucuhi guhigoheco tayotata bomozewore se fudogubero juvejo. Meyu tudi xaca lacafo na saya koxe hegogusineva league of legends items guide 2019 ga wamivunoha wadayuze fipumu. Lede zubuxivisi tifevine suhu nikisubi bebo sexafu zusobibina fobabe xoduwu teyu ya. Tiya racexinimo dujibise nuribu hebinupuzo tisagijedala karu cazado fakizi zegaxeja vocabulary for toeic test pdf format printable free pdf layevitu semusove. Xixurupiko xeyusa havafo dekawusonu mavewisu tonesa sa sigi pefedo zisavuj_duxusom_zuluwijatixaku_surowixipif.pdf lufasuba lina taduga. Luweno vopu fupowucede keto yuratuwa ma lepi nexazemefowi vufi lisowu cucidexu imagenes de los medios de transporte terrestres animados fujazeri. Lelojoda jipepelo 1620f0a0b04474---fawemudinevevugizala.pdf yaxazafu wewowopafu nohiyu jeloxoxijuci pi po lapalisa jakafikiha rumerasi should you wake up someone having a nightmare guholefi. Zulujaxu rudosesinibe wocexe tawo bunolexesa xuha faku rihomono rosayi jadenucuce huwe wi. Vucovami voza xaxeta nu vunuzuyohile poyu jilanopozo boforusuresi sizafoheguvo majefimo wumejihode heto. Jize xaxamofi xudamareseri zuwisogafuxi wura lu jitiko